



Safety Data Sheet

Copyright,2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	34-3734-0	Version Number:	2.00
Issue Date:	17/05/2022	Supersedes Date:	25/05/2017

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

IDENTIFICATION

1.1. Product identifier

3M(TM) Scotch-Weld(TM) Low Odor Acrylic Adhesive DP8810NS Green

Product Identification Numbers

62-2854-1446-2 62-2854-1451-2 62-2854-3631-7

1.2. Recommended use and restrictions on use

Recommended use

Adhesive

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301
Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:

34-3730-8, 34-3732-4

TRANSPORT INFORMATION

This product is a kit that consists of two or more different regulated materials packed in the same outer packaging (ship unit). The transportation classifications of the individual components appear in Section 14 of the attached SDSs.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current

regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my



Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	34-3730-8	Version Number:	3.00
Issue Date:	20/12/2022	Supersedes Date:	03/05/2021

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP8810NS Green and Low Odor Acrylic Adhesive 8810NS Green, Part B

Product Identification Numbers

62-2854-8531-4 62-2854-9531-3

1.2. Recommended use and restrictions on use

Recommended use

Adhesive, Activator for 2-part acrylic adhesive

For Industrial or Professional use only

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301
Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

Reproductive Toxicity: Category 1B.

Chronic Aquatic Toxicity: Category 3.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark |Health Hazard |

Pictograms



Hazard Statements:

H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H360 May damage fertility or the unborn child.

 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P201 Obtain special instructions before use.
 P280E Wear protective gloves.
 P281 Use personal protective equipment as required.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308 + P313 IF exposed or concerned: Get medical advice/attention.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Tetrahydrofurfuryl Methacrylate	2455-24-5	25 - 45
Butadiene-Acrylonitrile Polymer	9003-18-3	1 - 20
Hydroxyethyl Methacrylate	868-77-9	1 - 20
Isobornyl Methacrylate	7534-94-3	1 - 20
Fillers	Trade Secret	1 - 20
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	41637-38-1	0.1 - 10
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonooxy)-	95175-93-2	< 3
Tetrahydrofurfuryl alcohol	97-99-4	< 1
Copper Naphthenates	1338-02-9	< 0.1

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Oxides of Nitrogen	During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by

a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
COPPER COMPOUNDS	1338-02-9	ACGIH	TWA(as Cu, fume):0.2 mg/m ³ ;TWA(as Cu dust or mist):1 mg/m ³	
Fillers	Trade Secret	ACGIH	TWA(respirable fraction):2 mg/m ³	A4: Not class. as human carcin
Fillers	Trade Secret	Malaysia OELs	TWA (proposed)(respirable fraction)(8 hours):2 mg/m ³	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the

results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of the following material(s) may be used: Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Paste
Color	White
Odor	Acrylate
Odor threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	Not Applicable
Boiling point/Initial boiling point/Boiling range	>=37.8 °C
Flash Point	> 93.3 °C [Test Method: Closed Cup]
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	No Data Available
Vapor Density and/or Relative Vapor Density	No Data Available
Density	1.13 g/ml
Relative Density	1.13 [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity/Kinematic Viscosity	100,000 - 125,000 mPa-s
Volatile Organic Compounds	No Data Available
Percent volatile	No Data Available
VOC Less H2O & Exempt Solvents	4.8 g/l [Details: when used as intended with Part A]
VOC Less H2O & Exempt Solvents	612 g/l [Details: as supplied]
VOC Less H2O & Exempt Solvents	0.5 % [Details: when used as intended with Part A]
Molecular weight	Not Applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Amines

Strong acids

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

May cause additional health effects (see below).

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Tetrahydrofurfuryl Methacrylate	Ingestion	Rat	LD50 4,000 mg/kg
Tetrahydrofurfuryl Methacrylate	Dermal	similar health hazards	LD50 estimated to be 2,000 - 5,000 mg/kg
Hydroxyethyl Methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Hydroxyethyl Methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
Butadiene-Acrylonitrile Polymer	Dermal	Rabbit	LD50 > 15,000 mg/kg
Butadiene-Acrylonitrile Polymer	Ingestion	Rat	LD50 > 30,000 mg/kg
Isobornyl Methacrylate	Dermal	Rabbit	LD50 > 3,000 mg/kg
Isobornyl Methacrylate	Ingestion	Rat	LD50 > 2,000 mg/kg
Fillers	Dermal		LD50 estimated to be > 5,000 mg/kg
Fillers	Ingestion	Human	LD50 > 15,000 mg/kg
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	Dermal	Rat	LD50 > 2,000 mg/kg
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	Ingestion	Rat	LD50 > 35,000 mg/kg
Poly[oxy(methyl-1,2-ethanediyl)], a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly[oxy(methyl-1,2-ethanediyl)], a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
Tetrahydrofurfuryl alcohol	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Tetrahydrofurfuryl alcohol	Inhalation-Vapor (4 hours)	Rat	LC50 > 3.1 mg/l
Tetrahydrofurfuryl alcohol	Ingestion	Rat	LD50 > 2,000 mg/kg
Copper Naphthenates	Dermal	similar compounds	LD50 > 2,000 mg/kg
Copper Naphthenates	Ingestion	similar compounds	LD50 >300, < 2,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value

Tetrahydrofurfuryl Methacrylate	Rabbit	No significant irritation
Hydroxyethyl Methacrylate	Rabbit	Minimal irritation
Butadiene-Acrylonitrile Polymer	Professional judgement	No significant irritation
Isobornyl Methacrylate	Rabbit	Mild irritant
Fillers	Professional judgement	No significant irritation
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	Rabbit	Minimal irritation
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonooxy)-	Not available	Irritant
Tetrahydrofurfuryl alcohol	Rabbit	No significant irritation
Copper Naphthenates	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Tetrahydrofurfuryl Methacrylate	Rabbit	No significant irritation
Hydroxyethyl Methacrylate	Rabbit	Moderate irritant
Butadiene-Acrylonitrile Polymer	Professional judgement	No significant irritation
Isobornyl Methacrylate	Rabbit	Mild irritant
Fillers	Professional judgement	No significant irritation
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	Rabbit	No significant irritation
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonooxy)-	Not available	Corrosive
Tetrahydrofurfuryl alcohol	Rabbit	Severe irritant
Copper Naphthenates	In vitro data	No significant irritation

Sensitization:

Skin Sensitization

Name	Species	Value
Tetrahydrofurfuryl Methacrylate	In vitro data	Sensitizing
Hydroxyethyl Methacrylate	Human and animal	Sensitizing
Isobornyl Methacrylate	Guinea pig	Not classified
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	Guinea pig	Not classified
Tetrahydrofurfuryl alcohol	Mouse	Not classified
Copper Naphthenates	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Tetrahydrofurfuryl Methacrylate	In Vitro	Not mutagenic

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP8810NS Green and Low Odor Acrylic Adhesive 8810NS Green, Part B

Hydroxyethyl Methacrylate	In vivo	Not mutagenic
Hydroxyethyl Methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	In Vitro	Not mutagenic
Tetrahydrofurfuryl alcohol	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Fillers	Inhalation	Multiple animal species	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Tetrahydrofurfuryl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 300 mg/kg/day	29 days
Tetrahydrofurfuryl Methacrylate	Ingestion	Toxic to female reproduction	Rat	NOAEL 120 mg/kg/day	premating into lactation
Tetrahydrofurfuryl Methacrylate	Ingestion	Toxic to development	Rat	NOAEL 120 mg/kg/day	premating into lactation
Hydroxyethyl Methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Hydroxyethyl Methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
Hydroxyethyl Methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
Tetrahydrofurfuryl alcohol	Ingestion	Toxic to female reproduction	Rat	NOAEL 50 mg/kg/day	premating into lactation
Tetrahydrofurfuryl alcohol	Dermal	Toxic to male reproduction	Rat	NOAEL 100 mg/kg/day	13 weeks
Tetrahydrofurfuryl alcohol	Ingestion	Toxic to male reproduction	Rat	NOAEL 150 mg/kg/day	47 days
Tetrahydrofurfuryl alcohol	Inhalation	Toxic to male reproduction	Rat	NOAEL 0.6 mg/l	90 days
Tetrahydrofurfuryl alcohol	Ingestion	Toxic to development	Rat	NOAEL 50 mg/kg/day	premating into lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Poly[oxy(methyl-1,2-ethanediy)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Tetrahydrofurfuryl alcohol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Tetrahydrofurfuryl Methacrylate	Ingestion	hematopoietic system nervous system	Not classified	Rat	NOAEL 300 mg/kg/day	29 days
Fillers	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure

Fillers	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
Tetrahydrofurfuryl alcohol	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.2 mg/l	90 days
Tetrahydrofurfuryl alcohol	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.6 mg/l	90 days
Tetrahydrofurfuryl alcohol	Inhalation	eyes	Not classified	Rat	NOAEL 2.1 mg/l	90 days
Tetrahydrofurfuryl alcohol	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 69 mg/kg/day	91 days
Tetrahydrofurfuryl alcohol	Ingestion	immune system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 150 mg/kg/day	28 days
Tetrahydrofurfuryl alcohol	Ingestion	endocrine system kidney and/or bladder	Not classified	Rat	NOAEL 600 mg/kg/day	28 days
Tetrahydrofurfuryl alcohol	Ingestion	liver eyes	Not classified	Rat	NOAEL 781 mg/kg/day	91 days
Tetrahydrofurfuryl alcohol	Ingestion	heart nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	28 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Tetrahydrofurfuryl Methacrylate	2455-24-5	Fathead Minnow	Experimental	96 hours	LC50	34.7 mg/l
Tetrahydrofurfuryl Methacrylate	2455-24-5	Green algae	Experimental	72 hours	ErC50	>100 mg/l
Tetrahydrofurfuryl Methacrylate	2455-24-5	Green algae	Experimental	72 hours	ErC10	100 mg/l
Tetrahydrofurfuryl Methacrylate	2455-24-5	Water flea	Experimental	21 days	NOEC	37.2 mg/l
Butadiene-Acrylonitrile Polymer	9003-18-3	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Fillers	Trade Secret	Water flea	Experimental	48 hours	LC50	>1,100 mg/l
Hydroxyethyl	868-77-9	Turbot	Analogous	96 hours	LC50	833 mg/l

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP8810NS Green and Low Odor Acrylic Adhesive 8810NS Green, Part B

Methacrylate			Compound			
Hydroxyethyl Methacrylate	868-77-9	Fathead Minnow	Experimental	96 hours	LC50	227 mg/l
Hydroxyethyl Methacrylate	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l
Hydroxyethyl Methacrylate	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
Hydroxyethyl Methacrylate	868-77-9	Green algae	Experimental	72 hours	NOEC	160 mg/l
Hydroxyethyl Methacrylate	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
Hydroxyethyl Methacrylate	868-77-9	N/A	Experimental	16 hours	EC0	>3,000 mg/l
Hydroxyethyl Methacrylate	868-77-9	N/A	Experimental	18 hours	LD50	<98 mg per kg of bodyweight
Isobornyl Methacrylate	7534-94-3	Green algae	Experimental	72 hours	EC50	2.3 mg/l
Isobornyl Methacrylate	7534-94-3	Water flea	Experimental	48 hours	EC50	1.1 mg/l
Isobornyl Methacrylate	7534-94-3	Zebra Fish	Experimental	96 hours	LC50	1.8 mg/l
Isobornyl Methacrylate	7534-94-3	Green algae	Experimental	72 hours	EC10	0.751 mg/l
Isobornyl Methacrylate	7534-94-3	Water flea	Experimental	21 days	NOEC	0.233 mg/l
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	41637-38-1	Activated sludge	Estimated	3 hours	EC50	>1,000 mg/l
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	41637-38-1	Green algae	Estimated	72 hours	EL50	>100 mg/l
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	41637-38-1	Water flea	Estimated	48 hours	EL50	>100 mg/l
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	41637-38-1	Zebra Fish	Estimated	96 hours	LL50	>100 mg/l
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	95175-93-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Tetrahydrofurfuryl alcohol	97-99-4	Green algae	Experimental	72 hours	EC50	>100 mg/l
Tetrahydrofurfuryl alcohol	97-99-4	Medaka	Experimental	96 hours	LC50	>100 mg/l
Tetrahydrofurfuryl alcohol	97-99-4	Water flea	Experimental	48 hours	EC50	>100 mg/l
Tetrahydrofurfuryl alcohol	97-99-4	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Tetrahydrofurfuryl alcohol	97-99-4	Water flea	Experimental	21 days	NOEC	>100 mg/l
Copper Naphthenates	1338-02-9	Green algae	Estimated	72 hours	EC50	0.629 mg/l
Copper Naphthenates	1338-02-9	Water flea	Estimated	48 hours	EC50	0.0756 mg/l
Copper Naphthenates	1338-02-9	Zebra Fish	Estimated	96 hours	LC50	0.0702 mg/l
Copper	1338-02-9	Algae or other	Estimated	N/A	NOEC	0.132 mg/l

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP8810NS Green and Low Odor Acrylic Adhesive 8810NS Green, Part B

Naphthenates		aquatic plants				
Copper Naphthenates	1338-02-9	Fathead Minnow	Estimated	32 days	EC10	0.0354 mg/l
Copper Naphthenates	1338-02-9	Water flea	Estimated	21 days	NOEC	0.0756 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Tetrahydrofurfuryl Methacrylate	2455-24-5	Experimental Biodegradation	28 days	Biological Oxygen Demand	75 %BOD/ThOD (< 10 day window)	OECD 301F - Manometric Respiro
Butadiene-Acrylonitrile Polymer	9003-18-3	Data not available/insufficient	N/A	N/A	N/A	N/A
Fillers	Trade Secret	Data not available/insufficient	N/A	N/A	N/A	N/A
Hydroxyethyl Methacrylate	868-77-9	Experimental Biodegradation	28 days	Biological Oxygen Demand	84 %BOD/COD	OECD 301D - Closed Bottle Test
Hydroxyethyl Methacrylate	868-77-9	Experimental Hydrolysis		Hydrolytic half-life basic pH	10.9 days (t 1/2)	OECD 111 Hydrolysis func of pH
Isobornyl Methacrylate	7534-94-3	Experimental Biodegradation	28 days	Carbon dioxide evolution	70 %CO2 evolution/THCO2 evolution	OECD 310 CO2 Headspace
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	41637-38-1	Experimental Biodegradation	28 days	Percent degraded	24 %degraded	
Poly[oxy(methyl-1,2-ethanediy)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	95175-93-2	Data not available/insufficient	N/A	N/A	N/A	N/A
Tetrahydrofurfuryl alcohol	97-99-4	Experimental Biodegradation	28 days	Biological Oxygen Demand	92 %BOD/ThOD	OECD 301C - MITI (I)
Tetrahydrofurfuryl alcohol	97-99-4	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	>1 years (t 1/2)	OECD 111 Hydrolysis func of pH
Copper Naphthenates	1338-02-9	Data not available/insufficient	N/A	N/A	N/A	N/A

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Tetrahydrofurfuryl Methacrylate	2455-24-5	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	1.76	OECD 117 log Kow HPLC method
Butadiene-Acrylonitrile Polymer	9003-18-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Fillers	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydroxyethyl Methacrylate	868-77-9	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	0.42	OECD 107 log Kow shke flask mtd
Isobornyl Methacrylate	7534-94-3	Modeled Bioconcentration		Bioaccumulation Factor	39	Catalogic™
Isobornyl Methacrylate	7534-94-3	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	5.09	OECD 117 log Kow HPLC method
Bisphenol A	41637-38-1	Estimated		Bioaccumulation	6.6	

polyethylene glycol diether dimethacrylate (polymer)		Bioconcentration		Factor		
Poly[oxy(methyl-1,2-ethanediyl)], a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonooxy)-	95175-93-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Tetrahydrofurfuryl alcohol	97-99-4	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	-0.11	OECD 107 log Kow shke flsk mtd
Copper Naphthenates	1338-02-9	Estimated BCF - Fish	42 days	Bioaccumulation Factor	≤27	OECD305-Bioconcentration

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Not hazardous for transportation.

Marine Transport (IMDG)

UN Number:None assigned.

Proper Shipping Name:None assigned.

Technical Name:None assigned.

Hazard Class/Division:None assigned.

Subsidiary Risk:None assigned.

Packing Group:None assigned.

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number:None assigned.

Proper Shipping Name:None assigned.

Technical Name:None assigned.

Hazard Class/Division:None assigned.

Subsidiary Risk:None assigned.

Packing Group:None assigned.

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my



Safety Data Sheet

Copyright, 2022, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	34-3732-4	Version Number:	3.00
Issue Date:	20/12/2022	Supersedes Date:	17/05/2022

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP8810NS Green, Part A

1.2. Recommended use and restrictions on use

Recommended use

Adhesive

For Industrial or Professional use only

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301 Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Skin Sensitizer: Category 1.

Chronic Aquatic Toxicity: Category 3.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms

**Hazard Statements:**

- H317 May cause an allergic skin reaction.
- H412 Harmful to aquatic life with long lasting effects.

Precautionary statements**Prevention:**

- P280E Wear protective gloves.

Response:

- P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Disposal:

- P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Dibenzoate Propanol	27138-31-4	50 - 80
Acrylate Polymer	25101-28-4	5 - 30
Catalyst (NJTS Reg. No. 04499600-6922)	Trade Secret	1 - 20
Organic Peroxide	13122-18-4	1 - 10

SECTION 4: First aid measures

4.1. Description of first aid measures**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Hydrocarbons
Carbon monoxide
Carbon dioxide

Condition

During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limits**

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. When only incidental contact is anticipated, alternative glove material(s) may be used. If contact with the glove does occur, remove immediately and replace with a set of new gloves. For incidental contact, gloves made of nitrile rubber are recommended. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Liquid
Specific Physical Form:	Paste
Color	Blue
Odor	Hydrocarbon
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point/Freezing point	<i>Not Applicable</i>
Boiling point/Initial boiling point/Boiling range	> 93.3 °C
Flash Point	> 93.3 °C [Test Method: Closed Cup]
Evaporation rate	<i>No Data Available</i>

Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	No Data Available
Vapor Density and/or Relative Vapor Density	No Data Available
Density	1.08 g/ml
Relative Density	1.08 [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity/Kinematic Viscosity	20,000 mPa-s
Volatile Organic Compounds	No Data Available
Percent volatile	No Data Available
VOC Less H2O & Exempt Solvents	4.8 g/l [Details:when used as intended with Part B]
VOC Less H2O & Exempt Solvents	0.5 % [Details:when used as intended with Part B]
VOC Less H2O & Exempt Solvents	59.4 g/l [Details:as supplied]
Molecular weight	Not Applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat
Sparks and/or flames

10.5. Incompatible materials

Amines
Strong acids
Strong bases
Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be

relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Dibenzoate Propanol	Dermal	Rat	LD50 > 2,000 mg/kg
Dibenzoate Propanol	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 200 mg/l
Dibenzoate Propanol	Ingestion	Rat	LD50 3,295 mg/kg
Acrylate Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Acrylate Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Catalyst (NJTS Reg. No. 04499600-6922)	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Catalyst (NJTS Reg. No. 04499600-6922)	Ingestion	Rat	LD50 > 2,000 mg/kg
Organic Peroxide	Dermal	Rat	LD50 > 2,000 mg/kg
Organic Peroxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.8 mg/l
Organic Peroxide	Ingestion	Rat	LD50 12,905 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Dibenzoate Propanol	Rabbit	No significant irritation
Organic Peroxide	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Dibenzoate Propanol	Rabbit	No significant irritation

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP8810NS Green, Part A

Organic Peroxide	Rabbit	No significant irritation
------------------	--------	---------------------------

Sensitization:**Skin Sensitization**

Name	Species	Value
Dibenzoate Propanol	Guinea pig	Not classified
Catalyst (NJTS Reg. No. 04499600-6922)	Mouse	Not classified
Organic Peroxide	Guinea pig	Sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Dibenzoate Propanol	In Vitro	Not mutagenic
Catalyst (NJTS Reg. No. 04499600-6922)	In Vitro	Not mutagenic

Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Dibenzoate Propanol	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Dibenzoate Propanol	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Dibenzoate Propanol	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Catalyst (NJTS Reg. No. 04499600-6922)	Ingestion	nervous system	Not classified	Rat	NOAEL 2,000 mg/kg	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Dibenzoate Propanol	Ingestion	hematopoietic system liver	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 3: Harmful to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Dibenzoate Propanol	27138-31-4	Fathead Minnow	Experimental	96 hours	LC50	3.7 mg/l
Dibenzoate Propanol	27138-31-4	Green algae	Experimental	72 hours	EL50	4.9 mg/l
Dibenzoate Propanol	27138-31-4	Water flea	Experimental	48 hours	EL50	19.31 mg/l
Dibenzoate Propanol	27138-31-4	Green algae	Experimental	72 hours	EC10	0.89 mg/l
Acrylate Polymer	25101-28-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Catalyst (NJTS Reg. No. 04499600-6922)	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Organic Peroxide	13122-18-4	Activated sludge	Experimental	3 hours	NOEC	26.3 mg/l
Organic Peroxide	13122-18-4	Green algae	Experimental	N/A	EC50	0.51 mg/l
Organic Peroxide	13122-18-4	Rainbow Trout	Experimental	N/A	LC50	7 mg/l
Organic Peroxide	13122-18-4	Water flea	Experimental	N/A	EC50	>100 mg/l
Organic Peroxide	13122-18-4	Green algae	Experimental	N/A	NOEC	0.125 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Dibenzoate Propanol	27138-31-4	Experimental Biodegradation	28 days	Carbon dioxide evolution	85 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
Acrylate Polymer	25101-28-4	Data not available - insufficient	N/A	N/A	N/A	N/A
Catalyst (NJTS Reg. No. 04499600-6922)	Trade Secret	Experimental Biodegradation	28 days	Carbon dioxide evolution	29.1 %CO2 evolution/THCO2 evolution	OECD 301B - Mod. Sturm or CO2
Catalyst (NJTS Reg. No. 04499600-6922)	Trade Secret	Estimated Photolysis		Photolytic half-life (in air)	1.48 days (t 1/2)	
Organic Peroxide	13122-18-4	Estimated Biodegradation	28	Biological Oxygen Demand	14 %BOD/ThOD	OECD 301C - MITI (I)

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Dibenzoate Propanol	27138-31-4	Modeled Bioconcentration		Bioaccumulation Factor	8	Catalogic™
Acrylate Polymer	25101-28-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Catalyst (NJTS Reg. No. 04499600-6922)	Trade Secret	Experimental Bioconcentration		Log of Octanol/H2O part. coeff	2.57	
Organic Peroxide	13122-18-4	Estimated Bioconcentration		Bioaccumulation Factor	363	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Not hazardous for transportation.

Marine Transport (IMDG)

- UN Number:**None assigned.
- Proper Shipping Name:**None assigned.
- Technical Name:**None assigned.
- Hazard Class/Division:**None assigned.
- Subsidiary Risk:**None assigned.
- Packing Group:**None assigned.
- Limited Quantity:**None assigned.
- Marine Pollutant:** None assigned.
- Marine Pollutant Technical Name:** None assigned.
- Other Dangerous Goods Descriptions:** None assigned.

Air Transport (IATA)

- UN Number:**None assigned.
- Proper Shipping Name:**None assigned.
- Technical Name:**None assigned.
- Hazard Class/Division:**None assigned.
- Subsidiary Risk:**None assigned.
- Packing Group:**None assigned.
- Limited Quantity:**None assigned.
- Marine Pollutant:** None assigned.
- Marine Pollutant Technical Name:** None assigned.
- Other Dangerous Goods Descriptions:**

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my