



## Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	22-1383-3	<b>Version Number:</b>	5.01
<b>Issue Date:</b>	11/03/25	<b>Supersedes Date:</b>	05/21/18

### SECTION 1: Identification

#### 1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive 110 Translucent, Part B

#### Product Identification Numbers

62-3563-8531-0

7010366143

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Structural adhesive

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Industrial Adhesives and Tapes Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1.

#### 2.2. Label elements

##### Signal word

Warning

##### Symbols

Exclamation mark |

##### Pictograms



### Hazard Statements

Causes eye irritation.  
May cause an allergic skin reaction.

### Precautionary statements

#### Prevention:

Avoid breathing vapors.  
Wash exposed skin thoroughly after handling.  
Contaminated work clothing should not be allowed out of the workplace.  
Wear protective gloves.

#### Response:

IF ON SKIN: Wash with plenty of soap and water.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists or if skin irritation or rash occurs: Get medical attention.  
Take off contaminated clothing and wash it before reuse.

#### Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

1% of the mixture consists of ingredients of unknown acute oral toxicity.

## SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Epoxy Resin	25068-38-6	73 - 90
Methacrylate/Butadiene/Styrene Polymer	25053-09-2	1 - 30
Hydrogenated Terphenyl	61788-32-7	5 - 10
Hydrogenated Polyphenyls	68956-74-1	< 2
Amorphous Silica	67762-90-7	0.1 - 1.5
Terphenyl	26140-60-3	< 1

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching).

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products****Substance**

Aldehydes  
Hydrocarbons  
Carbon monoxide  
Carbon dioxide  
Hydrogen Chloride  
Ketones  
Toxic Vapor, Gas, Particulate

**Condition**

During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion  
During Combustion

**5.3. Special protective actions for fire-fighters**

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label

and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Terphenyl	26140-60-3	ACGIH	CEIL:5 mg/m3	
Terphenyl	26140-60-3	OSHA	CEIL:9 mg/m3(1 ppm)	
Hydrogenated Terphenyl	61788-32-7	ACGIH	TWA:0.5 ppm	
Silica: Amorphous, including natural diatomaceous earth	67762-90-7	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

##### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective

clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Specific Physical Form:</b>	Paste
<b>Color</b>	Colorless
<b>Odor</b>	Slight Epoxy
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point/Freezing point</b>	<i>No Data Available</i>
<b>Boiling point/Initial boiling point/Boiling range</b>	>=260 °C
<b>Flash Point</b>	>=248.9 °C [ <i>Test Method: Closed Cup</i> ]
<b>Evaporation rate</b>	<i>Not Applicable</i>
<b>Flammability</b>	Not Applicable
<b>Flammable Limits(LEL)</b>	<i>Not Applicable</i>
<b>Flammable Limits(UEL)</b>	<i>Not Applicable</i>
<b>Vapor Pressure</b>	<i>Not Applicable</i>
<b>Relative Vapor Density</b>	<i>Not Applicable</i>
<b>Density</b>	1.13 g/ml
<b>Relative Density</b>	1.13 [ <i>Ref Std: WATER=1</i> ]
<b>Water solubility</b>	Nil
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Kinematic Viscosity</b>	48,673 mm <sup>2</sup> /sec
<b>Volatile Organic Compounds</b>	<i>No Data Available</i>
<b>Percent volatile</b>	<i>No Data Available</i>
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	0 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ] [ <i>Details: when used as intended with Part A</i> ]
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	0 g/l [ <i>Test Method: calculated SCAQMD rule 443.1</i> ] [ <i>Details: as supplied</i> ]
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	0 % [ <i>Test Method: calculated SCAQMD rule 443.1</i> ]

	[Details:when used as intended with Part A]
Molecular weight	No Data Available

Particle Characteristics	Not Applicable
--------------------------	----------------

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**

Stable.

**10.3. Possibility of hazardous reactions**

Hazardous polymerization will not occur.

**10.4. Conditions to avoid**

Heat

**10.5. Incompatible materials**

Strong oxidizing agents

**10.6. Hazardous decomposition products**

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1. Information on Toxicological effects**

**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

**Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Epoxy Resin	Dermal	Rat	LD50 > 1,600 mg/kg
Epoxy Resin	Ingestion	Rat	LD50 > 1,000 mg/kg
Methacrylate/Butadiene/Styrene Polymer	Dermal	Rabbit	LD50 > 5,000 mg/kg
Methacrylate/Butadiene/Styrene Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrogenated Terphenyl	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hydrogenated Terphenyl	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 4.7 mg/l
Hydrogenated Terphenyl	Ingestion	Rat	LD50 > 10,000 mg/kg
Terphenyl	Dermal	Rabbit	LD50 > 5,000 mg/kg
Terphenyl	Inhalation-Dust/Mist (4 hours)	Rat	LD50 > 3.8 mg/l
Terphenyl	Ingestion	Rat	LD50 2,304 mg/kg
Amorphous Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Amorphous Silica	Ingestion	Rat	LD50 > 5,110 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Epoxy Resin	Rabbit	Mild irritant
Methacrylate/Butadiene/Styrene Polymer	Professional judgement	Minimal irritation
Hydrogenated Terphenyl	Rabbit	No significant irritation
Terphenyl	Rabbit	No significant irritation
Amorphous Silica	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Epoxy Resin	Rabbit	Moderate irritant
Methacrylate/Butadiene/Styrene Polymer	Professional judgement	Mild irritant
Hydrogenated Terphenyl	Rabbit	No significant irritation
Terphenyl	Rabbit	No significant irritation
Amorphous Silica	Rabbit	No significant irritation

**Skin Sensitization**

Name	Species	Value
Epoxy Resin	Human and animal	Sensitizing
Hydrogenated Terphenyl	Human	Not classified
Amorphous Silica	Human and animal	Not classified

**Respiratory Sensitization**

Name	Species	Value
Epoxy Resin	Human	Not classified

**Germ Cell Mutagenicity**

Name	Route	Value
Epoxy Resin	In vivo	Not mutagenic
Epoxy Resin	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hydrogenated Terphenyl	In Vitro	Not mutagenic
Hydrogenated Terphenyl	In vivo	Not mutagenic
Terphenyl	In Vitro	Not mutagenic
Terphenyl	In vivo	Not mutagenic
Amorphous Silica	In Vitro	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Epoxy Resin	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Amorphous Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Epoxy Resin	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
Epoxy Resin	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Hydrogenated Terphenyl	Ingestion	Not classified for female reproduction	Rat	NOAEL 81 mg/kg/day	2 generation
Hydrogenated Terphenyl	Ingestion	Not classified for male reproduction	Rat	NOAEL 62 mg/kg/day	2 generation
Hydrogenated Terphenyl	Ingestion	Not classified for development	Rat	NOAEL 500 mg/kg/day	during organogenesis
Amorphous Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
------	-------	-----------------	-------	---------	-------------	-------------------

Epoxy Resin	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Epoxy Resin	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Epoxy Resin	Ingestion	auditory system   heart   endocrine system   hematopoietic system   liver   eyes   kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Hydrogenated Terphenyl	Dermal	skin	Not classified	Rabbit	NOAEL 500 mg/kg/day	3 weeks
Hydrogenated Terphenyl	Dermal	hematopoietic system	Not classified	Rabbit	NOAEL 2,000 mg/kg/day	3 weeks
Hydrogenated Terphenyl	Inhalation	liver   hematopoietic system   eyes	Not classified	Rat	NOAEL 0.5 mg/l	13 weeks
Hydrogenated Terphenyl	Ingestion	hematopoietic system   kidney and/or bladder   liver   eyes   respiratory system	Not classified	Rat	NOAEL 120 mg/kg/day	14 weeks
Amorphous Silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

**EPA Hazardous Waste Number (RCRA):** Not regulated

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information****15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:****Physical Hazards**

Not Applicable.

**Health Hazards**

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

**15.2. State Regulations**

Contact 3M for more information.

**15.3. Chemical Inventories**

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

**15.4. International Regulations**

Contact 3M for more information.

**This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

**SECTION 16: Other information****NFPA Hazard Classification**

**Health: 2 Flammability: 1 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	22-1383-3	<b>Version Number:</b>	5.01
<b>Issue Date:</b>	11/03/25	<b>Supersedes Date:</b>	05/21/18

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

**3M USA SDSs are available at [www.3M.com](http://www.3M.com)**