Safety Data Sheet

Copyright,2026, 3M Company.
All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	08-5967-8	**Version Number:**	27.01
Issue Date:	11/09/26	**Supersedes Date:**	10/01/25

SECTION 1: Identification

1.1. Product identifier
3M™ Structural Bonding Tape 9270 with Components

1.2. Recommended use and restrictions on use

Recommended use
Automotive - Industrial/Professional use, Structural Bonding Tape

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Automotive and Aerospace Solutions Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number
1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification
Serious Eye Damage/Irritation: Category 2B.
Skin Sensitizer: Category 1.

2.2. Label elements
Signal word
Warning

Symbols
Exclamation mark |

Pictograms



Hazard Statements

Causes eye irritation.
May cause an allergic skin reaction.

Precautionary statements

Prevention:
Avoid breathing vapors.
Wash exposed skin thoroughly after handling.
Contaminated work clothing should not be allowed out of the workplace.
Wear protective gloves.

Response:
IF ON SKIN: Wash with plenty of soap and water.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists or if skin irritation or rash occurs: Get medical attention.
Take off contaminated clothing and wash it before reuse.

Disposal:
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
ACRYLATE COPOLYMER (NJTSRN 04499600-7176)	Trade Secret*	30 - 60
EPOXY RESIN	25068-38-6	10 - 30 Trade Secret *
SOLID EPOXY RESIN	25036-25-3	10 - 30 Trade Secret *
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	112945-52-5	1 - 5
DICYANDIAMIDE	461-58-5	1 - 5
SUBSTITUTED TRIAZINE (NJTSRN 04499600-6282)	Trade Secret*	0.5 - 1.5
2-HYDROXY-3-PHENOXYPROPYL ACRYLATE	16969-10-1	< 1
VINYLCAPROLACTAM	2235-00-9	< 1
Carbon Black	1333-86-4	< 0.1
If present, Component (e.g., button, clip, bracket) is considered a non-hazardous article and is not factored into the ingredient percentages.	None	Not Applicable

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required
Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Aldehydes	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Hydrogen Cyanide	During Combustion
Ammonia	During Combustion
Oxides of Nitrogen	During Combustion

5.3. Special protective actions for fire-fighters
When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
Avoid release to the environment.

6.3. Methods and material for containment and cleaning up
Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities
Protect from sunlight. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Silica: Amorphous, including natural diatomaceous earth	112945-52-5	OSHA	TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m3	
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	A3: Confirmed animal carcin.
Carbon Black	1333-86-4	OSHA	TWA:3.5 mg/m3	
VINYLCAPROLACTAM	2235-00-9	Manufacturer determined	TWA(8 hours):0.1 ppm(0.57 mg/m3)	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
OSHA : United States Department of Labor - Occupational Safety and Health Administration
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
No engineering controls required.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields
Indirect Vented Goggles

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective

clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection
None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Roll of Tape
Color	Gray
Odor	Mild Acrylate
Odor threshold	*No Data Available*
pH	*Not Applicable*
Melting point	*No Data Available*
Boiling Point	*Not Applicable*
Flash Point	No flash point
Evaporation rate	*Not Applicable*
Flammability	Not Applicable
Flammable Limits(LEL)	*Not Applicable*
Flammable Limits(UEL)	*Not Applicable*
Vapor Pressure	*Not Applicable*
Relative Vapor Density	*Not Applicable*
Density	*No Data Available*
Relative Density	*No Data Available*
Solubility In Water	*Not Applicable*
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	*Not Applicable*
Molecular weight	*No Data Available*
Volatile Organic Compounds	*Not Applicable*
Percent volatile	*Not Applicable*
VOC Less H2O & Exempt Solvents	*Not Applicable*
Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat

10.5. Incompatible materials
Strong acids
Strong bases
Strong oxidizing agents
Amines

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
No health effects are expected.

Skin Contact:
Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:
Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:
Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation.

Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
Carbon black	1333-86-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg

EPOXY RESIN	Dermal	Rat	LD50 > 1,600 mg/kg
EPOXY RESIN	Ingestion	Rat	LD50 > 1,000 mg/kg
SOLID EPOXY RESIN	Dermal	Rat	LD50 > 1,600 mg/kg
SOLID EPOXY RESIN	Ingestion	Rat	LD50 > 1,000 mg/kg
DICYANDIAMIDE	Dermal	Rabbit	LD50 > 10,000 mg/kg
DICYANDIAMIDE	Ingestion	Rat	LD50 > 30,000 mg/kg
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Dermal	Rabbit	LD50 > 5,000 mg/kg
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Ingestion	Rat	LD50 > 5,110 mg/kg
SUBSTITUTED TRIAZINE (NJTSRN 04499600-6282)	Dermal	Professional judgement	LD50 estimated to be > 5,000 mg/kg
SUBSTITUTED TRIAZINE (NJTSRN 04499600-6282)	Ingestion	Rat	LD50 > 2,000 mg/kg
VINYLCAPROLACTAM	Dermal	Rabbit	LD50 1,700 mg/kg
VINYLCAPROLACTAM	Ingestion	Rat	LD50 1,049 mg/kg
2-HYDROXY-3-PHENOXYPROPYL ACRYLATE	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
2-HYDROXY-3-PHENOXYPROPYL ACRYLATE	Ingestion	Rat	LD50 > 2,000 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
EPOXY RESIN	Rabbit	Mild irritant
SOLID EPOXY RESIN	Rabbit	Mild irritant
DICYANDIAMIDE	Human and animal	Minimal irritation
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Rabbit	No significant irritation
SUBSTITUTED TRIAZINE (NJTSRN 04499600-6282)	In vitro data	No significant irritation
VINYLCAPROLACTAM	Rabbit	Minimal irritation
2-HYDROXY-3-PHENOXYPROPYL ACRYLATE	Rabbit	No significant irritation
Carbon Black	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
EPOXY RESIN	Rabbit	Moderate irritant
SOLID EPOXY RESIN	Rabbit	Moderate irritant
DICYANDIAMIDE	Professional judgement	Mild irritant
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Rabbit	No significant irritation
SUBSTITUTED TRIAZINE (NJTSRN 04499600-6282)	In vitro data	No significant irritation
VINYLCAPROLACTAM	Rabbit	Severe irritant
2-HYDROXY-3-PHENOXYPROPYL ACRYLATE	Rabbit	Corrosive
Carbon Black	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
EPOXY RESIN	Human and	Sensitizing

	animal	
SOLID EPOXY RESIN	Human and animal	Sensitizing
DICYANDIAMIDE	Guinea pig	Not classified
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Human and animal	Not classified
SUBSTITUTED TRIAZINE (NJTSRN 04499600-6282)	In vitro data	Not classified
VINYLCAPROLACTAM	Mouse	Sensitizing
2-HYDROXY-3-PHENOXYPROPYL ACRYLATE	Guinea pig	Sensitizing

Respiratory Sensitization

Name	Species	Value
EPOXY RESIN	Human	Not classified
SOLID EPOXY RESIN	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
EPOXY RESIN	In vivo	Not mutagenic
EPOXY RESIN	In Vitro	Some positive data exist, but the data are not sufficient for classification
SOLID EPOXY RESIN	In vivo	Not mutagenic
SOLID EPOXY RESIN	In Vitro	Some positive data exist, but the data are not sufficient for classification
DICYANDIAMIDE	In Vitro	Not mutagenic
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	In Vitro	Not mutagenic
SUBSTITUTED TRIAZINE (NJTSRN 04499600-6282)	In Vitro	Not mutagenic
VINYLCAPROLACTAM	In Vitro	Not mutagenic
2-HYDROXY-3-PHENOXYPROPYL ACRYLATE	In Vitro	Not mutagenic
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
EPOXY RESIN	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
SOLID EPOXY RESIN	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
DICYANDIAMIDE	Ingestion	Rat	Not carcinogenic
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
EPOXY RESIN	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
EPOXY RESIN	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
EPOXY RESIN	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesi

					s
EPOXY RESIN	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
SOLID EPOXY RESIN	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
SOLID EPOXY RESIN	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
SOLID EPOXY RESIN	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
SOLID EPOXY RESIN	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
DICYANDIAMIDE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
DICYANDIAMIDE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	44 days
DICYANDIAMIDE	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating & during gestation
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
2-HYDROXY-3-PHENOXYPROPYL ACRYLATE	Ingestion	Not classified for female reproduction	Rat	NOAEL 100 mg/kg/day	premating into lactation
2-HYDROXY-3-PHENOXYPROPYL ACRYLATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 100 mg/kg/day	28 days
2-HYDROXY-3-PHENOXYPROPYL ACRYLATE	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	premating into lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
EPOXY RESIN	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
SOLID EPOXY RESIN	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
VINYLCAPROLACTAM	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	
2-HYDROXY-3-PHENOXYPROPYL ACRYLATE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
EPOXY RESIN	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
EPOXY RESIN	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
EPOXY RESIN	Ingestion	auditory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
EPOXY RESIN	Ingestion	heart	Not classified	Rat	NOAEL 1,000	28 days

					mg/kg/day	
EPOXY RESIN	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
EPOXY RESIN	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
EPOXY RESIN	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
EPOXY RESIN	Ingestion	eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
EPOXY RESIN	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
SOLID EPOXY RESIN	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
SOLID EPOXY RESIN	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
SOLID EPOXY RESIN	Ingestion	auditory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
SOLID EPOXY RESIN	Ingestion	heart	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
SOLID EPOXY RESIN	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
SOLID EPOXY RESIN	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
SOLID EPOXY RESIN	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
SOLID EPOXY RESIN	Ingestion	eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
SOLID EPOXY RESIN	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
DICYANDIAMIDE	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 6,822 mg/kg/day	13 weeks
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
SYNTHETIC AMORPHOUS SILICA, FUMED, CRYSTALLINE FREE	Inhalation	silicosis	Not classified	Human	NOAEL Not available	occupational exposure
VINYLCAPROLACTAM	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.001 mg/l	28 days
VINYLCAPROLACTAM	Inhalation	blood	Not classified	Rat	NOAEL 0.18 mg/l	90 days
VINYLCAPROLACTAM	Inhalation	liver	Not classified	Rat	NOAEL 0.18 mg/l	90 days
VINYLCAPROLACTAM	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.18 mg/l	90 days
VINYLCAPROLACTAM	Inhalation	eyes	Not classified	Rat	NOAEL 0.18 mg/l	90 days
VINYLCAPROLACTAM	Ingestion	liver	Not classified	Rat	NOAEL 260 mg/kg/day	3 months
2-HYDROXY-3-	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 100	28 days

PHENOXYPROPYL ACRYLATE					mg/kg/day	
2-HYDROXY-3-PHENOXYPROPYL ACRYLATE	Ingestion	endocrine system	Not classified	Rat	NOAEL 100 mg/kg/day	28 days
2-HYDROXY-3-PHENOXYPROPYL ACRYLATE	Ingestion	blood	Not classified	Rat	NOAEL 100 mg/kg/day	28 days
2-HYDROXY-3-PHENOXYPROPYL ACRYLATE	Ingestion	immune system	Not classified	Rat	NOAEL 100 mg/kg/day	28 days
2-HYDROXY-3-PHENOXYPROPYL ACRYLATE	Ingestion	nervous system	Not classified	Rat	NOAEL 100 mg/kg/day	28 days
2-HYDROXY-3-PHENOXYPROPYL ACRYLATE	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 100 mg/kg/day	28 days
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards
Not Applicable.

Health Hazards
Respiratory or Skin Sensitization
Serious eye damage or eye irritation

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

This product is an article as defined by TSCA regulations, and is exempt from TSCA Inventory listing requirements.
Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification
Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group:	08-5967-8	**Version Number:**	27.01
Issue Date:	11/09/26	**Supersedes Date:**	10/01/25

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com