**Safety Data Sheet**

Copyright,2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|---|---|---|---|
| **Document group:** | 26-4963-0 | **Version number:** | 5.00 |
| **Issue Date:** | 2025/09/05 | **Supersedes Date:** | 2025/09/04 |

# SECTION 1: Identification

**1.1. Product identifier**
5775A-MT QSIII 3 CONDUCTOR SPLICE KIT

**Product Identification Numbers**
70-2013-7537-8 78-8126-0101-7 80-6112-1803-5 CE-1007-2901-7 CE-1007-3678-0
CE-1007-3886-9 UU-0091-5884-9 XE-1014-8790-0

**1.2. Recommended use and restrictions on use**

**Recommended use**
Electrical

**1.3. Supplier's details**

**Company:** 3M Canada Company
**Division:** Electrical Markets Division
**Address:** 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

**Telephone:** (800) 364-3577
**E Mail:**

**1.4. Emergency telephone number**
Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS) or Article Information Sheet (AIS) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:**

06-4861-8, 40-0153-3, 26-2852-7, 34-7684-3

Transport in accordance with applicable regulations.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit

for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at www.3M.ca**

# Safety Data Sheet

Copyright,2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|---|---|---|---|
| **Document group:** | 06-4861-8 | **Version number:** | 11.07 |
| **Issue Date:** | 2025/07/18 | **Supercedes Date:** | 2025/04/30 |

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

## SECTION 1: Identification

**1.1. Product identifier**
3M™ P55/R Lubricant, Red

**1.2. Recommended use and restrictions on use**

**Intended Use**
Electrical

**Specific Use**
ELECTRICAL LUBRICATING GREASE

**Restrictions on use**
Not applicable

**1.3. Supplier's details**

| | |
|---|---|
| **Company:** | 3M Canada Company |
| **Division:** | Electrical Markets Division |
| **Address:** | 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1 |
| **Telephone:** | (800) 364-3577 |
| **Website:** | www.3M.ca |

**1.4. Emergency telephone number**
Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

## SECTION 2: Hazard identification

**2.1. Classification of the substance or mixture**
Not classified according to the Canadian Hazardous Products Regulation.

**2.2. Label elements**
**Signal word**
Not applicable.

**Symbols**
Not applicable

**Pictograms**
Not applicable

**2.3. Other hazards**
None known.

## SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|---|---|---|---|
| 1,1,2,3,3,3-HEXAFLUORO-1-PROPENE, OXIDIZED, POLYMD. | 69991-67-9 | 95 - 98 | 1-Propene, 1,1,2,3,3,3-hexafluoro-, oxidized, polymd. |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | 112945-52-5 | <= 5 | Fumed amorphous silica, crystalline-free |
| C.I. PIGMENT RED 170 | 2786-76-7 | <= 0.05 | No Data Available |

## SECTION 4: First aid measures

**4.1. Description of first aid measures**

**Inhalation:**
Remove person to fresh air. If you are concerned, get medical advice.

**Skin Contact:**
Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye Contact:**
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If Swallowed:**
Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**
No critical symptoms or effects. See Section 11.1, information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**
Not applicable.

## SECTION 5: Fire-fighting measures

**5.1. Suitable extinguishing media**
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Unsuitable extinguishing media**
None Determined

**5.3. Special hazards arising from the substance or mixture**
None inherent in this product.

**Hazardous Decomposition or By-Products**

| Substance | Condition |
|---|---|
| Carbonyl Fluoride | During Combustion |
| Carbon monoxide | During Combustion |

| | |
|---|---|
| Carbon dioxide | During Combustion |
| Hydrogen Fluoride | During Combustion |
| Oxides of Nitrogen | During Combustion |

**5.4. Special protection actions for fire-fighters**
Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**
Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

**6.2. Environmental precautions**
Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**
Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**
For industrial or professional use only. Not for consumer sale or use. Avoid release to the environment. Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard.

**7.2. Conditions for safe storage including any incompatibilities**
Store away from acids. Store away from strong bases.

## SECTION 8: Exposure controls/personal protection

**8.1. Control parameters**

**Occupational exposure limits**
No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

**8.2. Exposure controls**

**8.2.1. Engineering controls**
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**
None required.

**Skin/hand protection**
No chemical protective gloves are required.

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

| | |
|---|---|
| **Physical state** | Liquid |
| **Specific Physical Form:** | Paste |
| **Colour** | Red |
| **Odour** | Odourless |
| **Odour threshold** | *Not Applicable* |
| **pH** | *Not Applicable* |
| **Melting point/Freezing point** | *Not Applicable* |
| **Boiling point** | 270 ºC [*Details:*MITS data (per supplier info)] |
| **Flash Point** | Flash point > 93 °C (200 °F) |
| **Evaporation rate** | *No Data Available* |
| **Flammability** | Not Applicable |
| **Flammable Limits(LEL)** | *Not Applicable* |
| **Flammable Limits(UEL)** | *Not Applicable* |
| **Vapour Pressure** | <=1.3 Pa |
| **Relative Vapour Density** | *No Data Available* |
| **Density** | *No Data Available* |
| **Relative density** | Approximately 1.99 [*Ref Std:*WATER=1] |
| **Water solubility** | Nil |
| **Solubility- non-water** | *Not Applicable* |
| **Partition coefficient: n-octanol/ water** | *No Data Available* |
| **Autoignition temperature** | *Not Applicable* |
| **Decomposition temperature** | *Not Applicable* |
| **Kinematic Viscosity** | *No Data Available* |
| **Volatile Organic Compounds** | *No Data Available* |
| **Percent volatile** | 0 % |
| **VOC Less H2O & Exempt Solvents** | *No Data Available* |
| **Average particle size** | *No Data Available* |
| **Bulk density** | *No Data Available* |
| **Molecular weight** | *No Data Available* |
| **Softening point** | *No Data Available* |

| | |
|---|---|
| **Particle Characteristics** | *Not Applicable* |

## SECTION 10: Stability and reactivity

**10.1. Reactivity**
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**
Stable.

**10.3. Possibility of hazardous reactions**
Hazardous polymerization will not occur.

**10.4. Conditions to avoid**
Not determined

**10.5. Incompatible materials**
Strong acids
Strong bases
Reactive metals

No Data Available

**10.6. Hazardous decomposition products**

| Substance | Condition |
|---|---|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

## SECTION 11: Toxicological information

**The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.**

**11.1. Information on Toxicological effects**

**Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation:**
No known health effects.

**Skin Contact:**
Contact with the skin during product use is not expected to result in significant irritation.

**Eye Contact:**
Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**

No known health effects.

**Toxicological Data**
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

| Name | Route | Species | Value |
|---|---|---|---|
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| 1,1,2,3,3,3-HEXAFLUORO-1-PROPENE, OXIDIZED, POLYMD. | Dermal | Professional judgement | LD50 estimated to be > 5,000 mg/kg |
| 1,1,2,3,3,3-HEXAFLUORO-1-PROPENE, OXIDIZED, POLYMD. | Ingestion | Professional judgement | LD50 estimated to be > 5,000 mg/kg |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Ingestion | Rat | LD50 > 5,110 mg/kg |

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| Name | Species | Value |
|---|---|---|
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Rabbit | No significant irritation |

**Serious Eye Damage/Irritation**

| Name | Species | Value |
|---|---|---|
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Rabbit | No significant irritation |

**Skin Sensitization**

| Name | Species | Value |
|---|---|---|
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Human and animal | Not classified |

**Respiratory Sensitization**
For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

| Name | Route | Value |
|---|---|---|
| Synthetic Amorphous Silica, Fumed, Crystalline Free | In Vitro | Not mutagenic |

**Carcinogenicity**

| Name | Route | Species | Value |
|---|---|---|---|
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Not Specified | Mouse | Some positive data exist, but the data are not sufficient for classification |

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test result | Exposure Duration |
|---|---|---|---|---|---|
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |

| | | | | | |
|---|---|---|---|---|---|
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesis |

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**
For the component/components, either no data are currently available or the data are not sufficient for classification.

**Specific Target Organ Toxicity - repeated exposure**

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---|---|---|---|---|---|---|
| Synthetic Amorphous Silica, Fumed, Crystalline Free | Inhalation | respiratory system \| silicosis | Not classified | Human | NOAEL Not available | occupational exposure |

**Aspiration Hazard**
For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

## SECTION 12: Ecological information

No data available.

## SECTION 13: Disposal considerations

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Prior to disposal, consult all applicable authorities and regulations to insure proper classification. Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include HF. Facility must be capable of handling halogenated materials. Empty and clean product containers may be disposed as non-hazardous waste. Consult your specific regulations and service providers to determine available options and requirements.

## SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## SECTION 16: Other information

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**
**Health:** 3 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**HMIS Hazard Classification**
**Health:** 0 **Flammability:** 1 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

| | | | |
|---|---|---|---|
| **Document group:** | 06-4861-8 | **Version number:** | 11.07 |
| **Issue Date:** | 2025/07/18 | **Supercedes Date:** | 2025/04/30 |

**Reason for Reissue**
Conversion to GHS format SDS.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at www.3M.ca**

# Safety Data Sheet

Copyright,2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|---|---|---|---|
| **Document group:** | 40-0153-3 | **Version number:** | 2.00 |
| **Issue Date:** | 2025/08/27 | **Supersedes Date:** | 2022/09/21 |

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

## SECTION 1: Identification

### 1.1. Product identifier
3M Sheath Wrap Roll

**Product Identification Numbers**

| | | | | |
|---|---|---|---|---|
| CE-1006-9128-2 | CE-1006-9129-0 | UU-0102-5729-1 | UU-0102-5730-9 | UU-0102-5913-1 |
| UU-0102-5914-9 | UU-0102-5915-6 | UU-0102-5936-2 | UU-0102-5937-0 | UU-0102-5938-8 |
| UU-0102-6051-9 | UU-0102-6052-7 | UU-0112-2563-6 | | |

### 1.2. Recommended use and restrictions on use

**Intended Use**
Industrial use

**Restrictions on use**
Not applicable

### 1.3. Supplier's details

| | |
|---|---|
| **Company:** | 3M Canada Company |
| **Division:** | Electronics & Energy Business Spons |
| **Address:** | 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1 |
| **Telephone:** | (800) 364-3577 |
| **Website:** | www.3M.ca |

### 1.4. Emergency telephone number
Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

## SECTION 2: Hazard identification

### 2.1. Classification of the substance or mixture
Respiratory Sensitizer: Category 1.
Skin Sensitizer: Category 1A.
Specific Target Organ Toxicity (repeated exposure): Category 1.

### 2.2. Label elements
**Signal word**
Danger

**Symbols**
Health Hazard |

**Pictograms**



**Hazard Statements**

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Causes damage to organs through prolonged or repeated exposure: respiratory system.

**Precautionary statements**

**Prevention:**
Do not breathe fumes. Wash exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves. In case of inadequate ventilation wear respiratory protection.

**Response:**
IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical attention if you feel unwell. If skin irritation or rash occurs: Get medical attention. If experiencing respiratory symptoms: Call a POISON CENTER or doctor. Take off contaminated clothing and wash it before reuse.

**Disposal:**
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

**2.3. Other hazards**
None known.

## SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|---|---|---|---|
| Oxide glass chemicals | 65997-17-3 | 40 - 70 | Glass, oxide, chemicals |
| Polymer | Trade Secret | 30 - 60 | Not Applicable |
| P,P'-Methylenebis(phenyl isocyanate) | 101-68-8 | 1 - 5 Trade Secret * | Benzene, 1,1'-methylenebis[4-isocyanato- |
| Iron Oxide (FE3O4) | 1317-61-9 | 1 - 5 | Iron oxide (Fe3O4) |
| Diphenylmethane-2,4'-diisocyanate | 5873-54-1 | 0.5 - 1.5 Trade Secret * | Benzene, 1-isocyanato-2-[(4-isocyanatophenyl)methyl]- |
| CHROMIUM (CR+6) | 18540-29-9 | 0.001 - 0.02 | No Data Available |

Polymer is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

*The concentration (exact or range) of this component has been withheld as a trade secret.

## SECTION 4: First aid measures

**4.1. Description of first aid measures**

**Inhalation:**
Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**
No need for first aid is anticipated. If signs/symptoms persist, get medical attention.

**If Swallowed:**
Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

**4.3. Indication of any immediate medical attention and special treatment required**
Not applicable

## SECTION 5: Fire-fighting measures

**5.1. Suitable extinguishing media**
In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Unsuitable extinguishing media**
None Determined

**5.3. Special hazards arising from the substance or mixture**
None inherent in this product.

**Hazardous Decomposition or By-Products**

| Substance | Condition |
|---|---|
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |
| Hydrogen Cyanide | During Combustion |
| Oxides of Nitrogen | During Combustion |

**5.4. Special protection actions for fire-fighters**
Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**
Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For

information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

**6.2. Environmental precautions**
Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**
Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**
Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**
Store away from strong bases. Store away from oxidizing agents. Store away from amines.

## SECTION 8: Exposure controls/personal protection

**8.1. Control parameters**

**Occupational exposure limits**
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---|---|---|---|---|
| Oxide glass chemicals | 65997-17-3 | Manufacturer determined | TWA(as non-fibrous, respirable)(8 hours):3 mg/m3;TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m3 | |

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**
Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face

protection(s) are recommended:
Safety Glasses with side shields
Indirect Vented Goggles

**Skin/hand protection**
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Chemical Protective glove of any material type

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

| | |
|---|---|
| **Physical state** | Solid |
| **Specific Physical Form:** | Resin Sat.Glass Tape |
| **Colour** | Black |
| **Odour** | Slight Odour |
| **Odour threshold** | *Not Applicable* |
| **pH** | *No Data Available* |
| **Melting point/Freezing point** | *Not Applicable* |
| **Boiling point** | *Not Applicable* |
| **Flash Point** | 174.4 ºC [*Test Method:*Closed Cup] |
| **Evaporation rate** | *Not Applicable* |
| **Flammability** | Not Applicable |
| **Flammable Limits(LEL)** | *No Data Available* |
| **Flammable Limits(UEL)** | *No Data Available* |
| **Vapour Pressure** | *No Data Available* |
| **Relative Vapour Density** | *No Data Available* |
| **Density** | *No Data Available* |
| **Relative density** | *Not Applicable* |
| **Water solubility** | Nil |
| **Solubility- non-water** | Nil [*Details:*water sulubility] |
| **Partition coefficient: n-octanol/ water** | *No Data Available* |
| **Autoignition temperature** | *No Data Available* |
| **Decomposition temperature** | *No Data Available* |
| **Kinematic Viscosity** | *Not Applicable* |

| | |
|---|---|
| **Volatile Organic Compounds** | *No Data Available* |
| **Percent volatile** | *No Data Available* |
| **VOC Less H2O & Exempt Solvents** | *No Data Available* |
| **Molecular weight** | *No Data Available* |

| | |
|---|---|
| **Particle Characteristics** | *Not Applicable* |

## SECTION 10: Stability and reactivity

**10.1. Reactivity**
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**
Stable.

**10.3. Possibility of hazardous reactions**
Hazardous polymerization will not occur.

**10.4. Conditions to avoid**
Sparks and/or flames

**10.5. Incompatible materials**
Alcohols
Amines
Strong bases
Strong oxidizing agents

**10.6. Hazardous decomposition products**

| Substance | Condition |
|---|---|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

**The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.**

**11.1. Information on Toxicological effects**

**Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation:**
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic Respiratory Reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

**Skin Contact:**
Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**
Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**
May be harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**Additional Health Effects:**

**Prolonged or repeated exposure may cause target organ effects:**
Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

**Carcinogenicity:**

| Ingredient | CAS No. | Class Description | Regulation |
|---|---|---|---|
| Chromium Hexavalent Compounds | 18540-29-9 | Known To Be Human Carcinogen. | National Toxicology Program Carcinogens |
| Chromium[VI] compounds | 18540-29-9 | Grp. 1: Carcinogenic to humans | International Agency for Research on Cancer |
| Hexavalent chromium compounds | 18540-29-9 | Cancer hazard | OSHA Carcinogens |
| Glass Wool Fibers (Inhalable), Certain | 65997-17-3 | Anticipated human carcinogen | National Toxicology Program Carcinogens |

**Additional Information:**
Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

**Toxicological Data**
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

| Name | Route | Species | Value |
|---|---|---|---|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE >2,000 - =5,000 mg/kg |
| Oxide glass chemicals | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Oxide glass chemicals | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Polymer | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Polymer | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| P,P'-Methylenebis(phenyl isocyanate) | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| P,P'-Methylenebis(phenyl isocyanate) | Inhalation-Dust/Mist (4 hours) | Rat | LC50 0.368 mg/l |
| P,P'-Methylenebis(phenyl isocyanate) | Ingestion | Rat | LD50 31,600 mg/kg |
| Iron Oxide (FE3O4) | Dermal | Not available | LD50 3,100 mg/kg |
| Iron Oxide (FE3O4) | Ingestion | Not available | LD50 3,700 mg/kg |
| Diphenylmethane-2,4'-diisocyanate | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Diphenylmethane-2,4'-diisocyanate | Inhalation-Dust/Mist (4 hours) | Rat | LC50 0.368 mg/l |
| Diphenylmethane-2,4'-diisocyanate | Ingestion | Rat | LD50 31,600 mg/kg |
| CHROMIUM (CR+6) | Dermal | | LD50 estimated to be 200 - 1,000 mg/kg |
| CHROMIUM (CR+6) | Inhalation-Dust/Mist | | LC50 estimated to be 0 - 0.05 mg/l |
| CHROMIUM (CR+6) | Ingestion | | LD50 estimated to be 5 - 50 mg/kg |

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| Name | Species | Value |
|---|---|---|
| Oxide glass chemicals | Professional judgement | No significant irritation |
| P,P'-Methylenebis(phenyl isocyanate) | official classification | Irritant |
| Iron Oxide (FE3O4) | Rabbit | No significant irritation |
| Diphenylmethane-2,4'-diisocyanate | official classification | Irritant |
| CHROMIUM (CR+6) | Human | Corrosive |

**Serious Eye Damage/Irritation**

| Name | Species | Value |
|---|---|---|
| Oxide glass chemicals | Professional judgement | No significant irritation |
| P,P'-Methylenebis(phenyl isocyanate) | official classification | Severe irritant |
| Iron Oxide (FE3O4) | Rabbit | No significant irritation |
| Diphenylmethane-2,4'-diisocyanate | official classification | Severe irritant |
| CHROMIUM (CR+6) | similar health hazards | Corrosive |

**Skin Sensitization**

| Name | Species | Value |
|---|---|---|
| P,P'-Methylenebis(phenyl isocyanate) | Mouse | Sensitizing |
| Iron Oxide (FE3O4) | Human | Not classified |
| Diphenylmethane-2,4'-diisocyanate | Mouse | Sensitizing |
| CHROMIUM (CR+6) | Human and animal | Sensitizing |

**Respiratory Sensitization**

| Name | Species | Value |
|---|---|---|
| P,P'-Methylenebis(phenyl isocyanate) | Human | Sensitizing |
| Diphenylmethane-2,4'-diisocyanate | Human | Sensitizing |
| CHROMIUM (CR+6) | Human | Not classified |

**Germ Cell Mutagenicity**

| Name | Route | Value |
|---|---|---|
| Oxide glass chemicals | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| P,P'-Methylenebis(phenyl isocyanate) | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Iron Oxide (FE3O4) | In Vitro | Not mutagenic |
| Diphenylmethane-2,4'-diisocyanate | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| CHROMIUM (CR+6) | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| CHROMIUM (CR+6) | In vivo | Mutagenic |

### Carcinogenicity

| Name | Route | Species | Value |
|---|---|---|---|
| Oxide glass chemicals | Inhalation | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |
| P,P'-Methylenebis(phenyl isocyanate) | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |
| Iron Oxide (FE3O4) | Inhalation | Human | Some positive data exist, but the data are not sufficient for classification |
| Diphenylmethane-2,4'-diisocyanate | Inhalation | Rat | Some positive data exist, but the data are not sufficient for classification |
| CHROMIUM (CR+6) | Not Specified | Human | Carcinogenic |

### Reproductive Toxicity

### Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test result | Exposure Duration |
|---|---|---|---|---|---|
| P,P'-Methylenebis(phenyl isocyanate) | Inhalation | Not classified for development | Rat | NOAEL 0.004 mg/l | during organogenesis |
| Diphenylmethane-2,4'-diisocyanate | Inhalation | Not classified for development | Rat | NOAEL 0.004 mg/l | during organogenesis |
| CHROMIUM (CR+6) | Inhalation | Not classified for female reproduction | Rat | NOAEL 0.0002 mg/l | 3 generation |
| CHROMIUM (CR+6) | Inhalation | Not classified for male reproduction | Rat | NOAEL 0.0002 mg/l | 3 generation |
| CHROMIUM (CR+6) | Inhalation | Not classified for development | Rat | NOAEL 0.0002 mg/l | 3 generation |
| CHROMIUM (CR+6) | Ingestion | Toxic to female reproduction | Mouse | LOAEL 6 mg/kg/day | 12 weeks |
| CHROMIUM (CR+6) | Ingestion | Toxic to male reproduction | Mouse | LOAEL 6 mg/kg/day | 12 weeks |
| CHROMIUM (CR+6) | Ingestion | Toxic to development | Mouse | LOAEL 57 mg/kg/day | during gestation |

### Target Organ(s)

### Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---|---|---|---|---|---|---|
| P,P'-Methylenebis(phenyl isocyanate) | Inhalation | respiratory irritation | May cause respiratory irritation | official classification | NOAEL Not available | |
| Diphenylmethane-2,4'-diisocyanate | Inhalation | respiratory irritation | May cause respiratory irritation | official classification | NOAEL Not available | |
| CHROMIUM (CR+6) | Dermal | kidney and/or bladder | Not classified | Human | NOAEL Not available | |
| CHROMIUM (CR+6) | Inhalation | respiratory irritation | May cause respiratory irritation | Human | NOAEL Not available | occupational exposure |
| CHROMIUM (CR+6) | Ingestion | kidney and/or bladder | Causes damage to organs | Human | NOAEL Not available | |
| CHROMIUM (CR+6) | Ingestion | hematoppoitic system \| liver | Not classified | Human | NOAEL Not available | |
| CHROMIUM (CR+6) | Ingestion | nervous system | Not classified | Human | NOAEL Not available | poisoning and/or abuse |

### Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---|---|---|---|---|---|---|
| Oxide glass chemicals | Inhalation | respiratory system | Not classified | Human | NOAEL not available | occupational exposure |

| | | | | | | |
|---|---|---|---|---|---|---|
| P,P'-Methylenebis(phenyl isocyanate) | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | LOAEL 0.004 mg/l | 13 weeks |
| Iron Oxide (FE3O4) | Inhalation | pulmonary fibrosis \| pneumoconiosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Diphenylmethane-2,4'-diisocyanate | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | LOAEL 0.004 mg/l | 13 weeks |
| CHROMIUM (CR+6) | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |
| CHROMIUM (CR+6) | Inhalation | immune system | Not classified | Rat | NOAEL Not available | 90 days |
| CHROMIUM (CR+6) | Inhalation | heart \| endocrine system \| hematopoietic system \| liver \| nervous system \| kidney and/or bladder | Not classified | Rat | NOAEL 0.02 mg/l | 2 years |
| CHROMIUM (CR+6) | Ingestion | kidney and/or bladder | May cause damage to organs though prolonged or repeated exposure | Rat | LOAEL 100 mg/kg/day | 28 days |
| CHROMIUM (CR+6) | Ingestion | nervous system | Not classified | Rat | LOAEL 98 mg/kg/day | 28 days |
| CHROMIUM (CR+6) | Ingestion | liver | Not classified | Multiple animal species | NOAEL Not available | |
| CHROMIUM (CR+6) | Ingestion | hematopoietic system | Not classified | Mouse | NOAEL Not available | 1 generation |

**Aspiration Hazard**
For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

## SECTION 12: Ecological information

No data available.

## SECTION 13: Disposal considerations

**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Global inventory status**

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## SECTION 16: Other information

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**
**Health:** 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|---|---|---|---|
| **Document group:** | 40-0153-3 | **Version number:** | 2.00 |
| **Issue Date:** | 2025/08/27 | **Supersedes Date:** | 2022/09/21 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at www.3M.ca**

# Safety Data Sheet

Copyright,2026, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|---|---|---|---|
| **Document group:** | 26-2852-7 | **Version number:** | 9.00 |
| **Issue Date:** | 2026/10/22 | **Supersedes Date:** | 2025/04/29 |

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

## SECTION 1: Identification

### 1.1. Product identifier
3M™ Cable Preparation Kit CC-2 (Can)

**Product Identification Numbers**

| | | | | |
|---|---|---|---|---|
| LH-A100-0663-9 | 78-8061-7605-9 | 78-8127-6979-8 | 80-6105-9299-2 | 80-6112-0013-2 |
| 80-6114-2769-3 | CE-1007-3253-2 | CE-1007-4524-5 | JE-1900-3038-5 | UU-0060-7547-5 |
| UU-0060-8786-8 | UU-0109-3614-2 | UU-0112-0459-9 | UU-0114-6788-1 | UU-0115-6093-3 |
| UU-0117-4166-5 | | | | |

### 1.2. Recommended use and restrictions on use

**Intended Use**
Electrical, SOLVENT SOAKED PADS FOR CLEANING CABLE

**Restrictions on use**
Not applicable

### 1.3. Supplier's details

| | |
|---|---|
| **Company:** | 3M Canada Company |
| **Division:** | Electrical Markets Division |
| **Address:** | 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1 |
| **Telephone:** | (800) 364-3577 |
| **Website:** | www.3M.ca |

### 1.4. Emergency telephone number
Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

## SECTION 2: Hazard identification


### 2.1. Classification of the substance or mixture
Flammable Liquid: Category 4.
Skin Corrosion/Irritation: Category 2.
Skin Sensitizer: Category 1B.

### 2.2. Label elements
**Signal word**

Warning

**Symbols**
Exclamation mark |

**Pictograms**



**Hazard Statements**
Combustible Liquid
Causes skin irritation. May cause an allergic skin reaction.

**Precautionary statements**

**Prevention:**
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapours. Wash exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.

**Response:**
IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**Storage:**
Store in a well-ventilated place.

**Disposal:**
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

**2.3. Other hazards**
None known.

## SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|---|---|---|---|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | 64742-48-9 | 50 - 70 Trade Secret * | Naphtha, petroleum, hydrotreated heavy |
| Cotton Pads | None | 25 - 40 | Not Applicable |
| D-LIMONENE | 5989-27-5 | 5 - 10 Trade Secret * | Cyclohexene, 1-methyl-4-(1-methylethenyl)-, (R)- |

Cotton Pads is a non-hazardous material according to WHMIS criteria. Specific information has been withheld as a trade secret.

*The concentration (exact or range) of this component has been withheld as a trade secret.

## SECTION 4: First aid measures

**4.1. Description of first aid measures**

**Inhalation:**
Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**
If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

**If Swallowed:**
Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

Allergic skin reaction (redness, swelling, blistering, and itching).

**4.3. Indication of any immediate medical attention and special treatment required**
Not applicable

## SECTION 5: Fire-fighting measures

**5.1. Suitable extinguishing media**
In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**5.2. Unsuitable extinguishing media**
None Determined

**5.3. Special hazards arising from the substance or mixture**
None inherent in this product.

**5.4. Special protection actions for fire-fighters**
Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA). Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**
Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

**6.2. Environmental precautions**
Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Collect as much of the spilled material as possible using non-sparking tools. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**
For industrial or professional use only. Not for consumer sale or use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**
Store in a well-ventilated place. Keep cool. Store away from acids. Store away from oxidizing agents.

## SECTION 8: Exposure controls/personal protection

**8.1. Control parameters**

**Occupational exposure limits**
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---|---|---|---|---|
| D-LIMONENE | 5989-27-5 | AIHA | TWA:165.5 mg/m3(30 ppm) | |

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

**8.2. Exposure controls**

**8.2.1. Engineering controls**
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**
None required.

**Skin/hand protection**
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

For prolonged or repeated contact, gloves made from the following material(s) are recommended (breakthrough times are >4 hours): Nitrile Rubber, Polymer laminate, Polyvinyl Alcohol (PVA)

Any glove recommended for prolonged/repeated contact is also suitable for short-term/splash contact.

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.),

then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

| | |
|---|---|
| **Physical state** | Solid (Lint-free cloths soaked with liquid) |
| **Specific Physical Form:** | Cloth pads soaked in liquid in can or bag |
| **Colour** | White |
| **Odour** | Moderate Citrus |
| **Odour threshold** | *No Data Available* |
| **pH** | 7 |
| **Melting point/Freezing point** | *No Data Available* |
| **Boiling point** | 193.3 ºC - 248.9 ºC |
| **Flash Point** | 62.2 ºC [*Test Method:*Closed Cup] |
| **Evaporation rate** | *No Data Available* |
| **Flammability** | Flammable Liquid: Category 4. |
| **Flammable Limits(LEL)** | *No Data Available* |
| **Flammable Limits(UEL)** | *No Data Available* |
| **Vapour Pressure** | < 1 mmHg [@ 25 ºC] |
| **Relative Vapour Density** | > 1 [*Ref Std:*AIR=1] |
| **Density** | 0.76 g/ml |
| **Relative density** | 0.76 [*Ref Std:*WATER=1] |
| **Water solubility** | Nil |
| **Solubility- non-water** | *No Data Available* |
| **Partition coefficient: n-octanol/ water** | *No Data Available* |
| **Autoignition temperature** | *No Data Available* |
| **Decomposition temperature** | *No Data Available* |
| **Kinematic Viscosity** | 2 mm2/sec |
| **Volatile Organic Compounds** | Approximately 740 % |
| **Percent volatile** | *No Data Available* |
| **VOC Less H2O & Exempt Solvents** | 760 g/l |
| **Molecular weight** | *No Data Available* |

| | |
|---|---|
| **Particle Characteristics** | *Not Applicable* |

## SECTION 10: Stability and reactivity

**10.1. Reactivity**
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

**10.2. Chemical stability**

Stable.

**10.3. Possibility of hazardous reactions**
Hazardous polymerization will not occur.

**10.4. Conditions to avoid**
Sparks and/or flames

**10.5. Incompatible materials**
Strong oxidizing agents

**10.6. Hazardous decomposition products**

| Substance | Condition |
|---|---|
| Carbon monoxide | Not Specified |
| Carbon dioxide | Not Specified |

## SECTION 11: Toxicological information

**The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.**

**11.1. Information on Toxicological effects**

**Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation:**
Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

**Skin Contact:**
Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**
Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**
Physical Blockage: Signs/symptoms may include cramping, abdominal pain, and constipation. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**Toxicological Data**
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

| Name | Route | Species | Value |
|---|---|---|---|
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE >50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Dermal | similar compounds | LD50 > 2,200 mg/kg |

| | | | |
|---|---|---|---|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Ingestion | similar compounds | LD50 > 15,000 mg/kg |
| D-LIMONENE | Inhalation-Vapor (4 hours) | Mouse | LC50 > 3.14 mg/l |
| D-LIMONENE | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| D-LIMONENE | Ingestion | Rat | LD50 4,400 mg/kg |

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

| Name | Species | Value |
|---|---|---|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | similar compounds | Mild irritant |
| D-LIMONENE | Rabbit | Irritant |

**Serious Eye Damage/Irritation**

| Name | Species | Value |
|---|---|---|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | similar compounds | No significant irritation |
| D-LIMONENE | Rabbit | Mild irritant |

**Skin Sensitization**

| Name | Species | Value |
|---|---|---|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | similar compounds | Not classified |
| D-LIMONENE | Mouse | Sensitizing |

**Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity**

| Name | Route | Value |
|---|---|---|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | In Vitro | Not mutagenic |
| D-LIMONENE | In Vitro | Not mutagenic |
| D-LIMONENE | In vivo | Not mutagenic |

**Carcinogenicity**

| Name | Route | Species | Value |
|---|---|---|---|
| D-LIMONENE | Ingestion | Rat | Some positive data exist, but the data are not sufficient for classification |

**Reproductive Toxicity**

**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test result | Exposure Duration |
|---|---|---|---|---|---|
| D-LIMONENE | Ingestion | Not classified for female reproduction | Rat | NOAEL 750 mg/kg/day | premating & during gestation |
| D-LIMONENE | Ingestion | Not classified for development | Multiple animal species | NOAEL 591 mg/kg/day | during organogenesis |

**Target Organ(s)**

**Specific Target Organ Toxicity - single exposure**

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---|---|---|---|---|---|---|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| D-LIMONENE | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| D-LIMONENE | Ingestion | nervous system | Not classified | | NOAEL Not available | |

**Specific Target Organ Toxicity - repeated exposure**

| Name | Route | Target Organ(s) | Value | Species | Test result | Exposure Duration |
|---|---|---|---|---|---|---|
| D-LIMONENE | Ingestion | kidney and/or bladder | Not classified | Rat | LOAEL 75 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | liver | Not classified | Mouse | NOAEL 1,000 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | heart | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | endocrine system | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | bone, teeth, nails, and/or hair | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | hematopoietic system | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | immune system | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | muscles | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | nervous system | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |
| D-LIMONENE | Ingestion | respiratory system | Not classified | Rat | NOAEL 600 mg/kg/day | 103 weeks |

**Aspiration Hazard**

| Name | Value |
|---|---|
| HYDROTREATED HEAVY NAPHTHA (PETROLEUM) | Aspiration hazard |
| D-LIMONENE | Aspiration hazard |

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

## SECTION 12: Ecological information

No data available.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the

available treatment and disposal facilities.

## SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

## SECTION 16: Other information

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**
**Health:** 2 **Flammability:** 2 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**HMIS Hazard Classification**
**Health:** 2 **Flammability:** 2 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

| | | | |
|---|---|---|---|
| **Document group:** | 26-2852-7 | **Version number:** | 9.00 |
| **Issue Date:** | 2026/10/22 | **Supersedes Date:** | 2025/04/29 |

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit

for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at www.3M.ca**

# Article Information Sheet

Copyright,2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

This Article Information Sheet is provided as a courtesy in response to a customer request. A Safety Data Sheet (SDS) has not been prepared for these product(s) because they are articles. Articles are not subject to the Hazardous Products Act or Regulations. As defined in the act: “Article” means any article that is formed to a specific shape or design during manufacture, the intended use of which when in that form is dependent in whole or in part on its shape or design, and that, when being installed, if the intended use of the article requires it to be installed, and under normal conditions of use, will not release or otherwise cause an individual to be exposed to a hazardous product.

| | | | |
|---|---|---|---|
| **Document group:** | 34-7684-3 | **Version number:** | 2.00 |
| **Issue Date:** | 2025/04/29 | **Supercedes Date:** | 2023/01/12 |

## SECTION 1: Identification

### 1.1. Product identifier
Black EPDM Tubing (on plastic core)

**Product Identification Numbers**
78-8125-9775-1

### 1.2. Recommended use and restrictions on use

**Intended Use**
Electrical

**Restrictions on use**
Not applicable

### 1.3. Supplier’s details

| | |
|---|---|
| **Company:** | 3M Canada Company |
| **Division:** | Electrical Markets Division |
| **Address:** | 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1 |
| **Telephone:** | (800) 364-3577 |
| **Website:** | www.3M.ca |

### 1.4. Emergency telephone number
Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

## SECTION 2: Hazard identification

This product is exempt from hazard classification according to the Hazardous Products Act because it meets the manufactured article exemption.

## SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt | Common Name |
|---|---|---|---|
| Black EPDM Tubing Composite | None | 100 | No Data Available |

## SECTION 4: First aid measures

**4.1. Description of first aid measures**

**Inhalation:**
No need for first aid is anticipated.

**Skin Contact:**
No need for first aid is anticipated.

**Eye Contact:**
No need for first aid is anticipated.

**If Swallowed:**
No need for first aid is anticipated.

## SECTION 5: Fire-fighting measures

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**
Not applicable.

**6.2. Environmental precautions**
Not applicable.

**6.3. Methods and material for containment and cleaning up**
Not applicable.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling**
This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical under normal use conditions.

**7.2. Conditions for safe storage including any incompatibilities**
No special storage requirements.

## SECTION 8: Exposure controls/personal protection

This product is considered to be an article which does not release or otherwise result in exposure to a hazardous chemical under normal use conditions. No engineering controls or personal protective equipment (PPE) are necessary.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

| | |
|---|---|
| **Physical state** | Solid |

| | |
|---|---|
| **Colour** | Black |
| **Odour** | Mild Rubber |
| **Odour threshold** | *Not Applicable* |
| **pH** | *Not Applicable* |
| **Melting point/Freezing point** | *No Data Available* |
| **Boiling point** | *Not Applicable* |
| **Flash Point** | No flash point |
| **Evaporation rate** | *Not Applicable* |
| **Flammability** | Not Applicable |
| **Flammable Limits(LEL)** | *Not Applicable* |
| **Flammable Limits(UEL)** | *Not Applicable* |
| **Relative Vapour Density** | *Not Applicable* |
| **Density** | *No Data Available* |
| **Relative density** | *No Data Available* |
| **Water solubility** | *Not Applicable* |
| **Solubility- non-water** | *Not Applicable* |
| **Partition coefficient: n-octanol/ water** | *Not Applicable* |
| **Autoignition temperature** | *Not Applicable* |
| **Decomposition temperature** | *No Data Available* |
| **Kinematic Viscosity** | *Not Applicable* |
| **Volatile Organic Compounds** | *No Data Available* |
| **Percent volatile** | *No Data Available* |
| **VOC Less H2O & Exempt Solvents** | *No Data Available* |
| **Molecular weight** | *Not Applicable* |

| | |
|---|---|
| **Particle Characteristics** | *Not Applicable* |

## SECTION 10: Stability and reactivity

This material is considered to be non reactive under normal use conditions.

## SECTION 11: Toxicological information

**Inhalation:**
No health effects are expected

**Skin Contact:**
No health effects are expected

**Eye Contact:**
No health effects are expected

**Ingestion:**
No health effects are expected

**Additional Information:**
This product, when used under reasonable conditions and in accordance with the directions for use, should not present a health hazard. However, use or processing of the product in a manner not in accordance with the product's directions for use may affect the performance of the product and may present potential health and safety hazards.

## SECTION 12: Ecological information

No data available.

## SECTION 13: Disposal considerations

Dispose of contents/container in accordance with the local/regional/national/international regulations.

## SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

## SECTION 15: Regulatory information

This product is an article as defined by CEPA and is exempt from DSL inventory listing.

## SECTION 16: Other information

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**
**Health:** 0 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|---|---|---|---|
| **Document group:** | 34-7684-3 | **Version number:** | 2.00 |
| **Issue Date:** | 2025/04/29 | **Supercedes Date:** | 2023/01/12 |

The information in this Article Information Sheet (AIS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at www.3M.ca**