Safety Data Sheet

Copyright,2026, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	10-2818-2	**Version number:**	25.00
Revision date:	01/07/2026	**Supersedes date:**	25/02/2026

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006), as amended for GB.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier
3M™ TroubleShooter™ Baseboard Stripper

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Baseboard Stripper

1.3. Details of the supplier of the safety data sheet

Address:	3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.
Telephone:	+44 (0)1344 858 000
E Mail:	ner-productstewardship@mmm.com
Website:	www.3M.com/uk

1.4. Emergency telephone number
+44 (0)1344 858 000

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.
This material has been tested for skin corrosion/irritation and the test results are reflected in the assigned classification.

CLASSIFICATION:
Aerosol, Category 3 - Aerosol 3; H229
Skin Corrosion/Irritation, Category 1B - Skin Corr. 1B; H314
Serious Eye Damage/Eye Irritation, Category 1 - Eye Dam. 1; H318


For full text of H phrases, see Section 16.

2.2. Label elements
The retained CLP Regulation (EU) No 1272/2008 as amended for Great Britain

SIGNAL WORD
DANGER.

Symbols
GHS05 (Corrosion) |

Pictograms



Ingredient	Identifier(s)	EC No.	% by Wt
2-aminoethanol	141-43-5	205-483-3	< 5

HAZARD STATEMENTS:

H229	Pressurised container: may burst if heated.
H314	Causes severe skin burns and eye damage.

PRECAUTIONARY STATEMENTS

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251	Do not pierce or burn, even after use.
P260E	Do not breathe vapour or spray.
P280D	Wear protective gloves, protective clothing, and eye/face protection.

Response:

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTRE or doctor/physician.

Storage:

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

SUPPLEMENTAL INFORMATION:

Supplemental Hazard Statements:

EUH071	Corrosive to the respiratory tract.

Notes on labelling
Updated per Regulation (EC) No. 648/2004 as amended for Great Britain on detergents. Nota K applied.
Ingredients required per 648/2004: <5%: Non-ionic surfactants. Contains: Perfumes, d-limonene.
Contains <10% flammable components.

2.3. Other hazards

None known.
This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances
Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP], as amended for GB
Water	Mixture	60 - 90	Substance not classified as hazardous
2-butoxyethanol	(CAS-No.) 111-76-2 (EC-No.) 203-905-0	10 - 15	Acute Tox. 4, H332 Acute Tox. 4, H302(LD50 = 1200 mg/kg **ATE values per GB MCL**) Skin Irrit. 2, H315 Eye Irrit. 2, H319
Petroleum gases, liquefied, sweetened	(CAS-No.) 68476-86-8 (EC-No.) 270-705-8	< 10	Flam. Gas 1A, H220 Liquified gas, H280 Nota K,S,U STOT SE 3, H336
2-aminoethanol	(CAS-No.) 141-43-5 (EC-No.) 205-483-3	< 5	Acute Tox. 4, H332 Acute Tox. 4, H312 Acute Tox. 4, H302 Skin Corr. 1B, H314 STOT SE 3, H335 Eye Dam. 1, H318 Aquatic Chronic 3, H412
Alcohols, C12-15, ethoxylated	(CAS-No.) 68131-39-5 (EC-No.) 500-195-7	< 1	Aquatic Acute 1, H400,M=10 Aquatic Chronic 2, H411

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
2-aminoethanol	(CAS-No.) 141-43-5 (EC-No.) 205-483-3	(C >= 5%) STOT SE 3, H335

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation
Remove person to fresh air. Get medical attention.

Skin contact
Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye contact
Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed
Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed
The most important symptoms and effects based on the GB CLP classification include:
Corrosive to respiratory tract (severe nose and throat pain, chest tightness and pain, wheezing, and breathlessness). Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required
Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media
Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture
Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance	Condition
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.

5.3. Advice for fire-fighters
No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or

if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. For large spills, if necessary, get assistance from professional spill clean up team. For small spills, carefully neutralise spill by adding appropriate dilute acid such as vinegar. Work slowly to avoid boiling or spattering. Continue to add neutralising agent until reaction stops. Let cool before collecting. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with water. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections
Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling
For industrial/occupational use only. Not for consumer sale or use. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities
Protect from sunlight. Do not expose to temperatures exceeding 50ºC/122ºF. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)
See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	Identifier(s)	Agency	Limit type	Additional comments
2-butoxyethanol	111-76-2	UK HSE	TWA:123 mg/m3(25 ppm);STEL:246 mg/m3(50 ppm)	SKIN
2-aminoethanol	141-43-5	UK HSE	TWA:2.5 mg/m3(1 ppm);STEL:7.6 mg/m3(3 ppm)	SKIN

UK HSE : UK Health and Safety Commission
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

Biological limit values

Ingredient	Identifier(s)	Agency	Determinant	Biological Specimen	Sampling Time	Value	Additional comments
2-butoxyethanol	111-76-2	UK EH40 BMGVs	Butoxyacetic acid	Creatinine in urine	EOS	240 mmol/mol	

UK EH40 BMGVs : UK. EH40 Biological Monitoring Guidance Values (BMGVs)
EOS: End of shift.

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Full face shield.
Indirect vented goggles.

Applicable Norms/Standards
Use eye/face protection conforming to EN 16321

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	>0.30	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours
Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards
Use a respirator conforming to EN 140 or EN 136
Use a respirator conforming to EN 140 or EN 136: filter type A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Aerosol
Colour	Off-White
Odor	Strong Petroleum
Odour threshold	*No data available.*
Melting point/freezing point	*Not applicable.*
Boiling point/boiling range	> 100 ºC
Flammability	Non-flammable Aerosol: Category 3.
Flammable Limits(LEL)	*No data available.*
Flammable Limits(UEL)	*No data available.*
Flash point	*No data available.*
Autoignition temperature	*No data available.*
Decomposition temperature	*No data available.*
pH	11 - 12.1
Kinematic Viscosity	80.2 mm²/sec
Water solubility	Complete
Solubility- non-water	*No data available.*
Partition coefficient: n-octanol/water	*No data available.*
Vapour pressure	*No data available.*
Density	0.967 g/ml - 1.027 g/ml
Relative density	0.967 - 1.027 [*Ref Std:*WATER=1]
Relative Vapour Density	*No data available.*
Particle Characteristics	*Not applicable.*

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	*No data available.*
Evaporation rate	*No data available.*
Molecular weight	*No data available.*
Percent volatile	60 - 90 % weight
Foam Flame Hgt and Duration	4 cm [@ 7 sec] [*Details:*Foam Flame Height <4 cm for a duration of 7 seconds]

SECTION 10: Stability and reactivity

10.1 Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability
Stable.

10.3 Possibility of hazardous reactions
Hazardous polymerisation will not occur.

10.4 Conditions to avoid
Heat.
Sparks and/or flames.

10.5 Incompatible materials
Strong oxidising agents.

Strong acids.

10.6 Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from 3M assessments.

11.1. Information on hazard classes as defined in the retained CLP Regulation (EU) No 1272/2008, as amended for Great Britain.

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation
Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact
Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eye contact
Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion
Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen.

Additional Health Effects:

Single exposure may cause target organ effects:
Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
2-butoxyethanol	Dermal	Guinea	LD50 > 2,000 mg/kg

		pig	
2-butoxyethanol	Inhalation-Vapour (4 hours)	Guinea pig	LC50 > 2.6 mg/l
2-butoxyethanol	Ingestion	Guinea pig	LD50 1,200 mg/kg
Petroleum gases, liquefied, sweetened	Inhalation-Gas (4 hours)	Rat	LC50 277,000 ppm
2-aminoethanol	Inhalation-Vapour	official classification	LC50 estimated to be 10 - 20 mg/l
2-aminoethanol	Dermal	Rabbit	LD50 2,504 mg/kg
2-aminoethanol	Ingestion	Rat	LD50 1,089 mg/kg
Alcohols, C12-15, ethoxylated	Ingestion	similar compounds	LD50 > 2,000 mg/kg
Alcohols, C12-15, ethoxylated	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	In vitro data	Corrosive
2-butoxyethanol	Rabbit	Irritant
Petroleum gases, liquefied, sweetened	Professional judgement	No significant irritation
2-aminoethanol	Rabbit	Corrosive
Alcohols, C12-15, ethoxylated	Rabbit	Mild irritant

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	Professional judgement	Severe irritant
2-butoxyethanol	Rabbit	Severe irritant
Petroleum gases, liquefied, sweetened	Professional judgement	No significant irritation
2-aminoethanol	Rabbit	Corrosive
Alcohols, C12-15, ethoxylated	similar compounds	No significant irritation

Skin Sensitisation

Name	Species	Value
2-butoxyethanol	Guinea pig	Not classified
2-aminoethanol	Guinea pig	Not classified
Alcohols, C12-15, ethoxylated	similar compounds	Not classified

Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
2-butoxyethanol	In Vitro	Some positive data exist, but the data are not sufficient for classification
Petroleum gases, liquefied, sweetened	In Vitro	Not mutagenic
2-aminoethanol	In Vitro	Not mutagenic
2-aminoethanol	In vivo	Not mutagenic
Alcohols, C12-15, ethoxylated	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
2-butoxyethanol	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
2-butoxyethanol	Dermal	Not classified for development	Rat	NOAEL 1,760 mg/kg/day	during gestation
2-butoxyethanol	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	during organogenesis
2-butoxyethanol	Inhalation	Not classified for development	Multiple animal species	NOAEL 0.48 mg/l	during organogenesis
2-aminoethanol	Dermal	Not classified for development	Rat	NOAEL 225 mg/kg/day	during organogenesis
2-aminoethanol	Ingestion	Not classified for development	Rat	NOAEL 450 mg/kg/day	during organogenesis
Alcohols, C12-15, ethoxylated	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Alcohols, C12-15, ethoxylated	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	29 days
Alcohols, C12-15, ethoxylated	Ingestion	Not classified for development	Rat	NOAEL 300 mg/kg/day	premating into lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 902 mg/kg	6 hours
2-butoxyethanol	Dermal	liver	Not classified	Rabbit	LOAEL 72 mg/kg	not available
2-butoxyethanol	Dermal	kidney and/or bladder	Not classified	Rabbit	LOAEL 451 mg/kg	6 hours
2-butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	
2-butoxyethanol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
2-butoxyethanol	Inhalation	central nervous system depression	Not classified	Professional judgeme	NOAEL Not available	

				nt		
2-butoxyethanol	Inhalation	blood	Not classified	Multiple animal species	NOAEL Not available	
2-butoxyethanol	Ingestion	central nervous system depression	Not classified	Professional judgement	NOAEL Not available	
2-butoxyethanol	Ingestion	blood	Not classified	Multiple animal species	NOAEL Not available	
2-butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Human	NOAEL Not available	poisoning and/or abuse
Petroleum gases, liquefied, sweetened	Inhalation	cardiac sensitisation	Causes damage to organs	similar compounds	NOAEL Not available	
Petroleum gases, liquefied, sweetened	Inhalation	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Petroleum gases, liquefied, sweetened	Inhalation	respiratory irritation	Not classified		NOAEL Not available	
2-aminoethanol	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Alcohols, C12-15, ethoxylated	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available.	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
2-butoxyethanol	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	not available
2-butoxyethanol	Dermal	endocrine system	Not classified	Rabbit	NOAEL 150 mg/kg/day	90 days
2-butoxyethanol	Inhalation	liver	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
2-butoxyethanol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.15 mg/l	14 weeks
2-butoxyethanol	Inhalation	blood	Not classified	Rat	LOAEL 0.15 mg/l	6 months
2-butoxyethanol	Inhalation	endocrine system	Not classified	Dog	LOAEL 1.9 mg/l	8 days
2-butoxyethanol	Ingestion	blood	Not classified	Rat	LOAEL 69 mg/kg/day	13 weeks
2-butoxyethanol	Ingestion	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	not available
Petroleum gases, liquefied, sweetened	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL Not available	
2-aminoethanol	Inhalation	hematopoietic system | liver	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
2-aminoethanol	Inhalation	respiratory system	Not classified	Rat	LOAEL 0.0102 mg/l	28 days
2-aminoethanol	Inhalation	heart | endocrine system | immune system | nervous system | eyes | kidney and/or bladder	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
2-aminoethanol	Ingestion	hematopoietic system | liver | kidney and/or bladder | respiratory system	Not classified	Rat	NOAEL Not available	
Alcohols, C12-15, ethoxylated	Ingestion	endocrine system | gastrointestinal tract	Not classified	Rat	NOAEL 1,000	13 weeks

		| liver | kidney and/or bladder | hematopoietic system | nervous system | eyes			mg/kg/day	

Aspiration Hazard
For the component/components, either no data is currently available or the data is not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	Identifier(s)	Organism	Type	Exposure	Test endpoint	Test result
2-butoxyethanol	111-76-2	Activated sludge	Experimental	16 hours	IC50	>1,000 mg/l
2-butoxyethanol	111-76-2	Eastern oyster	Experimental	96 hours	LC50	89.4 mg/l
2-butoxyethanol	111-76-2	Green algae	Experimental	72 hours	ErC50	1,840 mg/l
2-butoxyethanol	111-76-2	Rainbow trout	Experimental	96 hours	LC50	1,474 mg/l
2-butoxyethanol	111-76-2	Water flea	Experimental	48 hours	EC50	1,550 mg/l
2-butoxyethanol	111-76-2	Green algae	Experimental	72 hours	ErC10	679 mg/l
2-butoxyethanol	111-76-2	Water flea	Experimental	21 days	NOEC	100 mg/l
Petroleum gases, liquefied, sweetened	68476-86-8	N/A	Data not available or insufficient for classification	N/A	N/A	n/a
2-aminoethanol	141-43-5	Diatom	Experimental	72 hours	ErC50	198 mg/l
2-aminoethanol	141-43-5	Green algae	Experimental	72 hours	ErC50	2.5 mg/l
2-aminoethanol	141-43-5	Rainbow trout	Experimental	96 hours	LC50	105 mg/l
2-aminoethanol	141-43-5	Water flea	Experimental	48 hours	EC50	27.04 mg/l
2-aminoethanol	141-43-5	Green algae	Experimental	72 hours	NOEC	1 mg/l
2-aminoethanol	141-43-5	Medaka	Experimental	41 days	NOEC	1.24 mg/l
2-aminoethanol	141-43-5	Water flea	Experimental	21 days	NOEC	0.85 mg/l
2-aminoethanol	141-43-5	Activated sludge	Experimental	30 minutes	IC50	>1,000 mg/l
2-aminoethanol	141-43-5	Plant	Experimental	21 days	EC50	1,290 mg/kg (Dry Weight)

2-aminoethanol	141-43-5	Redworm	Experimental	35 days	LC50	3,715 mg/kg (Dry Weight)
2-aminoethanol	141-43-5	Springtail	Experimental	28 days	LC50	1,893 mg/kg (Dry Weight)
Alcohols, C12-15, ethoxylated	68131-39-5	Fish	Analogous Compound	96 hours	LC50	1 mg/l
Alcohols, C12-15, ethoxylated	68131-39-5	Green algae	Analogous Compound	72 hours	ErC50	0.57 mg/l
Alcohols, C12-15, ethoxylated	68131-39-5	Water flea	Analogous Compound	48 hours	LC50	0.1 mg/l
Alcohols, C12-15, ethoxylated	68131-39-5	Green algae	Analogous Compound	72 hours	NOEC	0.035 mg/l

12.2. Persistence and degradability

Material	Identifier(s)	Test type	Duration	Study Type	Test result	Protocol
2-butoxyethanol	111-76-2	Experimental Biodegradation	28 days	CO2 evolution	90.4 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2
2-butoxyethanol	111-76-2	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	100 %removal of DOC	OECD 302B Zahn-Wellens/EVPA
Petroleum gases, liquefied, sweetened	68476-86-8	Data not availbl-insufficient	N/A	N/A	N/A	N/A
2-aminoethanol	141-43-5	Experimental Biodegradation	28 days	CO2 evolution	80 %CO2 evolution/THCO2 evolution	
2-aminoethanol	141-43-5	Experimental Biodegradation	21 days	Dissolv. Organic Carbon Deplet	>90 %removal of DOC	OECD 301A - DOC Die Away Test
2-aminoethanol	141-43-5	Experimental Photolysis		Photolytic half-life (in air)	5.5 hours (t 1/2)	
Alcohols, C12-15, ethoxylated	68131-39-5	Analogous Compound Biodegradation	28 days	CO2 evolution	82 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2

12.3 : Bioaccumulative potential

Material	Identifier(s)	Test type	Duration	Study Type	Test result	Protocol
2-butoxyethanol	111-76-2	Experimental Bioconcentration		Log Kow	0.81	
Petroleum gases, liquefied, sweetened	68476-86-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Petroleum gases, liquefied, sweetened	68476-86-8	Estimated Bioconcentration		Log Kow	2.8	
2-aminoethanol	141-43-5	Experimental Bioconcentration		Log Kow	-2.3	OECD 107 log Kow shke flsk mtd
Alcohols, C12-15, ethoxylated	68131-39-5	Modeled BCF - Fish		Bioaccumulation factor	470	Catalogic™
Alcohols, C12-15, ethoxylated	68131-39-5	Experimental Bioconcentration		Log Kow	5.79	OECD 123 log Kow slow stir

12.4. Mobility in soil

Material	Identifier(s)	Test type	Study Type	Test result	Protocol
2-butoxyethanol	111-76-2	Estimated Mobility in Soil	Koc	67 l/kg	
2-aminoethanol	141-43-5	Experimental Mobility in Soil	Koc	200-500 l/kg	
Alcohols, C12-15, ethoxylated	68131-39-5	Modeled Mobility in Soil	Koc	280-2100	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Other adverse effects

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

SECTION 13: Disposal considerations

13.1 Waste treatment methods
Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Facility must be capable of handling aerosol cans. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)
070704* Other organic solvents, washing liquids and mother liquors

EU waste code (product container after use)
15 01 04 Metallic packaging

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 - UN Number or ID number	UN1950	UN1950	UN1950
14.2 UN proper shipping name	AEROSOLS	AEROSOLS, NON-FLAMMABLE, CONTAINING SUBSTANCES IN CLASS 8, PACKING GROUP III(ISOBORNYL METHACRYLATE; COPPER SALT)	AEROSOLS(ISOBORNYL METHACRYLATE; COPPER SALT)
14.3 Transport hazard class(es)	2.2	2.2	2.2
14.4 Packing group	No data available.	No data available.	No data available.

14.5 Environmental hazards	Environmentally Hazardous	Not applicable.	Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	5C	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient	Identifier(s)	Classification	Regulation
2-butoxyethanol	111-76-2	Gr. 3: Not classifiable	International Agency for Research on Cancer

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

COMAH Regulation, SI 2015/483

Seveso hazard categories, Annex 1, Part 1
None

Seveso named dangerous substances, Annex 1, Part 2
None

Regulation (EU) No 649/2012, as amended for GB
No chemicals listed

15.2. Chemical Safety Assessment
A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended for GB.

SECTION 16: Other information

List of relevant H statements

H220	Extremely flammable gas.
H229	Pressurised container: may burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

List of Relevant Notas

Nota K	The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w 1,3- butadiene (Einecs No 203-450-8), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 shall apply.
Nota S	This substance may not require a label according to Article 17 (see Section 1.3 of Annex I) (Table 3).
Nota U	When put on the market gases have to be classified as ‘Gases under pressure’, in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Nota 2).

Revision information:
EU Section 14 - Table Data information was added.
EU Section 14 - Table Headers information was added.
GB Section 15: Label remarks and EU Detergent information was modified.
GBSDS Section 14 Transport in bulk - Main Heading information was deleted.
GBSDS Section 14 UN Number information was deleted.
Label: Graphic information was modified.
Section 9: All Properties information was added.
Section 9: Vapour pressure value information was added.

Section 9: Vapour pressure value information was deleted.
Section 14 Classification Code – Main Heading information was deleted.
Section 14 Classification Code – Regulation Data information was deleted.
Section 14 Control Temperature – Main Heading information was deleted.
Section 14 Control Temperature – Regulation Data information was deleted.
Section 14 Emergency Temperature – Main Heading information was deleted.
Section 14 Emergency Temperature – Regulation Data information was deleted.
Section 14 Hazard Class + Sub Risk – Main Heading information was deleted.
Section 14 Hazard Class + Sub Risk – Regulation Data information was deleted.
Section 14 Other Dangerous Goods – Main Heading information was deleted.
Section 14 Other Dangerous Goods – Regulation Data information was deleted.
Section 14 Packing Group – Main Heading information was deleted.
Section 14 Packing Group – Regulation Data information was deleted.
Section 14 Proper Shipping Name information was deleted.
Section 14 Regulations – Main Headings information was deleted.
Section 14 Segregation – Regulation Data information was deleted.
Section 14 Segregation Code – Main Heading information was deleted.
Section 14 Special Precautions – Main Heading information was deleted.
Section 14 Special Precautions – Regulation Data information was deleted.
Section 14 Transport in bulk – Regulation Data information was deleted.
Section 14 UN Number Column data information was deleted.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M SDSs for Great Britain are available at www.3M.com/uk
For Northern Ireland documents, please contact your 3M representative to obtain a copy.