



Safety Data Sheet

Copyright, 2025, Solventum. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing Solventum products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from Solventum, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	34-6746-1	Version number:	3.00
Issue Date:	11/06/2025	Supersedes date:	29/02/2024

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

SECTION 1: Identification

1.1. Product identifier

3M™ Cavilon™ Advanced Skin Protectant 5050, 5050G, 5050G4P, 5051, 5051G, 5051C, 5051GP, 5051G4P

Product Identification Numbers

70-2007-8927-2 70-2011-8944-9 71-0001-5523-5

1.2. Recommended use and restrictions on use

Recommended use

Skin Protectant

For Professional use only.

1.3. Supplier's details

Address:	KCI Medical Australia Pty Ltd, Level 3, Building A, 1 Rivett Rd North Ryde, NSW 2113
Telephone:	1800945183
E Mail:	psops_supportteam@solventum.com
Website:	Solventum.com

1.4. Emergency telephone number

+61 2 9037 2994; (24/7) +1-703-527-3887; (24/7)

SECTION 2: Hazard identification

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.

Serious Eye Damage/Irritation: Category 2.

2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product

label.

Signal word

Danger

Symbols

Flame | Exclamation mark |

Pictograms



Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

Precautionary statements

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P264 Wash exposed skin thoroughly after handling.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice.

P370 + P378 In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other assigned/identified product hazards

This material has been tested for eye damage/irritation and the test results are reflected in the assigned classification.

2.4. Other hazards which do not result in classification

Very toxic to aquatic life with long lasting effects.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Hexamethylsiloxane	107-46-0	80 - 90
Acrylic Polymer	Trade Secret	5 - 10
2-Octyl Cyanoacrylate	133978-15-1	5 - 10

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

No need for first aid is anticipated. If symptoms develop, remove the affected person to fresh air. Get medical attention.

Skin contact

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Do not induce vomiting. Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.

Carbon dioxide.

Condition

During combustion.

During combustion.

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

Hazchem Code: 2YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools.

Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or

exhaust vapors, in accordance with good industrial hygiene practice. **WARNING !** A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid eye contact. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

8.2. Exposure controls

8.2.1. Engineering controls

Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face

protection(s) are recommended:

Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

Skin/hand protection

No chemical protective gloves are required.

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Colourless
Odour	Mild Alcohol
Odour threshold	<i>Not applicable.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	-59 °C
Boiling point/Initial boiling point/Boiling range	101 °C
Flash point	-8.3 °C [Test Method: Closed Cup]
Evaporation rate	<i>Not applicable.</i>
Flammability	Flammable Liquid: Category 2.
Flammable Limits(LEL)	0.5 %
Flammable Limits(UEL)	21.8 %
Vapour pressure	<i>Not applicable.</i>
Relative Vapor Density	5.61 [Ref Std: AIR=1]
Density	0.77 g/ml
Relative density	0.77
Water solubility	<i>Not applicable.</i>
Solubility- non-water	<i>Not applicable.</i>
Partition coefficient: n-octanol/water	<i>Not applicable.</i>
Autoignition temperature	<i>Not applicable.</i>
Decomposition temperature	<i>Not applicable.</i>
Kinematic Viscosity	<i>Not applicable.</i>
Volatile organic compounds (VOC)	<i>No data available.</i>
Percent volatile	<i>No data available.</i>
VOC less H ₂ O & exempt solvents	<i>No data available.</i>
Molecular weight	<i>Not applicable.</i>

Particle Characteristics	<i>Not applicable.</i>
--------------------------	------------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3. Conditions to avoid

Sparks and/or flames.

10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products**Substance****Condition**

None known.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

No health effects are expected.

Skin contact

Contact with the skin during product use is not expected to result in significant irritation.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Hexamethylsiloxane	Dermal	Rabbit	LD50 12,160 mg/kg
Hexamethylsiloxane	Inhalation-Vapour (4 hours)	Rat	LC50 106 mg/l
Hexamethylsiloxane	Ingestion	Rat	LD50 > 12,200 mg/kg
2-Octyl Cyanoacrylate	Ingestion	similar compounds	LD50 > 5,000 mg/kg
2-Octyl Cyanoacrylate	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Rabbit	No significant irritation
Hexamethylsiloxane	Rabbit	No significant irritation
2-Octyl Cyanoacrylate	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	In vitro data	Severe irritant
Hexamethylsiloxane	Rabbit	Mild irritant
2-Octyl Cyanoacrylate	similar compounds	No significant irritation

Skin Sensitisation

Name	Species	Value
Overall product	Human	Not classified
Hexamethylsiloxane	Human	Not classified
2-Octyl Cyanoacrylate	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Hexamethylsiloxane	In Vitro	Not mutagenic
Hexamethylsiloxane	In vivo	Not mutagenic
2-Octyl Cyanoacrylate	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Hexamethylsiloxane	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Hexamethylsiloxane	Inhalation	Not classified for female reproduction	Rabbit	NOAEL 33 mg/l	2 generation
Hexamethylsiloxane	Inhalation	Not classified for male reproduction	Rabbit	NOAEL 33 mg/l	2 generation
Hexamethylsiloxane	Inhalation	Not classified for development	Multiple animal species	NOAEL 19.9 mg/l	during gestation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Overall product	Dermal	heart skin endocrine	Not classified	Rat	NOAEL 63 mg/cm2/day	90 days

		system bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system kidney and/or bladder respiratory system vascular system				
Hexamethylsiloxane	Dermal	liver kidney and/or bladder endocrine system hematopoietic system nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	4 weeks
Hexamethylsiloxane	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 33 mg/l	13 weeks
Hexamethylsiloxane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 1.3 mg/l	13 weeks
Hexamethylsiloxane	Inhalation	heart endocrine system liver immune system nervous system eyes respiratory system	Not classified	Rat	NOAEL 33 mg/l	13 weeks
Hexamethylsiloxane	Ingestion	hematopoietic system liver immune system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 640 mg/kg/day	4 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Exposure Levels

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

Interactive Effects

Not Determined

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity**Acute aquatic hazard:**

GHS Acute 1: Very toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 1: Very toxic to aquatic life with long lasting effects.

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Hexamethylsiloxane	107-46-0	Green algae	Experimental	70 hours	ErC50	>0.55 mg/l
Hexamethylsiloxane	107-46-0	Rainbow trout	Experimental	96 hours	LC50	0.46 mg/l
Hexamethylsiloxane	107-46-0	Green algae	Experimental	70 hours	ErC10	0.09 mg/l
Hexamethylsiloxane	107-46-0	Water flea	Experimental	21 days	NOEC	0.08 mg/l
2-Octyl Cyanoacrylate	133978-15-1	N/A	Data not available or insufficient for classification	N/A	N/A	N/A

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Hexamethylsiloxane	107-46-0	Experimental Photolysis		Photolytic half-life (in air)	22.5 days (t 1/2)	
Hexamethylsiloxane	107-46-0	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	120 hours (t 1/2)	
2-Octyl Cyanoacrylate	133978-15-1	Data not available-insufficient	N/A	N/A	N/A	N/A

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Hexamethylsiloxane	107-46-0	Experimental BCF - Fish	56 days	Bioaccumulation factor	2410	OECD305-Bioconcentration
Hexamethylsiloxane	107-46-0	Experimental Bioconcentration		Log Kow	4.2	
2-Octyl Cyanoacrylate	133978-15-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

SECTION 14: Transport Information

Australian Dangerous Goods Code (ADG) - Road/Rail Transport

UN No.: UN1866

Proper shipping name: RESIN SOLUTION

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

Special Instructions: Limited quantity may apply

Hazchem Code: 2YE

IERG: 14

International Air Transport Association (IATA) - Air Transport

UN No.: UN1866

Proper shipping name: RESIN SOLUTION

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: UN1866

Proper shipping name: RESIN SOLUTION

Class/Division: 3

Sub Risk: Not applicable.

Packing Group: II

Marine Pollutant: Not applicable.

Special Instructions: Limited quantity may apply

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Australian Inventory Status:

This product is regulated by the Therapeutics Goods Administration and is exempt from compliance with the Industrial Chemicals (Notification and Assessment) Act 1989 as amended.

SECTION 16: Other information

Revision information:

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

Solventum Australia SDSs are available at [Solventum.com](https://www.solventum.com)