Safety Data Sheet

Copyright,2025, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	22-1415-3	**Version number:**	6.00
Issue Date:	2025/06/23	**Supercedes Date:**	2020/11/20

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier
HI-TEMP(TM) FILLER COMPOUND

Product Identification Numbers
80-6114-9049-3 98-0000-0711-6

1.2. Recommended use and restrictions on use

Intended Use
Exclude moisture and enhance mechanical holding strength

Restrictions on use
Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Electrical Markets Division
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number
Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
Skin Sensitizer: Category 1.
Carcinogenicity: Category 2.
Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements
Signal word
Danger

Symbols

Exclamation mark |Health Hazard |

Pictograms



Hazard Statements

May cause an allergic skin reaction. Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure: respiratory system.

Precautionary statements

Prevention:
Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wash exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves and respiratory protection.

Response:
IF ON SKIN: Wash with plenty of soap and water. IF exposed or concerned: Get medical attention. Get medical attention if you feel unwell. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash it before reuse.

Storage:
Store locked up.

Disposal:
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

2.3. Other hazards
None known.

41% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Synthetic Amorphous Silica, Fumed, Crystalline Free	112945-52-5	30 - 60	Fumed amorphous silica, crystalline-free
Aluminum Oxide	1344-28-1	15 - 45	Aluminum oxide (Al2O3)
Other non-hazardous fillers	Trade Secret	30 - 45	Not Applicable
Aluminum	7429-90-5	1 - 5	Aluminum
Nickel	7440-02-0	1 - 5 Trade Secret *	Nickel

*The concentration (exact or range) of this component has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:
Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required
Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Unsuitable extinguishing media
None Determined

5.3. Special hazards arising from the substance or mixture
None inherent in this product.

Hazardous Decomposition or By-Products

Substance	Condition
Formaldehyde	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

5.4. Special protection actions for fire-fighters
No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice.

6.2. Environmental precautions
Avoid release to the environment.

6.3. Methods and material for containment and cleaning up
Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
For industrial or professional use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities
Store away from heat. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m3	
Aluminum	7429-90-5	ACGIH	TWA(respirable fraction):1 mg/m3	
Nickel	7440-02-0	ACGIH	TWA (inhalable fraction):1.5 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the

results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.
Gloves made from the following material(s) are recommended: Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Nitrile

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Specific Physical Form:	Paste
Colour	Milky White
Odour	Odourless
Odour threshold	*No Data Available*
pH	*Not Applicable*
Melting point/Freezing point	*No Data Available*
Boiling point	*No Data Available*
Flash Point	> 260 ºC [*Test Method:*Closed Cup]
Evaporation rate	*Not Applicable*
Flammability	Not Applicable
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapour Pressure	*No Data Available*
Relative Vapour Density	*No Data Available*
Density	2.3 kg/l
Relative density	2.3 [*Ref Std:*WATER=1]
Water solubility	Negligible
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	*Not Applicable*
Volatile Organic Compounds	*No Data Available*
Percent volatile	*Not Applicable*
VOC Less H2O & Exempt Solvents	*No Data Available*
Average particle size	*No Data Available*
Bulk density	*No Data Available*
Molecular weight	*No Data Available*

Softening point	*No Data Available*

Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat

10.5. Incompatible materials
Not determined

No Data Available

10.6. Hazardous decomposition products

Substance	**Condition**
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
May be harmful if inhaled. May cause additional health effects (see below).

Skin Contact:
Mechanical Skin irritation: Signs/symptoms may include abrasion, redness, pain, and itching. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:
Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

Ingestion:
Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:
Respiratory Effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and/or respiratory failure.

Carcinogenicity:
Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
NICKEL (METALLIC)	7440-02-0	Anticipated human carcinogen	National Toxicology Program Carcinogens
Nickel, metallic and alloys	7440-02-0	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >5 - =12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Synthetic Amorphous Silica, Fumed, Crystalline Free	Dermal	Rabbit	LD50 > 5,000 mg/kg
Synthetic Amorphous Silica, Fumed, Crystalline Free	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Rat	LD50 > 5,110 mg/kg
Other non-hazardous fillers	Dermal	Multiple animal species	LD50 > 2,000 mg/kg
Other non-hazardous fillers	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminum Oxide	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum Oxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminum	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum	Ingestion		LD50 estimated to be > 5,000 mg/kg
Nickel	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminum	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.888 mg/l
Nickel	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.55 mg/l
Nickel	Ingestion	Rat	LD50 > 9,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Synthetic Amorphous Silica, Fumed, Crystalline Free	Rabbit	No significant irritation
Other non-hazardous fillers	Human and animal	No significant irritation
Aluminum Oxide	Rabbit	No significant irritation
Aluminum	Rabbit	No significant irritation
Nickel	Rabbit	Minimal irritation

Serious Eye Damage/Irritation

Name	Species	Value
Synthetic Amorphous Silica, Fumed, Crystalline Free	Rabbit	No significant irritation
Other non-hazardous fillers	Rabbit	No significant irritation
Aluminum Oxide	Rabbit	No significant irritation
Aluminum	Rabbit	No significant irritation
Nickel	Rabbit	Mild irritant

Skin Sensitization

Name	Species	Value
Synthetic Amorphous Silica, Fumed, Crystalline Free	Human and animal	Not classified
Other non-hazardous fillers	Human and animal	Not classified
Aluminum	Guinea pig	Not classified
Nickel	Human	Sensitizing

Respiratory Sensitization

Name	Species	Value
Aluminum	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Synthetic Amorphous Silica, Fumed, Crystalline Free	In Vitro	Not mutagenic
Other non-hazardous fillers	In Vitro	Not mutagenic
Other non-hazardous fillers	In vivo	Not mutagenic
Aluminum Oxide	In Vitro	Not mutagenic
Aluminum	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Synthetic Amorphous Silica, Fumed, Crystalline Free	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Other non-hazardous fillers	Dermal	Mouse	Not carcinogenic
Other non-hazardous fillers	Ingestion	Mouse	Not carcinogenic
Aluminum Oxide	Inhalation	Rat	Not carcinogenic
Nickel	Inhalation	similar compounds	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Synthetic Amorphous Silica, Fumed, Crystalline Free	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Other non-hazardous fillers	Ingestion	Not classified for development	Rat	NOAEL 3,800 mg/kg/day	during organogenesis
Other non-hazardous fillers	Dermal	Not classified for development	Rabbit	NOAEL 1,000 mg/kg/day	during organogenesi

					s

Target Organ(s)

Specific Target Organ Toxicity - single exposure
For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Synthetic Amorphous Silica, Fumed, Crystalline Free	Inhalation	respiratory system | silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Other non-hazardous fillers	Ingestion	eyes	Not classified	Rat	NOAEL 10%	90 days
Other non-hazardous fillers	Ingestion	respiratory system	Not classified	Rat	NOAEL 1%	90 days
Other non-hazardous fillers	Ingestion	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 10%	90 days
Other non-hazardous fillers	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 10%	90 days
Other non-hazardous fillers	Ingestion	heart | liver | kidney and/or bladder | vascular system	Not classified	Rat	NOAEL 1%	90 days
Aluminum Oxide	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Aluminum	Inhalation	nervous system | respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Nickel	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.001 mg/l	13 weeks

Aspiration Hazard
For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.
Health: 2 **Flammability:** 0 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification
Health: *2 **Flammability:** 0 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document group:	22-1415-3	**Version number:**	6.00
Issue Date:	2025/06/23	**Supercedes Date:**	2020/11/20

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca