



## Safety Data Sheet

Copyright,2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 33-7190-3  
**Revision date:** 17/12/2025

**Version number:** 5.00  
**Supersedes date:** 06/12/2022

**Transportation version number:**

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8425NS Green

#### Product Identification Numbers

62-2862-1445-7 62-2862-3630-2

7100078165 7100078166

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Structural adhesive.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2  
**Telephone:** +353 1 280 3555  
**E Mail:** ner-productstewardship@mmm.com

**Website:** www.3M.com

#### 1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

**This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:**

33-7187-9, 33-7188-7

### TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

## KIT LABEL

### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

#### CLASSIFICATION:

Flammable Liquid, Category 2 - Flam. Liq. 2; H225

Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315

Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H335

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

### 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

#### SIGNAL WORD

DANGER.

#### Symbols

GHS02 (Flame) |GHS07 (Exclamation mark) |

#### Pictograms



Contains:

2-hydroxyethyl methacrylate; methyl methacrylate; Tert-butyl 3,5,5-trimethylperoxyhexanoate.

#### HAZARD STATEMENTS:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENTS

##### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261A Avoid breathing vapours.  
P280E Wear protective gloves.

##### Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
P370 + P378 In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

**For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:**

**<=125 ml Hazard statements**

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

**<=125 ml Precautionary statements**

**Prevention:**

P280E Wear protective gloves.

**Response:**

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Refer to Safety Data Sheet for component % unknown values ([www.3M.com/msds](http://www.3M.com/msds)).

Nota L applied.

**Revision information:**

Kit: Component document group number(s) information was modified.

Label: CLP Ingredients - kit components information was modified.

Section 1: Address information was modified.

Section 1: E-mail address information was modified.

Section 2: <125ml Hazard - Environmental information was added.

CLP Remark(phrase) information was added.

Label: CLP Classification information was modified.

Label: CLP Environmental Hazard Statements information was modified.

Label: CLP Precautionary - Prevention information was modified.

Label: CLP Precautionary - Response information was modified.

Label: Graphic information was modified.

Section 15: Label remarks and EU Detergent information was deleted.



## Safety Data Sheet

Copyright, 2025, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 33-7187-9      **Version number:** 8.00  
**Revision date:** 17/12/2025      **Supersedes date:** 06/06/2024

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M™ Scotch-Weld™ Acrylic Adhesive DP8425NS Green and Acrylic Adhesive 8425NS Green, Part B

#### Product Identification Numbers

62-2862-9530-8

7100084535

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Product

Only for industrial use.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2  
**Telephone:** +353 1 280 3555  
**E Mail:** ner-productstewardship@mmm.com  
**Website:** www.3M.com

#### 1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

##### CLASSIFICATION:

Flammable Liquid, Category 2 - Flam. Liq. 2; H225  
 Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315  
 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319  
 Skin Sensitization, Category 1 - Skin Sens. 1; H317  
 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H335

For full text of H phrases, see Section 16.

## 2.2. Label elements

### CLP REGULATION (EC) No 1272/2008

#### SIGNAL WORD

DANGER.

#### Symbols

GHS02 (Flame) |GHS07 (Exclamation mark) |

#### Pictograms



#### Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
methyl methacrylate	80-62-6	201-297-1	45 - 70
2-hydroxyethyl methacrylate	868-77-9	212-782-2	1 - 5

#### HAZARD STATEMENTS:

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.

#### PRECAUTIONARY STATEMENTS

##### Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261A	Avoid breathing vapours.
P280E	Wear protective gloves.

##### Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P370 + P378	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

#### For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:

##### <=125 ml Hazard statements

H317	May cause an allergic skin reaction.
------	--------------------------------------

## &lt;=125 ml Precautionary statements

**Prevention:**

P280E Wear protective gloves.

**Response:**

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Contains 7% of components with unknown hazards to the aquatic environment.

Nota L applied.

**2.3. Other hazards**

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

**SECTION 3: Composition/information on ingredients****3.1. Substances**

Not applicable

**3.2. Mixtures**

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
methyl methacrylate	(CAS-No.) 80-62-6 (EC-No.) 201-297-1 (REACH-No.) 01-2119452498-28	45 - 70	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335 Nota D
Acrylonitrile - butadiene polymer	(CAS-No.) 9003-18-3	1 - 25	Substance not classified as hazardous
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	(CAS-No.) 41637-38-1	0.1 - 10	Substance not classified as hazardous
Kaolin	(CAS-No.) 1332-58-7 (EC-No.) 310-194-1	3 - 7	Substance with a national occupational exposure limit
Siloxanes and Silicones, di-Me, reaction products with silica	(CAS-No.) 67762-90-7	3 - 7	Substance not classified as hazardous
CALCIUM STEARATE	(CAS-No.) 1592-23-0 (EC-No.) 216-472-8	0.1 - 5	Substance with a national occupational exposure limit
Distillates (petroleum), hydrotreated light paraffinic	(CAS-No.) 64742-55-8 (EC-No.) 265-158-7	1 - 5	Nota L Asp. Tox. 1, H304
2-hydroxyethyl methacrylate	(CAS-No.) 868-77-9 (EC-No.) 212-782-2 (REACH-No.) 01-2119490169-29	1 - 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Nota D
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w. -	(CAS-No.) 95175-93-2	< 3	Skin Irrit. 2, H315 Eye Dam. 1, H318

(phosphonoxy)- naphthenic acids, copper salts	(CAS-No.) 1338-02-9 (EC-No.) 215-657-0	< 0.2	Flam. Liq. 3, H226 Acute Tox. 4, H302 Aquatic Acute 1, H400, M=10 Aquatic Chronic 1, H410, M=1
--	---	-------	---

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain).

Irritation to the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision).

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### Hazardous Decomposition or By-Products

#### Substance

Carbon monoxide  
Carbon dioxide.  
Hydrogen Chloride  
Oxides of nitrogen.

#### Condition

During combustion.  
During combustion.  
During combustion.  
During combustion.

### 5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure

demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Kaolin	1332-58-7	Ireland OELs	TWA(as respirable dust)(8 hours):2 mg/m <sup>3</sup>	
Stearates (except lead stearate)	1592-23-0	Ireland OELs	TWA(8 hours):10 mg/m <sup>3</sup>	
methyl methacrylate	80-62-6	Ireland OELs	TWA(8 hours):50 ppm;TWA(8 hours):50 ppm;STEL(15 minutes):100 ppm;STEL(15 minutes):100 ppm	Respiratory/Dermal Sensitizer

Ireland OELs : Ireland. OELs

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

#### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

#### Derived no effect level (DNEL)

Ingredient	Degradation Product	Population	Human exposure pattern	DNEL
methyl methacrylate		Worker	Dermal, Long-term exposure (8 hours), Local effects	1.5 mg/cm <sup>2</sup>
methyl methacrylate		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	13.67 mg/kg bw/d
methyl methacrylate		Worker	Dermal, Short-term exposure, Local effects	1.5 mg/cm <sup>2</sup>
methyl methacrylate		Worker	Inhalation, Long-term exposure (8 hours), Local effects	208 mg/m <sup>3</sup>
methyl methacrylate		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	208 mg/m <sup>3</sup>
methyl methacrylate		Worker	Inhalation, Short-term exposure, Local effects	416 mg/m <sup>3</sup>
2-hydroxyethyl methacrylate		Worker	Dermal, Long-term exposure (8 hours), Systemic effects	1.3 mg/kg bw/d
2-hydroxyethyl methacrylate		Worker	Inhalation, Long-term exposure (8 hours), Systemic effects	4.9 mg/m <sup>3</sup>

#### Predicted no effect concentrations (PNEC)

Ingredient	Degradation Product	Compartment	PNEC
methyl methacrylate		Freshwater	0.94 mg/l
methyl methacrylate		Freshwater sediments	5.74 mg/kg d.w.

methyl methacrylate		Intermittent releases to water	0.94 mg/l
methyl methacrylate		Marine water	0.94 mg/l
2-hydroxyethyl methacrylate		Agricultural soil	0.476 mg/kg d.w.
2-hydroxyethyl methacrylate		Freshwater	0.482 mg/l
2-hydroxyethyl methacrylate		Freshwater sediments	3.79 mg/kg d.w.
2-hydroxyethyl methacrylate		Intermittent releases to water	1 mg/l
2-hydroxyethyl methacrylate		Marine water	0.482 mg/l
2-hydroxyethyl methacrylate		Marine water sediments	3.79 mg/kg d.w.
2-hydroxyethyl methacrylate		Sewage Treatment Plant	10 mg/l

**Recommended monitoring procedures:** Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

## 8.2. Exposure controls

In addition, refer to the annex for more information.

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Indirect vented goggles.

#### Applicable Norms/Standards

Use eye protection conforming to EN 16321

#### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	0.5	=>8 hours
Polymer laminate	>0.30	4-8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

*Applicable Norms/Standards*  
Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

*Applicable Norms/Standards*

Use a respirator conforming to EN 140 or EN 136: filter types A & P

**8.2.3. Environmental exposure controls**

Refer to Annex

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	White
Odor	Strong Methacrylate
Odour threshold	No data available.
Melting point/freezing point	Not applicable.
Boiling point/boiling range	>=37.8 °C
Flammability	Flammable Liquid: Category 2.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Flash point	>=10 °C [Test Method:Closed Cup]
Autoignition temperature	No data available.
Decomposition temperature	No data available.
pH	substance/mixture is non-soluble (in water)
Kinematic Viscosity	73,913 mm <sup>2</sup> /sec
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	No data available.
Density	1.15 g/ml
Relative density	1.15 [Ref Std:WATER=1]
Relative Vapour Density	No data available.
Particle Characteristics	Not applicable.

**9.2. Other information**

**9.2.2 Other safety characteristics**

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Molecular weight	<i>No data available.</i>

**SECTION 10: Stability and reactivity****10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

**10.2 Chemical stability**

Stable.

**10.3 Possibility of hazardous reactions**

Hazardous polymerisation will not occur.

**10.4 Conditions to avoid**

Heat.

Sparks and/or flames.

**10.5 Incompatible materials**

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

**10.6 Hazardous decomposition products**

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Signs and Symptoms of Exposure**

**Based on test data and/or information on the components, this material may produce the following health effects:**

**Inhalation**

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

**Skin contact**

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain.

Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye contact**

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**Ingestion**

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

**Additional Health Effects:****Prolonged or repeated exposure may cause target organ effects:**

Olfactory effects: Signs/symptoms may include decreased ability to detect odours and complete loss of smell.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
methyl methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
methyl methacrylate	Inhalation-Vapour (4 hours)	Rat	LC50 29.8 mg/l
methyl methacrylate	Ingestion	Rat	LD50 7,900 mg/kg
Acrylonitrile - butadiene polymer	Dermal	Rabbit	LD50 > 15,000 mg/kg
Acrylonitrile - butadiene polymer	Ingestion	Rat	LD50 > 30,000 mg/kg
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	Dermal	Rat	LD50 > 2,000 mg/kg
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	Ingestion	Rat	LD50 > 35,000 mg/kg
Kaolin	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolin	Ingestion	Human	LD50 > 15,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Rat	LD50 > 5,110 mg/kg
2-hydroxyethyl methacrylate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2-hydroxyethyl methacrylate	Ingestion	Rat	LD50 5,564 mg/kg
Distillates (petroleum), hydrotreated light paraffinic	Dermal	similar compounds	LD50 > 2,000 mg/kg
Distillates (petroleum), hydrotreated light paraffinic	Inhalation-Dust/Mist (4 hours)	similar compounds	LC50 > 5.53 mg/l
Distillates (petroleum), hydrotreated light paraffinic	Ingestion	similar compounds	LD50 > 5,000 mg/kg
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	Dermal	similar health hazards	LD50 estimated to be > 5,000 mg/kg
CALCIUM STEARATE	Dermal	Rat	LD50 > 2,000 mg/kg
CALCIUM STEARATE	Ingestion	Rat	LD50 > 2,000 mg/kg
naphthenic acids, copper salts	Dermal	similar compounds	LD50 > 2,000 mg/kg

naphthenic acids, copper salts	Ingestion	similar compounds	LD50 >300, < 2,000 mg/kg
--------------------------------	-----------	-------------------	--------------------------

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
methyl methacrylate	Rabbit	Irritant
Acrylonitrile - butadiene polymer	Professional judgement	No significant irritation
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	Rabbit	Minimal irritation
Kaolin	Professional judgement	No significant irritation
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
2-hydroxyethyl methacrylate	Rabbit	Minimal irritation
Distillates (petroleum), hydrotreated light paraffinic	similar compounds	No significant irritation
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	Not available	Irritant
CALCIUM STEARATE	In vitro data	No significant irritation
naphthenic acids, copper salts	Rabbit	No significant irritation

### Serious Eye Damage/Irritation

Name	Species	Value
methyl methacrylate	Rabbit	Mild irritant
Acrylonitrile - butadiene polymer	Professional judgement	No significant irritation
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	Rabbit	No significant irritation
Kaolin	Professional judgement	No significant irritation
Siloxanes and Silicones, di-Me, reaction products with silica	Rabbit	No significant irritation
2-hydroxyethyl methacrylate	Rabbit	Moderate irritant
Distillates (petroleum), hydrotreated light paraffinic	similar compounds	No significant irritation
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	Not available	Corrosive
CALCIUM STEARATE	In vitro data	No significant irritation
naphthenic acids, copper salts	In vitro data	No significant irritation

### Skin Sensitisation

Name	Species	Value
methyl methacrylate	Human and animal	Sensitising
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	Guinea pig	Not classified
Siloxanes and Silicones, di-Me, reaction products with silica	Human and	Not classified

2-hydroxyethyl methacrylate	animal Human and animal	Sensitising
Distillates (petroleum), hydrotreated light paraffinic	similar compounds	Not classified
CALCIUM STEARATE	similar compounds	Not classified
naphthenic acids, copper salts	Guinea pig	Not classified

### Respiratory Sensitisation

Name	Species	Value
methyl methacrylate	Human	Not classified

### Germ Cell Mutagenicity

Name	Route	Value
methyl methacrylate	In vivo	Not mutagenic
methyl methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	In Vitro	Not mutagenic
Siloxanes and Silicones, di-Me, reaction products with silica	In Vitro	Not mutagenic
2-hydroxyethyl methacrylate	In vivo	Not mutagenic
2-hydroxyethyl methacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Distillates (petroleum), hydrotreated light paraffinic	In Vitro	Not mutagenic
CALCIUM STEARATE	In Vitro	Not mutagenic

### Carcinogenicity

Name	Route	Species	Value
methyl methacrylate	Ingestion	Rat	Not carcinogenic
methyl methacrylate	Inhalation	Human and animal	Not carcinogenic
Kaolin	Inhalation	Multiple animal species	Not carcinogenic
Siloxanes and Silicones, di-Me, reaction products with silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
methyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
methyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
methyl methacrylate	Ingestion	Not classified for development	Rabbit	NOAEL 450 mg/kg/day	during gestation
methyl methacrylate	Inhalation	Not classified for development	Rat	NOAEL 8.3 mg/l	during organogenesis
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Siloxanes and Silicones, di-Me, reaction products with silica	Ingestion	Not classified for development	Rat	NOAEL 1,350	during organogenesis

				mg/kg/day	
2-hydroxyethyl methacrylate	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	pre mating & during gestation
2-hydroxyethyl methacrylate	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	49 days
2-hydroxyethyl methacrylate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	pre mating & during gestation
CALCIUM STEARATE	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	pre mating into lactation
CALCIUM STEARATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
CALCIUM STEARATE	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	pre mating into lactation

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
methyl methacrylate	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	occupational exposure
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

#### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
methyl methacrylate	Dermal	peripheral nervous system	Not classified	Human	NOAEL Not available	occupational exposure
methyl methacrylate	Inhalation	olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
methyl methacrylate	Inhalation	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	14 weeks
methyl methacrylate	Inhalation	liver	Not classified	Mouse	NOAEL 12.3 mg/l	14 weeks
methyl methacrylate	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
methyl methacrylate	Ingestion	kidney and/or bladder   heart   skin   endocrine system   gastrointestinal tract   hematopoietic system   liver   muscles   nervous system   respiratory system	Not classified	Rat	NOAEL 90.3 mg/kg/day	2 years
Kaolin	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Kaolin	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
Siloxanes and Silicones, di-Me, reaction products with silica	Inhalation	respiratory system   silicosis	Not classified	Human	NOAEL Not available	occupational exposure
CALCIUM STEARATE	Ingestion	hematopoietic system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	28 days

		heart   skin   endocrine system   gastrointestinal tract   bone, teeth, nails, and/or hair   liver   immune system   eyes   respiratory system				
--	--	--	--	--	--	--

### Aspiration Hazard

Name	Value
Distillates (petroleum), hydrotreated light paraffinic	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

### 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

## SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

### 12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
methyl methacrylate	80-62-6	Green algae	Experimental	72 hours	EC50	>110 mg/l
methyl methacrylate	80-62-6	Rainbow trout	Experimental	96 hours	LC50	>79 mg/l
methyl methacrylate	80-62-6	Water flea	Experimental	48 hours	EC50	69 mg/l
methyl methacrylate	80-62-6	Green algae	Experimental	72 hours	NOEC	110 mg/l
methyl methacrylate	80-62-6	Water flea	Experimental	21 days	NOEC	37 mg/l
methyl methacrylate	80-62-6	Activated sludge	Experimental	30 minutes	EC20	150 mg/l
methyl methacrylate	80-62-6	Soil microbes	Experimental	28 days	NOEC	>1,000 mg/kg (Dry Weight)
Acrylonitrile - butadiene polymer	9003-18-3	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	41637-38-1	Activated sludge	Estimated	3 hours	EC50	>1,000 mg/l
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	41637-38-1	Green algae	Estimated	72 hours	EL50	>100 mg/l
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	41637-38-1	Water flea	Estimated	48 hours	EL50	>100 mg/l

Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	41637-38-1	Zebra Fish	Estimated	96 hours	LL50	>100 mg/l
Kaolin	1332-58-7	Water flea	Experimental	48 hours	LC50	>1,100 mg/l
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
2-hydroxyethyl methacrylate	868-77-9	Turbot	Analogous Compound	96 hours	LC50	833 mg/l
2-hydroxyethyl methacrylate	868-77-9	Fathead minnow	Experimental	96 hours	LC50	227 mg/l
2-hydroxyethyl methacrylate	868-77-9	Green algae	Experimental	72 hours	EC50	710 mg/l
2-hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	48 hours	EC50	380 mg/l
2-hydroxyethyl methacrylate	868-77-9	Green algae	Experimental	72 hours	NOEC	160 mg/l
2-hydroxyethyl methacrylate	868-77-9	Water flea	Experimental	21 days	NOEC	24.1 mg/l
2-hydroxyethyl methacrylate	868-77-9	N/A	Experimental	16 hours	EC0	>3,000 mg/l
2-hydroxyethyl methacrylate	868-77-9	N/A	Experimental	18 hours	LD50	<98 mg per kg of bodyweight
CALCIUM STEARATE	1592-23-0	Green algae	Experimental	72 hours	EC50	>100 mg/l
CALCIUM STEARATE	1592-23-0	Medaka	Experimental	96 hours	LC50	>100 mg/l
CALCIUM STEARATE	1592-23-0	Green algae	Experimental	72 hours	NOEC	100 mg/l
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	Fathead minnow	Estimated	96 hours	LL50	>100 mg/l
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	Water flea	Estimated	48 hours	EL50	>100 mg/l
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	Green algae	Estimated	72 hours	NOEL	100 mg/l
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	Water flea	Estimated	21 days	NOEC	10 mg/l
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	95175-93-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
naphthenic acids, copper salts	1338-02-9	Green algae	Estimated	72 hours	ErC50	0.629 mg/l
naphthenic acids, copper salts	1338-02-9	Water flea	Estimated	48 hours	EC50	0.0756 mg/l
naphthenic acids, copper salts	1338-02-9	Zebra Fish	Estimated	96 hours	LC50	0.07 mg/l
naphthenic acids, copper salts	1338-02-9	Fathead minnow	Estimated	32 days	EC10	0.0354 mg/l
naphthenic acids, copper salts	1338-02-9	Green algae	Estimated	N/A	NOEC	0.132 mg/l
naphthenic acids, copper salts	1338-02-9	Sediment Worm	Estimated	28 days	NOEC	110 mg/kg (Dry Weight)
naphthenic acids, copper salts	1338-02-9	Water flea	Estimated	7 days	NOEC	0.02 mg/l
naphthenic acids, copper salts	1338-02-9	Activated sludge	Estimated	N/A	EC50	42 mg/l
naphthenic acids, copper salts	1338-02-9	Barley	Estimated	4 days	NOEC	96 mg/kg (Dry Weight)

naphthenic acids, copper salts	1338-02-9	Redworm	Estimated	56 days	NOEC	60 mg/kg (Dry Weight)
naphthenic acids, copper salts	1338-02-9	Soil microbes	Estimated	4 days	NOEC	72 mg/kg (Dry Weight)
naphthenic acids, copper salts	1338-02-9	Springtail	Estimated	28 days	NOEC	167 mg/kg (Dry Weight)

## 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
methyl methacrylate	80-62-6	Experimental Biodegradation	14 days	BOD	94 %BOD/ThO D	OECD 301C - MITI test (I)
Acrylonitrile - butadiene polymer	9003-18-3	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	41637-38-1	Experimental Biodegradation	28 days	Percent degraded	24 %degraded	
Kaolin	1332-58-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A
2-hydroxyethyl methacrylate	868-77-9	Experimental Biodegradation	28 days	BOD	84 %BOD/CO D	OECD 301D - Closed bottle test
2-hydroxyethyl methacrylate	868-77-9	Experimental Hydrolysis		Hydrolytic half-life basic pH	10.9 days (t 1/2)	OECD 111 Hydrolysis func of pH
CALCIUM STEARATE	1592-23-0	Experimental Biodegradation	24 days	CO2 evolution	91 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	Estimated Biodegradation	28 days	CO2 evolution	22 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Poly[oxy(methyl-1,2-ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.-(phosphonoxy)-	95175-93-2	Data not availbl-insufficient	N/A	N/A	N/A	N/A
naphthenic acids, copper salts	1338-02-9	Data not availbl-insufficient	N/A	N/A	N/A	N/A

## 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
methyl methacrylate	80-62-6	Experimental Bioconcentration		Log Kow	1.38	OECD 107 log Kow shke flsk mtd
Acrylonitrile - butadiene polymer	9003-18-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Bisphenol A polyethylene glycol diether dimethacrylate (polymer)	41637-38-1	Estimated Bioconcentration		Bioaccumulation factor	6.6	
Kaolin	1332-58-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Siloxanes and Silicones, di-Me, reaction products with silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2-hydroxyethyl methacrylate	868-77-9	Experimental Bioconcentration		Log Kow	0.42	OECD 107 log Kow shke flsk mtd
CALCIUM STEARATE	1592-23-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Poly[oxy(methyl-1,2-	95175-93-2	Data not available	N/A	N/A	N/A	N/A

ethanediyl)], .a.-(2-methyl-1-oxo-2-propenyl)-.w.- (phosphonoxy)-		or insufficient for classification				
naphthenic acids, copper salts	1338-02-9	Analogous Compound BCF - Fish	42 days	Bioaccumulation factor	≤27	OECD305-Bioconcentration

## 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
methyl methacrylate	80-62-6	Experimental Mobility in Soil	Koc	8.7-72 l/kg	
2-hydroxyethyl methacrylate	868-77-9	Experimental Mobility in Soil	Koc	42.7 l/kg	

## 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

## 12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

### EU waste code (product as sold)

08 04 09\* Waste adhesives and sealants containing organic solvents or other dangerous substances  
20 01 27\* Paint, inks, adhesives and resins containing dangerous substances

## SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 UN number or ID number	UN1133	UN1133	UN1133

<b>14.2 UN proper shipping name</b>	ADHESIVES	ADHESIVES	ADHESIVES
<b>14.3 Transport hazard class(es)</b>	3	3	3
<b>14.4 Packing group</b>	II	II	II
<b>14.5 Environmental hazards</b>	Not Environmentally Hazardous	Not applicable	Not a Marine Pollutant
<b>14.6 Special precautions for user</b>	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
<b>14.7 Marine Transport in bulk according to IMO instruments</b>	No data available.	No data available.	No data available.
<b>Control Temperature</b>	No data available.	No data available.	No data available.
<b>Emergency Temperature</b>	No data available.	No data available.	No data available.
<b>ADR Classification Code</b>	F1	Not applicable.	Not applicable.
<b>IMDG Segregation Code</b>	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Carcinogenicity

**Ingredient**  
methyl methacrylate

**CAS Nbr**  
80-62-6

**Classification**  
Gr. 3: Not classifiable

**Regulation**  
International Agency for Research on Cancer

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

**DIRECTIVE 2012/18/EU**

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
P5c FLAMMABLE LIQUIDS*	5000	50000

\*If maintained at a temperature above its boiling point or if particular processing conditions, such as high pressure or high temperature, may create major-accident hazards, P5a or P5b FLAMMABLE LIQUIDS may apply

Seveso named dangerous substances, Annex 1, Part 2

None

**Regulation (EU) No 649/2012**

No chemicals listed

**15.2. Chemical Safety Assessment**

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

## SECTION 16: Other information

**List of relevant H statements**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

**Revision information:**

Section 1: Address information was modified.

Section 1: E-mail address information was modified.

Section 1: Product use information information was modified.

Section 2: &lt;125ml Precautionary - Prevention information was modified.

CLP: Ingredient table information was modified.

Section 3: Composition/ Information of ingredients table information was modified.

Section 6: Accidental release personal information information was modified.

Section 7: Conditions safe storage information was modified.

Section 8: Occupational exposure limit table information was modified.

Section 08: Personal Protection - Apron Statement information was added.

Section 9: Property description for optional properties information was modified.

Section 11: Acute Toxicity table information was modified.

Section 11: Carcinogenicity Table information was modified.

Section 11: Germ Cell Mutagenicity Table information was modified.

Section 11: Reproductive Toxicity Table information was modified.

Section 11: Serious Eye Damage/Irritation Table information was modified.

Section 11: Skin Corrosion/Irritation Table information was modified.  
 Section 11: Skin Sensitization Table information was modified.  
 Section 11: Target Organs - Repeated Table information was modified.  
 Section 12: Component ecotoxicity information information was modified.  
 Section 12: Persistence and Degradability information information was modified.  
 Section 12: Biocumulative potential information information was modified.  
 Section 14 Proper Shipping Name information was modified.  
 Section 15: Label remarks and EU Detergent information was deleted.

## Annex

<b>1. Title</b>	
<b>Substance identification</b>	
<b>Exposure Scenario Name</b>	Article Service Life and Disposal
<b>Lifecycle Stage</b>	Widespread use by professional workers
<b>Contributing activities</b>	-Not applicable. - ERC 11a -Widespread use of articles with low release (indoor)
<b>Processes, tasks and activities covered</b>	Article service life.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	Physical state:Liquid.
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> None needed; <b>Environmental:</b> None needed;
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

<b>1. Title</b>	
<b>Substance identification</b>	methyl methacrylate; EC No. 201-297-1; CAS Nbr 80-62-6;
<b>Exposure Scenario Name</b>	Formulation
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 03 -Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition PROC 08a -Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities ERC 02 -Formulation into mixture
<b>Processes, tasks and activities covered</b>	Mixing operations (closed systems). Transfers with dedicated controls, including loading, filling, dumping, bagging.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	Physical state:Liquid. <b>General operating conditions:</b> Continuous release; Duration of use: 4 hours/day;

	<p>Emission days per year: 300 days/year; Indoor use;</p> <p><b>Task: Spraying;</b> Duration of use: &lt; 15 min task;</p> <p><b>Task: PROC03;</b> Closed process;</p>
<b>Risk management measures</b>	<p>Under the operational conditions described above the following risk management measures apply:</p> <p><b>General risk management measures:</b></p> <p><b>Human health:</b> Goggles - Chemical resistant; Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.;</p> <p>Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour);</p> <p><b>Environmental:</b> None needed; ;</p> <p>The following task-specific risk management measures apply in addition to those listed above:</p> <p><b>Task: PROC08a;</b> <b>Human Health;</b> Local exhaust ventilation;</p>
<b>Waste management measures</b>	<p>Do not apply industrial sludge to natural soils; Send to an industrial sewage treatment plant;</p>
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

<b>1. Title</b>	
<b>Substance identification</b>	methyl methacrylate; EC No. 201-297-1; CAS Nbr 80-62-6;
<b>Exposure Scenario Name</b>	Industrial Use of Adhesives
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 05 -Mixing or blending in batch processes PROC 08b -Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC 13 -Treatment of articles by dipping and pouring ERC 06c -Use of monomer in polymerisation processes at industrial site (inclusion or not into/onto article)
<b>Processes, tasks and activities covered</b>	Application of product through a mixing nozzle Mixing or blending of solid or liquid materials. Transfer of substance/mixture with dedicated engineering controls.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<p><b>Physical state:</b>Liquid.</p> <p><b>General operating conditions:</b> Continuous process; Duration of use: 8 hours/day; Emission days per year: 300 days/year; Indoor use;</p>
<b>Risk management measures</b>	<p>Under the operational conditions described above the following risk management measures apply:</p> <p><b>General risk management measures:</b></p> <p><b>Human health:</b></p>

	<p>Goggles - Chemical resistant;      Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.;      Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour);  <b>Environmental:</b>      Industrial Sewage Treatment Plant;      ;      The following task-specific risk management measures apply in addition to those listed above:  <b>Task: PROC05;</b>  <b>Human Health;</b>      Local exhaust ventilation;</p> <p><b>Task: PROC13;</b>  <b>Human Health;</b>      Local exhaust ventilation;</p>
<b>Waste management measures</b>	Do not apply industrial sludge to natural soils;
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

<b>1. Title</b>	
<b>Substance identification</b>	2-hydroxyethyl methacrylate; EC No. 212-782-2; CAS Nbr 868-77-9;
<b>Exposure Scenario Name</b>	Industrial Use of Adhesives and Sealants
<b>Lifecycle Stage</b>	Use at industrial sites
<b>Contributing activities</b>	PROC 05 -Mixing or blending in batch processes PROC 13 -Treatment of articles by dipping and pouring ERC 05 -Use at industrial site leading to inclusion into/onto article
<b>Processes, tasks and activities covered</b>	Manual application of product. Mixing operations (open systems).
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<p><b>Physical state:</b>Liquid.</p> <p><b>General operating conditions:</b>      Duration of use: 8 hours/day;      Frequency of exposure at workplace [for one worker]: 5 days/week;      Indoor use;</p>
<b>Risk management measures</b>	<p>Under the operational conditions described above the following risk management measures apply:</p> <p><b>General risk management measures:</b>  <b>Human health:</b>      Goggles - Chemical resistant;  <b>Environmental:</b>      None needed;</p>
<b>Waste management measures</b>	No use-specific waste management measures are required for this product. Refer to Section 13 of main SDS for disposal instructions:
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

<b>1. Title</b>	
<b>Substance identification</b>	methyl methacrylate; EC No. 201-297-1; CAS Nbr 80-62-6;

<b>Exposure Scenario Name</b>	Professional Use of Adhesives
<b>Lifecycle Stage</b>	<b>Use at industrial sites</b>
<b>Contributing activities</b>	PROC 05 -Mixing or blending in batch processes PROC 13 -Treatment of articles by dipping and pouring ERC 08c -Widespread use leading to inclusion into/onto article (indoor)
<b>Processes, tasks and activities covered</b>	Application of product through a mixing nozzle Mixing or blending of solid or liquid materials.
<b>2. Operational conditions and risk management measures</b>	
<b>Operating Conditions</b>	<b>Physical state:</b> Liquid. <b>General operating conditions:</b> Continuous release; Duration of use: 8 hours/day; Emission days per year: 300 days/year; Indoor use;
<b>Risk management measures</b>	Under the operational conditions described above the following risk management measures apply: <b>General risk management measures:</b> <b>Human health:</b> Goggles - Chemical resistant; Protective Gloves - Chemical resistant. Refer to Section 8 of the SDS for specific glove material.; Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour); <b>Environmental:</b> None needed; ; The following task-specific risk management measures apply in addition to those listed above: <b>Task: PROC05;</b> <b>Human Health;</b> Local exhaust ventilation;  <b>Task: PROC13;</b> <b>Human Health;</b> Local exhaust ventilation;
<b>Waste management measures</b>	Do not release directly to waterways; Send to a municipal sewage treatment plant;
<b>3. Prediction of exposure</b>	
<b>Prediction of exposure</b>	Human and environmental exposures are not expected to exceed the DNELs and PNECs when the identified risk management measures are adopted.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

**3M Ireland MSDSs are available at [www.3M.com](http://www.3M.com)**



## Safety Data Sheet

Copyright,2024, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 33-7188-7      **Version number:** 3.01  
**Revision date:** 17/12/2024      **Supersedes date:** 09/01/2024

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M(TM) Scotch-Weld(TM) Acrylic Adhesive DP8425NS, Green, Part A

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Structural adhesive.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M Ireland Limited, The Iveagh Building, The Park, Carrickmines, Dublin 18.  
**Telephone:** +353 1 280 3555  
**E Mail:** tox.uk@mmm.com  
**Website:** www.3M.com

#### 1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

##### CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

##### CLASSIFICATION:

Skin Sensitization, Category 1 - Skin Sens. 1; H317

Hazardous to the Aquatic Environment (Chronic), Category 2 - Aquatic Chronic 2; H411

For full text of H phrases, see Section 16.

#### 2.2. Label elements

##### CLP REGULATION (EC) No 1272/2008

## SIGNAL WORD

WARNING.

## Symbols

GHS07 (Exclamation mark) | GHS09 (Environment) |

## Pictograms



## Ingredients:

Ingredient	CAS Nbr	EC No.	% by Wt
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	236-050-7	0.1 - 10

## HAZARD STATEMENTS:

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

## PRECAUTIONARY STATEMENTS

### Prevention:

P273 Avoid release to the environment.  
P280E Wear protective gloves.

### Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.  
P391 Collect spillage.

**For containers not exceeding 125 ml the following Hazard and Precautionary statements may be used:**

### <=125 ml Hazard statements

H317 May cause an allergic skin reaction.

### <=125 ml Precautionary statements

**Prevention:**  
P280E Wear protective gloves.

### Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

11% of the mixture consists of components of unknown acute oral toxicity.

Contains 49% of components with unknown hazards to the aquatic environment.

## Notes on labelling

The organic peroxide classification from CAS# 13122-18-4 does not apply to the material. The calculated available oxygen content is less than 1%.

## 2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Oxydipropyl dibenzoate	(CAS-No.) 27138-31-4 (EC-No.) 248-258-5 (REACH-No.) 01-2119529241-49	45 - 65	Aquatic Chronic 3, H412
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	(CAS-No.) 25101-28-4	10 - 30	Substance not classified as hazardous
Catalyst.	Trade Secret	1 - 15	Substance not classified as hazardous
BENZOATE ESTERS	None	< 11	Substance not classified as hazardous
Tert-butyl 3,5,5-trimethylperoxyhexanoate	(CAS-No.) 13122-18-4 (EC-No.) 236-050-7	0.1 - 10	Org. Perox. CD, H242 Skin Sens. 1B, H317 Aquatic Acute 1, H400, M=1 Aquatic Chronic 3, H412

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### Eye contact

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

#### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:  
Allergic skin reaction (redness, swelling, blistering, and itching).

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Part of the oxygen for combustion is supplied by the peroxide itself.

#### Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During combustion.
Carbon dioxide.	During combustion.

### 5.3. Advice for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible.

### 6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Keep cool. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

### 7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this Safety Data Sheet.

#### Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

None required.

##### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

##### Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

##### Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

##### Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Physical state</b>	Liquid.
<b>Specific Physical Form:</b>	Paste
<b>Colour</b>	Blue
<b>Odor</b>	Mild Ester
<b>Odour threshold</b>	<i>No data available.</i>
<b>Melting point/freezing point</b>	<i>Not applicable.</i>
<b>Boiling point/boiling range</b>	$\geq 65.6\text{ }^{\circ}\text{C}$
<b>Flammability</b>	<i>Not applicable.</i>
<b>Flammable Limits(LEL)</b>	<i>No data available.</i>
<b>Flammable Limits(UEL)</b>	<i>No data available.</i>
<b>Flash point</b>	$> 93.3\text{ }^{\circ}\text{C}$ [Test Method:Closed Cup]
<b>Autoignition temperature</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>pH</b>	<i>substance/mixture is non-soluble (in water)</i>
<b>Kinematic Viscosity</b>	18,519 mm <sup>2</sup> /sec
<b>Water solubility</b>	Nil
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Vapour pressure</b>	<i>No data available.</i>
<b>Density</b>	1.08 g/ml
<b>Relative density</b>	1.08 [Ref Std:WATER=1]
<b>Relative Vapour Density</b>	<i>No data available.</i>
<b>Particle Characteristics</b>	<i>Not applicable.</i>

## 9.2. Other information

### 9.2.2 Other safety characteristics

**EU Volatile Organic Compounds**

*No data available.*

**Evaporation rate**

*No data available.*

**Molecular weight**

*No data available.*

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

### 10.2 Chemical stability

Stable.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### 10.4 Conditions to avoid

Heat.

Sparks and/or flames.

### 10.5 Incompatible materials

Amines.

Strong acids.

Strong bases.

Strong oxidising agents.

## 10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

##### Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

##### Skin contact

Contact with the skin during product use is not expected to result in significant irritation. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

##### Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

##### Ingestion

May be harmful if swallowed.

#### Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000 mg/kg
Oxydipropyl dibenzoate	Dermal	Rat	LD50 > 2,000 mg/kg
Oxydipropyl dibenzoate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 200 mg/l
Oxydipropyl dibenzoate	Ingestion	Rat	LD50 3,295 mg/kg
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	Dermal		LD50 estimated to be > 5,000 mg/kg
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	Ingestion	Rat	LD50 > 5,000 mg/kg
Catalyst.	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Catalyst.	Ingestion	Rat	LD50 > 2,000 mg/kg

Tert-butyl 3,5,5-trimethylperoxyhexanoate	Dermal	Rat	LD50 > 2,000 mg/kg
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.8 mg/l
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Ingestion	Rat	LD50 12,905 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
Oxydipropyl dibenzoate	Rabbit	No significant irritation
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Rabbit	No significant irritation

### Serious Eye Damage/Irritation

Name	Species	Value
Oxydipropyl dibenzoate	Rabbit	No significant irritation
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Rabbit	No significant irritation

### Skin Sensitisation

Name	Species	Value
Oxydipropyl dibenzoate	Guinea pig	Not classified
Catalyst.	Mouse	Not classified
Tert-butyl 3,5,5-trimethylperoxyhexanoate	Guinea pig	Sensitising

### Respiratory Sensitisation

For the component/components, either no data is currently available or the data is not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
Oxydipropyl dibenzoate	In Vitro	Not mutagenic
Catalyst.	In Vitro	Not mutagenic

### Carcinogenicity

For the component/components, either no data is currently available or the data is not sufficient for classification.

### Reproductive Toxicity

#### Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Oxydipropyl dibenzoate	Ingestion	Not classified for female reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Oxydipropyl dibenzoate	Ingestion	Not classified for male reproduction	Rat	NOAEL 400 mg/kg/day	2 generation
Oxydipropyl dibenzoate	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	during gestation

### Target Organ(s)

#### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Catalyst.	Ingestion	nervous system	Not classified	Rat	NOAEL	

				2,000 mg/kg	
--	--	--	--	-------------	--

#### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Oxydipropyl dibenzoate	Ingestion	hematopoietic system   liver	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days

#### Aspiration Hazard

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

#### 11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

### SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

#### 12.1. Toxicity

No product test data available.

Material	CAS #	Organism	Type	Exposure	Test endpoint	Test result
Oxydipropyl dibenzoate	27138-31-4	Fathead minnow	Experimental	96 hours	LC50	3.7 mg/l
Oxydipropyl dibenzoate	27138-31-4	Green algae	Experimental	72 hours	EL50	4.9 mg/l
Oxydipropyl dibenzoate	27138-31-4	Water flea	Experimental	48 hours	EL50	19.31 mg/l
Oxydipropyl dibenzoate	27138-31-4	Green algae	Experimental	72 hours	EC10	0.89 mg/l
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	25101-28-4	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Catalyst.	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Green algae	Experimental	72 hours	ErC50	0.51 mg/l
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Rainbow trout	Experimental	96 hours	LC50	7.03 mg/l
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Water flea	Experimental	48 hours	EC50	>100 mg/l
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Green algae	Experimental	72 hours	NOEC	0.125 mg/l
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Water flea	Experimental	21 days	NOEC	0.22 mg/l

Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Activated sludge	Experimental	3 hours	EC50	327.02 mg/l
---	------------	------------------	--------------	---------	------	-------------

## 12.2. Persistence and degradability

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Oxydipropyl dibenzoate	27138-31-4	Experimental Biodegradation	28 days	CO2 evolution	85 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	25101-28-4	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Catalyst.	Trade Secret	Experimental Biodegradation	28 days	CO2 evolution	29.1 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Catalyst.	Trade Secret	Estimated Photolysis		Photolytic half-life (in air)	1.48 days (t 1/2)	
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Experimental Biodegradation	28 days	BOD	72 %BOD/ThOD	OECD 301D - Closed bottle test
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Experimental Aquatic Inherent Biodegrad.	56 days	BOD	58 %BOD/ThOD	OECD 302A - Modified SCAS Test
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Experimental Hydrolysis		Hydrolytic half-life (pH 7)	51 hours (t 1/2)	OECD 111 Hydrolysis func of pH

## 12.3 : Bioaccumulative potential

Material	Cas No.	Test type	Duration	Study Type	Test result	Protocol
Oxydipropyl dibenzoate	27138-31-4	Modeled Bioconcentration		Bioaccumulation factor	8	Catalogic™
Styrene, polymer with 1,3-Butadiene, butylacrylate and methyl methacrylate	25101-28-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Catalyst.	Trade Secret	Experimental Bioconcentration		Log Kow	2.57	
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Modeled Bioconcentration		Bioaccumulation factor	380	Catalogic™
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Experimental Bioconcentration		Log Kow	5.16	OECD 117 log Kow HPLC method

## 12.4. Mobility in soil

Material	Cas No.	Test type	Study Type	Test result	Protocol
Catalyst.	Trade Secret	Estimated Mobility in Soil	Koc	<270 l/kg	ACD/Labs ChemSketch™
Tert-butyl 3,5,5-trimethylperoxyhexanoate	13122-18-4	Modeled Mobility in Soil	Koc	3,550 l/kg	Episuite™

## 12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

## 12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

## 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

**13.1 Waste treatment methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

**EU waste code (product as sold)**

08 04 09*	Waste adhesives and sealants containing organic solvents or other dangerous substances
20 01 27*	Paint, inks, adhesives and resins containing dangerous substances

**SECTION 14: Transportation information**

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
<b>14.1 UN number or ID number</b>	No data available.	No data available.	No data available.
<b>14.2 UN proper shipping name</b>	No data available.	No data available.	No data available.
<b>14.3 Transport hazard class(es)</b>	No data available.	No data available.	No data available.
<b>14.4 Packing group</b>	No data available.	No data available.	No data available.
<b>14.5 Environmental hazards</b>	No data available.	No data available.	No data available.
<b>14.6 Special precautions for user</b>	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
<b>14.7 Marine Transport in bulk according to IMO instruments</b>	No data available.	No data available.	No data available.
<b>Control Temperature</b>	No data available.	No data available.	No data available.

<b>Emergency Temperature</b>	No data available.	No data available.	No data available.
<b>ADR Classification Code</b>	No data available.	No data available.	No data available.
<b>IMDG Segregation Code</b>	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

#### DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

Hazard Categories	Qualifying quantity (tonnes) for the application of	
	Lower-tier requirements	Upper-tier requirements
E2 Hazardous to the Aquatic environment	200	500

Seveso named dangerous substances, Annex 1, Part 2

None

#### Regulation (EU) No 649/2012

No chemicals listed

### 15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this mixture. Chemical safety assessments for the contained substances may have been carried out by the registrants of the substances in accordance with Regulation (EC) No 1907/2006, as amended.

## SECTION 16: Other information

### List of relevant H statements

H242	Heating may cause a fire.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

### Revision information:

Section 3: Composition/ Information of ingredients table information was modified.

Section 9: Flammability (solid, gas) information information was deleted.

Section 09: Flammability information information was added.

Section 09: Odor information was modified.

Section 09: Particle Characteristics N/A information was added.

Section 12: Component ecotoxicity information information was modified.

Section 12: Mobility in soil information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12: Biocumulative potential information information was modified.

Two-column table displaying the unique list of H Codes and statements (std phrases) for all components of the given material. information was modified.

**DISCLAIMER:** The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

**3M Ireland MSDSs are available at [www.3M.com](http://www.3M.com)**