



Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	17-9873-5	Version Number:	4.00
Issue Date:	02/07/2021	Supersedes Date:	20/08/2020

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

IDENTIFICATION

1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive DP420NS Black

Product Identification Numbers

62-3299-1430-3	62-3299-1431-1	62-3299-1435-2	62-3299-1436-0	62-3299-3532-4
62-3299-3832-8	HB-0042-4681-3	HB-0045-4594-1	HB-0045-4595-8	

1.2. Recommended use and restrictions on use

Recommended use

Structural adhesive

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301 Petaling, Jaya, Selangor

Telephone: 03-7884 2888

E Mail: 3mmyehsr@mmm.com

Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:

17-9844-6, 17-9858-6

TRANSPORT INFORMATION

This product is a kit that consists of two or more different regulated materials packed in the same outer packaging (ship unit). The transportation classifications of the individual components appear in Section 14 of the attached SDSs.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation

classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Malaysia SDSs are available at www.3M.com.my



Safety Data Sheet

Copyright, 2021, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	17-9844-6	Version Number:	4.00
Issue Date:	21/06/2021	Supersedes Date:	20/08/2020

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive DP420NS Black, Part A or Epoxy Adhesive 420NS Black, Part A

Product Identification Numbers

62-3399-8530-1 62-3399-9530-0 62-3399-9531-8

1.2. Recommended use and restrictions on use

Recommended use

2-Part Epoxy Adhesive, Structural adhesive

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301 Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 1.

Serious Eye Damage/Irritation: Category 1.

Reproductive Toxicity: Category 1B.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Health Hazard |

Pictograms

**Hazard Statements:**

H314 Causes severe skin burns and eye damage.
 H360 May damage fertility or the unborn child.

Precautionary statements**Prevention:**

P201 Obtain special instructions before use.
 P260 Do not breathe dust/fume/gas/mist/vapors/spray.
 P280D Wear protective gloves, protective clothing, and eye/face protection.
 P281 Use personal protective equipment as required.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER or doctor/physician.

2.3. Other hazards

May cause chemical gastrointestinal burns.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Modified Epoxy Resin	Trade Secret	50 - 80
4,7,10-Trioxatridecane-1,13-Diamine	4246-51-9	20 - 40
Amorphous Silica	67762-90-7	5 - 10
2,4,6-Tris((Dimethylamino)Methyl)Phenol	90-72-2	1 - 5
Calcium Salt	55120-75-7	1 - 5
toluene	108-88-3	< 1

SECTION 4: First aid measures

4.1. Description of first aid measures**Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Amine Compounds	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Hydrogen Chloride	During Combustion
Hydrogen Fluoride	During Combustion
Oxides of Nitrogen	During Combustion
Toxic Vapor, Gas, Particulate	During Combustion

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been

read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
toluene	108-88-3	Malaysia OELs	TWA(8 hours):188 mg/m3(50 ppm)	SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Fluoroelastomer

Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Paste
Color	Off-White
Odor	Slight Amine
Odor threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	No Data Available
Boiling point/Initial boiling point/Boiling range	> 171.1 °C
Flash Point	>=171.1 °C [Test Method: Tagliabue Closed Cup]
Evaporation rate	Not Applicable
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	<=186,158.4 Pa [@ 55 °C]
Vapor Density and/or Relative Vapor Density	3.72 [Ref Std: AIR=1]
Density	1.15 g/ml
Relative Density	1.15 [Ref Std: WATER=1]
Water solubility	Slight (less than 10%)
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available
Decomposition temperature	No Data Available
Viscosity/Kinematic Viscosity	8,000 - 10,000 mPa-s [@ 22.8 °C]
Volatile Organic Compounds	
Percent volatile	
VOC Less H2O & Exempt Solvents	0 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: when used as intended with Part B]
VOC Less H2O & Exempt Solvents	0 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: as supplied]
VOC Less H2O & Exempt Solvents	0 % [Test Method: calculated SCAQMD rule 443.1] [Details: when used as intended with Part B]
Molecular weight	No Data Available

Nanoparticles

This material contains nanoparticles.

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

Extreme heat arising from situations such as misuse or equipment failure can generate hydrogen fluoride as a decomposition product.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May cause additional health effects (see below).

Additional Health Effects:**Reproductive/Developmental Toxicity:**

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
4,7,10-Trioxatridecane-1,13-Diamine	Dermal	Rabbit	LD50 2,500 mg/kg
4,7,10-Trioxatridecane-1,13-Diamine	Ingestion	Rat	LD50 3,160 mg/kg
Amorphous Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Amorphous Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
2,4,6-Tris((Dimethylamino)Methyl)Phenol	Dermal	Rat	LD50 1,280 mg/kg
2,4,6-Tris((Dimethylamino)Methyl)Phenol	Ingestion	Rat	LD50 1,000 mg/kg
Calcium Salt	Dermal	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Calcium Salt	Ingestion	Rat	LD50 > 2,000 mg/kg
toluene	Dermal	Rat	LD50 12,000 mg/kg
toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
4,7,10-Trioxatridecane-1,13-Diamine	Rabbit	Corrosive
Amorphous Silica	Rabbit	No significant irritation
2,4,6-Tris((Dimethylamino)Methyl)Phenol	Rabbit	Corrosive
Calcium Salt	Rabbit	Minimal irritation
toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
4,7,10-Trioxatridecane-1,13-Diamine	similar health hazards	Corrosive
Amorphous Silica	Rabbit	No significant irritation
2,4,6-Tris((Dimethylamino)Methyl)Phenol	Rabbit	Corrosive
Calcium Salt	Rabbit	Corrosive
toluene	Rabbit	Moderate irritant

Sensitization:**Skin Sensitization**

Name	Species	Value
Amorphous Silica	Human and	Not classified

3M™ Scotch-Weld™ Epoxy Adhesive DP420NS Black, Part A or Epoxy Adhesive 420NS Black, Part A

	animal	
2,4,6-Tris((Dimethylamino)Methyl)Phenol	Guinea pig	Not classified
Calcium Salt	Guinea pig	Not classified
toluene	Guinea pig	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Amorphous Silica	In Vitro	Not mutagenic
2,4,6-Tris((Dimethylamino)Methyl)Phenol	In Vitro	Not mutagenic
Calcium Salt	In Vitro	Not mutagenic
toluene	In Vitro	Not mutagenic
toluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Amorphous Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Amorphous Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
4,7,10-Trioxatridecane-1,13-Diamine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
2,4,6-Tris((Dimethylamino)Methyl)Phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	

3M™ Scotch-Weld™ Epoxy Adhesive DP420NS Black, Part A or Epoxy Adhesive 420NS Black, Part A

Calcium Salt	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL not available	
toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Amorphous Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
2,4,6-Tris((Dimethylamino)Methyl)Phenol	Dermal	skin liver nervous system auditory system hematopoietic system eyes	Not classified	Rat	NOAEL 125 mg/kg/day	28 days
toluene	Inhalation	auditory system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	nervous system	May cause damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

Not acutely toxic to aquatic life by GHS criteria.

Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
4,7,10-Trioxatridecane-1,13-Diamine	4246-51-9	Bacteria	Experimental	17 hours	EC50	4,000 mg/l
4,7,10-Trioxatridecane-1,13-Diamine	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
4,7,10-Trioxatridecane-1,13-Diamine	4246-51-9	Green algae	Experimental	72 hours	EC50	>500 mg/l
4,7,10-Trioxatridecane-1,13-Diamine	4246-51-9	Water flea	Experimental	48 hours	EC50	218.16 mg/l
4,7,10-Trioxatridecane-1,13-Diamine	4246-51-9	Green algae	Experimental	72 hours	EC10	5.4 mg/l
Amorphous Silica	67762-90-7		Data not available or insufficient for classification			N/A
2,4,6-Tris((Dimethyl amino)Methyl)Phenol	90-72-2		Experimental	96 hours	LC50	718 mg/l
2,4,6-Tris((Dimethyl amino)Methyl)Phenol	90-72-2	Common Carp	Experimental	96 hours	LC50	>100 mg/l
2,4,6-Tris((Dimethyl amino)Methyl)Phenol	90-72-2	Green algae	Experimental	72 hours	EC50	46.7 mg/l
2,4,6-Tris((Dimethyl amino)Methyl)Phenol	90-72-2	Water flea	Experimental	48 hours	EC50	>100 mg/l

amino)Methyl) Phenol						
2,4,6-Tris((Dimethyl amino)Methyl) Phenol	90-72-2	Green algae	Experimental	72 hours	NOEC	6.44 mg/l
Calcium Salt	55120-75-7	Green Algae	Estimated	72 hours	EC50	54 mg/l
Calcium Salt	55120-75-7	Rainbow Trout	Estimated	96 hours	LC50	>100 mg/l
Calcium Salt	55120-75-7	Water flea	Estimated	48 hours	EC50	>100 mg/l
Calcium Salt	55120-75-7	Green Algae	Estimated	72 hours	NOEC	6.4 mg/l
toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
toluene	108-88-3	Grass Shrimp	Experimental	96 hours	LC50	9.5 mg/l
toluene	108-88-3	Green Algae	Experimental	72 hours	EC50	12.5 mg/l
toluene	108-88-3	Leopard frog	Experimental	9 days	LC50	0.39 mg/l
toluene	108-88-3	Pink Salmon	Experimental	96 hours	LC50	6.41 mg/l
toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
toluene	108-88-3	Coho Salmon	Experimental	40 days	NOEC	1.39 mg/l
toluene	108-88-3	Diatom	Experimental	72 hours	NOEC	10 mg/l
toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l
toluene	108-88-3	Activated sludge	Experimental	12 hours	IC50	292 mg/l
toluene	108-88-3	Bacteria	Experimental	16 hours	NOEC	29 mg/l
toluene	108-88-3	Bacteria	Experimental	24 hours	EC50	84 mg/l
toluene	108-88-3	Redworm	Experimental	28 days	LC50	>150 mg per kg of bodyweight
toluene	108-88-3	Soil microbes	Experimental	28 days	NOEC	<26 mg/kg (Dry Weight)

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
4,7,10-Trioxatridecane -1,13-Diamine	4246-51-9	Estimated Photolysis		Photolytic half- life (in air)	2.96 hours (t 1/2)	Non-standard method
4,7,10-Trioxatridecane -1,13-Diamine	4246-51-9	Experimental Biodegradation	25 days	Carbon dioxide evolution	-8 %CO2 evolution/THC O2 evolution	OECD 301B - Mod. Sturm or CO2
Amorphous Silica	67762-90-7	Data not availbl- insufficient			N/A	
2,4,6-Tris((Dimethyl amino)Methyl) Phenol	90-72-2	Experimental Biodegradation	28 days	Biological Oxygen Demand	4 % BOD/ThBOD	OECD 301D - Closed Bottle Test
Calcium Salt	55120-75-7	Estimated Biodegradation	28 days	Biological Oxygen Demand	0 % BOD/ThBOD	OECD 301D - Closed Bottle Test
toluene	108-88-3	Experimental Photolysis		Photolytic half- life (in air)	5.2 days (t 1/2)	
toluene	108-88-3	Experimental Biodegradation	20 days	Biological Oxygen Demand	80 % BOD/ThBOD	APHA Std Meth Water/Wastewater

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
4,7,10-Trioxatridecane-1,13-Diamine	4246-51-9	Experimental Bioconcentration		Log of Octanol/H ₂ O part. coeff	-1.25	Non-standard method
Amorphous Silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
2,4,6-Tris((Dimethylamino)Methyl)Phenol	90-72-2	Experimental Bioconcentration		Log of Octanol/H ₂ O part. coeff	-0.66	830.7550 Part.Coeff Shake Flask
Calcium Salt	55120-75-7	Estimated Bioconcentration	35 days	Bioaccumulation Factor	0.03	OECD 305E-Bioaccum Fl-thru fis
toluene	108-88-3	Experimental BCF - Other	72 hours	Bioaccumulation Factor	90	
toluene	108-88-3	Experimental Bioconcentration		Log of Octanol/H ₂ O part. coeff	2.73	

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number:UN2735

Proper Shipping Name:AMINES, LIQUID, CORROSIVE, N.O.S.

Technical Name:(4,7,10-Trioxatridecane-1,13-Diamine)

Hazard Class/Division:8

Subsidiary Risk:None assigned.

Packing Group:II

Limited Quantity:None assigned.

Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

Forbidden:Package size exceeds IATA quantity limitations

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M Malaysia SDSs are available at www.3M.com.my



Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	17-9858-6	Version Number:	6.00
Issue Date:	19/03/2025	Supersedes Date:	21/06/2021

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Epoxy Adhesive DP420NS Black, Part B or Epoxy Adhesive 420NS Black, Part B

Product Identification Numbers

62-3299-8535-2 62-3299-9530-2 62-3299-9531-0

1.2. Recommended use and restrictions on use

Recommended use

2-Part Epoxy Adhesive, Structural adhesive

For Industrial or Professional use only

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301
Petaling, Jaya, Selangor
Telephone: 03-7884 2888
E Mail: 3mmyehsr@mmm.com
Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

Chronic Aquatic Toxicity: Category 2.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark | Environment |

Pictograms



Hazard Statements:

H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention:

P273	Avoid release to the environment.
P280E	Wear protective gloves.

Response:

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical attention.

Disposal:

P501	Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.
------	---

2.3. Other hazards

None known

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Epoxy Resin	25068-38-6	75 - 98
Acrylic Polymer	Trade Secret	1 - 20
Amorphous Silica	67762-90-7	1 - 5
Carbon Black	1333-86-4	<= 0.15

Any remaining components do not contribute to the hazards of this material.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Aldehydes
Carbon monoxide
Carbon dioxide
Hydrogen Chloride
Irritant Vapors or Gases

Condition

During Combustion
During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate

solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Carbon Black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m3	A3: Confirmed animal carcin.
Carbon Black	1333-86-4	Malaysia OELs	TWA(8 hours):3.5 mg/m3	
DUST, INERT OR NUISANCE	1333-86-4	Malaysia OELs	TWA (proposed)(respirable particles)(8 hours):3 mg/m3;TWA (proposed)(Inhalable particulate)(8 hours):10 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

CMRG : Chemical Manufacturer's Recommended Guidelines

Malaysia OELs : Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the

substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Paste
Color	Black
Odor	Mild Epoxy
Odor threshold	<i>No Data Available</i>
pH	<i>Not Applicable</i>
Melting point/Freezing point	<i>Not Applicable</i>
Boiling point/Initial boiling point/Boiling range	> 121.1 °C
Flash Point	121.1 °C
Evaporation rate	<i>Not Applicable</i>
Flammability	Not Applicable
Flammable Limits(LEL)	<i>No Data Available</i>
Flammable Limits(UEL)	<i>No Data Available</i>
Vapor Pressure	<i>Not Applicable</i>
Relative Vapor Density	<i>Not Applicable</i>
Density	1.1 g/ml
Relative Density	0.97 - 1.1 [Ref Std: WATER=1]
Water solubility	Nil
Solubility- non-water	<i>No Data Available</i>
Partition coefficient: n-octanol/ water	<i>No Data Available</i>
Autoignition temperature	<i>No Data Available</i>
Decomposition temperature	<i>No Data Available</i>
Kinematic Viscosity	77,295 mm ² /sec
Volatile Organic Compounds	<i>No Data Available</i>
Percent volatile	<i>No Data Available</i>
VOC Less H₂O & Exempt Solvents	0 g/l [Test Method:calculated SCAQMD rule 443.1] [Details:when used as intended with Part A]
VOC Less H₂O & Exempt Solvents	6 g/l [Test Method:calculated SCAQMD rule 443.1] [Details:as supplied]
VOC Less H₂O & Exempt Solvents	0 % [Test Method:calculated SCAQMD rule 443.1]

	[Details:when used as intended with Part A]
Molecular weight	No Data Available

Particle Characteristics	Not Applicable
---------------------------------	----------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat
Heat is generated during cure. Do not cure a mass larger than 50 grams in a confined space to prevent a premature exothermic reaction with production of intense heat and smoke.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Epoxy Resin	Dermal	Rat	LD50 > 1,600 mg/kg
Epoxy Resin	Ingestion	Rat	LD50 > 1,000 mg/kg
Acrylic Polymer	Dermal	Rabbit	LD50 > 5,000 mg/kg
Acrylic Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Amorphous Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Amorphous Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Amorphous Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Carbon Black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon Black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Epoxy Resin	Rabbit	Mild irritant
Acrylic Polymer	Professional judgement	Minimal irritation
Amorphous Silica	Rabbit	No significant irritation
Carbon Black	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Epoxy Resin	Rabbit	Moderate irritant
Acrylic Polymer	Professional judgement	Mild irritant
Amorphous Silica	Rabbit	No significant irritation
Carbon Black	Rabbit	No significant irritation

Sensitization:**Skin Sensitization**

Name	Species	Value
Epoxy Resin	Human and animal	Sensitizing
Amorphous Silica	Human and animal	Not classified

Respiratory Sensitization

Name	Species	Value
------	---------	-------

Epoxy Resin	Human	Not classified
-------------	-------	----------------

Germ Cell Mutagenicity

Name	Route	Value
Epoxy Resin	In vivo	Not mutagenic
Epoxy Resin	In Vitro	Some positive data exist, but the data are not sufficient for classification
Amorphous Silica	In Vitro	Not mutagenic
Carbon Black	In Vitro	Not mutagenic
Carbon Black	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Epoxy Resin	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Amorphous Silica	Not Specified	Mouse	Some positive data exist, but the data are not sufficient for classification
Carbon Black	Dermal	Mouse	Not carcinogenic
Carbon Black	Ingestion	Mouse	Not carcinogenic
Carbon Black	Inhalation	Rat	Carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
Epoxy Resin	Ingestion	Not classified for female reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin	Ingestion	Not classified for male reproduction	Rat	NOAEL 750 mg/kg/day	2 generation
Epoxy Resin	Dermal	Not classified for development	Rabbit	NOAEL 300 mg/kg/day	during organogenesis
Epoxy Resin	Ingestion	Not classified for development	Rat	NOAEL 750 mg/kg/day	2 generation
Amorphous Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Amorphous Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Epoxy Resin	Dermal	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	2 years
Epoxy Resin	Dermal	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Epoxy Resin	Ingestion	auditory system heart endocrine system hematopoietic system liver eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

		kidney and/or bladder				
Amorphous Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Carbon Black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects

No product test data available

Material	Cas #	Organism	Type	Exposure	Test Endpoint	Test Result
Epoxy Resin	25068-38-6	Activated sludge	Estimated	3 hours	IC50	>100 mg/l
Epoxy Resin	25068-38-6	Green algae	Estimated	72 hours	EC50	>11 mg/l
Epoxy Resin	25068-38-6	Rainbow Trout	Estimated	96 hours	LC50	2 mg/l
Epoxy Resin	25068-38-6	Water flea	Estimated	48 hours	EC50	1.8 mg/l
Epoxy Resin	25068-38-6	Green algae	Estimated	72 hours	NOEC	4.2 mg/l
Epoxy Resin	25068-38-6	Water flea	Estimated	21 days	NOEC	0.3 mg/l
Acrylic Polymer	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Amorphous Silica	67762-90-7	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Carbon Black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon Black	1333-86-4	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Carbon Black	1333-86-4	Green algae	Experimental	72 hours	No tox obs at lmt of water sol	100 mg/l
Carbon Black	1333-86-4	Activated sludge	Experimental	3 hours	NOEC	>800 mg/l

12.2. Persistence and degradability

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Epoxy Resin	25068-38-6	Estimated	28 days	Biological Oxygen	5 %BOD/COD	OECD 301F - Manometric

3M™ Scotch-Weld™ Epoxy Adhesive DP420NS Black, Part B or Epoxy Adhesive 420NS Black, Part B

		Biodegradation		Demand		Respiro
Epoxy Resin	25068-38-6	Estimated Hydrolysis		Hydrolytic half-life	117 hours (t 1/2)	
Acrylic Polymer	Trade Secret	Data not available or insufficient	N/A	N/A	N/A	N/A
Amorphous Silica	67762-90-7	Data not available or insufficient	N/A	N/A	N/A	N/A
Carbon Black	1333-86-4	Data not available or insufficient	N/A	N/A	N/A	N/A

12.3. Bioaccumulative potential

Material	CAS No.	Test Type	Duration	Study Type	Test Result	Protocol
Epoxy Resin	25068-38-6	Estimated Bioconcentration		Log of Octanol/H ₂ O part. coeff	3.242	
Acrylic Polymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Amorphous Silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carbon Black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations**13.1. Disposal methods**

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information**Marine Transport (IMDG)**

UN Number:UN3082

Proper Shipping Name:ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Technical Name:None assigned.

Hazard Class/Division:9

Subsidiary Risk:None assigned.

Packing Group:III

Limited Quantity:None assigned.

Marine Pollutant: Yes

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number:UN3082

Proper Shipping Name:ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Technical Name:None assigned.

Hazard Class/Division:None assigned.

Subsidiary Risk:None assigned.

Packing Group:III

Limited Quantity:None assigned.

Marine Pollutant: Yes

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my