

Safety Data Sheet

Copyright, 2024, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 33-5983-3 **Version Number:** 1.00 **Issue Date:** 11/11/2024 **Supercedes Date:** Initial Issue

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

IDENTIFICATION

1.1. Product identifier

3MTM Impact Resistant Structural Adhesive PNs 07333, 57333

Product Identification Numbers

60-4550-8345-5 60-4550-8333-1 60-4551-1451-6

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Two-part color changing adhesive with optimized shear, peel and impact performance.

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301

Petaling, Jaya, Selangor

03-7884 2888 **Telephone:**

E Mail: 3mmyehsr@mmm.com Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

This product is a kit or a multipart product which consists of multiple, independently packaged components. An SDS for each of these components is included. Please do not separate the component SDSs from this cover page. The document numbers of the SDSs for components of this product are:

33-5988-2, 33-5984-1

TRANSPORT INFORMATION

This product is a kit that consists of two or more different regulated materials packed in the same outer packaging (ship unit). The transportation classifications of the individual components appear in Section 14 of the attached SDSs.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current

regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my



Safety Data Sheet

Copyright, 2024, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:33-5984-1Version Number:1.00Issue Date:10/11/2024Supercedes Date:Initial Issue

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3MTM Impact Resistant Structural Adhesive Part A, PNs 07333, 57333

Product Identification Numbers

UU-0128-3031-9

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Accelerator for two-part color changing adhesive with optimized shear, peel and impact performance.

For Industrial or Professional use only

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301

Petaling, Jaya, Selangor

Telephone: 03-7884 2888

E Mail: 3mmyehsr@mmm.com Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Acute Toxicity (oral): Category 4. Skin Corrosion/Irritation: Category 1. Serious Eye Damage/Irritation: Category 1.

Skin Sensitizer: Category 1. Carcinogenicity: Category 1A.

Chronic Aquatic Toxicity: Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion | Exclamation mark | Health Hazard | Environment |

Pictograms



Hazard Statements:

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

H350 May cause cancer.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Prevention:

P201 Obtain special instructions before use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling. P273 Avoid release to the environment.

P280J Wear protective gloves, protective clothing, respiratory protection, and eye/face

protection.

P281 Use personal protective equipment as required.

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

2.3. Other hazards

May cause chemical gastrointestinal burns., Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt |
|---|--------------|---------|
| Bis(3-Aminopropyl) Ether of Diethylene | 4246-51-9 | 15 - 40 |
| Glycol | | |
| Epoxy Copolymer | Trade Secret | 10 - 30 |
| Acrylic Copolymer | Trade Secret | 5 - 15 |
| 2-Propenenitrile, Polymer with 1,3- | 68683-29-4 | 5 - 10 |
| Butadiene, 1-cyano-1-methyl-4-oxo-4-[[2- | | |
| (1-piperazinyl)ethyl]amino]butyl-terminated | | |
| Aluminum | 7429-90-5 | 5 - 10 |
| Methylenedi(cyclohexylamine) | 1761-71-3 | 5 - 9 |
| Treated Inorganic Filler | Trade Secret | 3 - 7 |
| Inorganic Filler | Trade Secret | 1 - 5 |
| Mineral Filler | Trade Secret | 1 - 5 |
| Treated Filler | Trade Secret | 1 - 5 |
| 2,4,6- | 90-72-2 | < 3 |
| Tris(dimethylaminomonomethyl)phenol | | |
| m-Xylenealpha.alpha'.Diamine | 1477-55-0 | < 2 |
| Formaldehyde, Polymer with Benzenamine, | 135108-88-2 | < 2 |
| Hydrogenated | | |
| N-Aminoethylpiperazine | 140-31-8 | < 0.25 |
| Quartz Silica | 14808-60-7 | < 0.2 |

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Skin burns (localized redness, swelling, itching, intense pain, blistering, and tissue destruction). Allergic skin reaction (redness, swelling, blistering, and itching). Serious damage to the eyes (corneal cloudiness, severe pain, tearing, ulcerations, and significantly impaired or loss of vision). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|------------------------------|------------|---------------|---|--------------------------------|
| m-Xylenealpha.alpha'.Diamine | 1477-55-0 | ACGIH | CEIL:0.018 ppm | Danger of cutaneous absorption |
| m-Xylenealpha.alpha'.Diamine | 1477-55-0 | Malaysia OELs | CEIL:0.1 mg/m3 | SKIN |
| Quartz Silica | 14808-60-7 | ACGIH | TWA(respirable fraction):0.025 mg/m3 | A2: Suspected human carcin. |
| Quartz Silica | 14808-60-7 | Malaysia OELs | TWA(respirable fraction)(8 hours):0.1 mg/m3 | |

| Aluminum | 7429-90-5 | ACGIH | TWA(respirable fraction):1 | A4: Not class. as human |
|--|-----------|---------------|---------------------------------|-------------------------|
| | | | mg/m3 | carcin |
| Aluminum | 7429-90-5 | Malaysia OELs | TWA(as dust)(8 hours):10 | |
| | | | mg/m3;TWA(Al, welding | |
| | | | fume)(8 hours):5 | |
| | | | mg/m3;TWA(as Al pyrophoric | |
| | | | powder)(8 hours):5 mg/m3 | |
| DUST, INERT OR NUISANCE | 7429-90-5 | Malaysia OELs | TWA (proposed)(respirable | |
| | | | particles)(8 hours):3 | |
| | | | mg/m3;TWA | |
| | | | (proposed)(Inhalable | |
| | | | particulate)(8 hours):10 mg/m3 | |
| Inorganic Filler | Trade | Manufacturer | TWA(as non-fibrous, | |
| | Secret | determined | respirable)(8 hours):3 | |
| | | | mg/m3;TWA(as non-fibrous, | |
| | | | inhalable fraction)(8 hours):10 | |
| | | | mg/m3 | |
| Inorganic Filler | Trade | ACGIH | TWA(as fiber):0.2 fiber/cc | A2: Suspected human |
| | Secret | | | carcin. |
| Inorganic Filler | Trade | ACGIH | TWA(as fiber):1 fiber/cc | A3: Confirmed animal |
| | Secret | | | carcin. |
| Inorganic Filler | Trade | ACGIH | TWA(as fiber):1 fiber/cc | A4: Not class. as human |
| | Secret | | | carcin |
| Inorganic Filler | Trade | ACGIH | TWA(inhalable fraction):5 | A4: Not class. as human |
| | Secret | | mg/m3 | carcin |
| Inorganic Filler | Trade | Malaysia OELs | TWA(inhalable fraction)(8 | |
| | Secret | | hours):5 mg/m3;TWA(as | |
| | | | fiber)(8 hours):1 fibers/ml | |
| Mineral Filler | Trade | ACGIH | TWA(inhalable fraction):1 | A4: Not class. as human |
| | Secret | | mg/m3 | carcin |
| Treated Filler | Trade | ACGIH | TWA(inhalable | |
| | Secret | | particulates):10 mg/m3 | |
| Treated Filler | Trade | ACGIH | TWA(respirable particles):3 | |
| | Secret | | mg/m3 | |
| Treated Filler | Trade | Malaysia OELs | TWA (proposed)(8 hours):10 | |
| ACGIH: American Conference of Government | Secret | | mg/m3 | |

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer's Recommended Guidelines

Malaysia OELs: Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face

protection(s) are recommended: Full Face Shield Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber Neoprene

Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Apron - Neoprene

Apron – Nitrile

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates Half facepiece or full facepiece supplied-air respirator

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state | Liquid | |
|---|-----------------------------------|--|
| Specific Physical Form: | Paste | |
| | | |
| Color | Silver-Gray | |
| Odor | Very Slight Acrylic | |
| Odor threshold | No Data Available | |
| pH | No Data Available | |
| Melting point/Freezing point | No Data Available | |
| Boiling point/Initial boiling point/Boiling range | No Data Available | |
| Flash Point | 103.9 °C [Test Method:Closed Cup] | |
| Evaporation rate | No Data Available | |
| Flammability | Not Applicable | |
| | | |
| Flammable Limits(LEL) | No Data Available | |
| Flammable Limits(UEL) | No Data Available | |
| Vapor Pressure | 666.6 Pa | |
| Relative Vapor Density | No Data Available | |
| Density | 1.18 g/ml | |
| Relative Density | 1.18 [Ref Std:WATER=1] | |
| Water solubility | No Data Available | |
| Solubility- non-water | No Data Available | |

| Partition coefficient: n-octanol/ water | No Data Available |
|---|--|
| Autoignition temperature | No Data Available |
| Decomposition temperature | No Data Available |
| Kinematic Viscosity | 46,610 mm2/sec |
| Volatile Organic Compounds | 0.3 % weight [Test Method:calculated per CARB title 2] |
| Volatile Organic Compounds | 3 g/l [Test Method:calculated SCAQMD rule 443.1] |
| Percent volatile | 0.3 % weight |
| VOC Less H2O & Exempt Solvents | 3 g/l [Test Method:calculated SCAQMD rule 443.1] |
| Molecular weight | No Data Available |

| Particle Characteristics | Not Applicable | |
|--------------------------|----------------|--|
|--------------------------|----------------|--|

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong acids

Strong oxidizing agents

10.6. Hazardous decomposition products

SubstanceConditionAldehydesNot SpecifiedCarbon monoxideNot SpecifiedCarbon dioxideNot Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

May be harmful in contact with skin.

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eve Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Harmful if swallowed. Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Muscular Effects: Signs/symptoms may include generalized muscle weakness, paralysis and atrophy.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Additional Information:

Persons previously sensitized to amines may develop a cross-sensitization reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|---|-------------|---------|---|
| Overall product | Dermal | | No data available; calculated ATE >2,000 - =5,000 |
| | | | mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE >300 - =2,000 |
| | | | mg/kg |
| Bis(3-Aminopropyl) Ether of Diethylene Glycol | Dermal | Rabbit | LD50 2,525 mg/kg |
| Bis(3-Aminopropyl) Ether of Diethylene Glycol | Ingestion | Rat | LD50 2,850 mg/kg |
| Aluminum | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Aluminum | Ingestion | | LD50 estimated to be > 5,000 mg/kg |
| Aluminum | Inhalation- | Rat | LC50 > 0.888 mg/l |
| | Dust/Mist | | |
| | (4 hours) | | |

| Methylenedi(cyclohexylamine) Ingestion Rat LD50 350 mg/kg | Methylenedi(cyclohexylamine) | Dermal | Rabbit | LD50 2,110 mg/kg |
|--|---|-----------|--------|--|
| 4-oxo-4- [2-(1-piperaziny) ethy amino butyl-terminated | | Ingestion | Rat | LD50 350 mg/kg |
| 2-Propenenitrile, Polymer with 1,3-Butadiene, 1-eyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino buyl-terminated Dermal Rabbit LD50 > 5,000 mg/kg | | Dermal | Rabbit | LD50 > 3,000 mg/kg |
| 4-0x0-4-[[2-(1-piperaziny)tethyl]amino]butyl-terminated | | | | |
| Treated Inorganic Filler | | Ingestion | Rat | LD50 > 15,300 mg/kg |
| Inhalation-Dust/Mist (4 hours) Rat LD50 > 0.691 mg/l | | | | |
| Dust/Mist (4 hours) Freated Inorganic Filler Ingestion Rat LD50 > 5,110 mg/kg | | | | |
| Treated Inorganic Filler Ingestion Rat LD50 > 5,110 mg/kg Treated Filler Dermal Rat LD50 > 2,000 mg/kg Treated Filler Inhalation-Dust/Mist (4 hours) Rat LC50 3 mg/l Treated Filler Ingestion Rat LD50 < 6,450 mg/kg | Treated Inorganic Filler | | Rat | LC50 > 0.691 mg/l |
| Treated Inorganic Filler Ingestion Rat LD50 > 5,110 mg/kg Treated Filler Dermal Rat LD50 > 2,000 mg/kg Treated Filler Inhalation-Dust/Mist (4 hours) LC50 3 mg/l Freated Filler Ingestion Rat LD50 6,450 mg/kg Mineral Filler Ingestion Rat LD50 > 5,000 mg/kg Mineral Filler Dermal similar compoun ds LD50 > 5,000 mg/kg Mineral Filler Inhalation-Dust/Mist (4 hours) bismilar compoun ds LC50 > 2.08 mg/l 2,4,6-Tris(dimethylaminomonomethyl)phenol Dermal Rat LD50 1,280 mg/kg 2,4,6-Tris(dimethylaminomonomethyl)phenol Ingestion Rat LD50 1,000 mg/kg m-Xylene-alpha.alpha'.Diamine Dermal Rabbit LD50 > 2,000 mg/kg m-Xylene-alpha.alpha'.Diamine Inhalation-Dust/Mist (4 hours) Rat LC50 1,2 mg/l m-Xylene-alpha.alpha'.Diamine Ingestion Rat LD50 > 800 mg/kg Formaldehyde, Polymer with Benzenamine, Hydrogenated Dermal Rat LD50 > 800 mg/kg Formaldehyde, Polymer with Benzenamine, Hydrogenated Ingestion <td></td> <td></td> <td></td> <td></td> | | | | |
| Treated Filler Dermal Inhalation-Dust/Mist (4 hours) Rat (4 hours) LD50 ≥ 2,000 mg/kg Treated Filler Inpestion (4 hours) Rat (4 hours) LD50 6,450 mg/kg Mineral Filler Ingestion (4 hours) Rat (4 hours) LD50 > 5,000 mg/kg Mineral Filler Inhalation-Dust/Mist (4 hours) similar compoun ds LC50 > 2.08 mg/l Mineral Filler Inhalation-Dust/Mist (4 hours) kg LC50 > 2.08 mg/l 2,4,6-Tris(dimethylaminomonomethyl)phenol Dermal Rat LD50 1,280 mg/kg LC50 > 2.08 mg/l 2,4,6-Tris(dimethylaminomonomethyl)phenol Ingestion Rat LD50 1,000 mg/kg LD50 > 2,000 mg/kg m-Xylene-alpha.alpha'.Diamine Dermal Rabbit LD50 > 2,000 mg/kg LC50 > 2.08 mg/l m-Xylene-alpha.alpha'.Diamine Dermal Rat LD50 1,000 mg/kg LC50 1.2 mg/l Formaldehyde, Polymer with Benzenamine, Hydrogenated Ingestion Rat LD50 980 mg/kg LC50 1.2 mg/l Formaldehyde, Polymer with Benzenamine, Hydrogenated Dermal Rat LD50 stimated to be > 5,000 mg/kg LD50 estimated to be > 5,000 mg/kg Inorganic Filler Ingestion Rat LD50 stimated to be 2,000 - 5,000 mg/kg LD50 estimated to be 2,000 - 5,000 mg/kg N-Aminoethylpiperazine | T 17 | | | X 7 50 . 5 110 |
| Treated Filler Inhalation-Dust/Mist (4 hours) Rat (4 hours) LC50 s y g/g Treated Filler Ingestion Rat (1.050 > 5.000 mg/kg Mineral Filler Dermal similar compounds LD50 > 5.000 mg/kg Mineral Filler Inhalation-Dust/Mist (4 hours) ds LS0 > 2.08 mg/l Z.4,6-Tris(dimethylaminomonomethyl)phenol Dermal lestion Rat (1.050 1.280 mg/kg Z.4,6-Tris(dimethylaminomonomethyl)phenol Ingestion Rat (1.050 1.280 mg/kg m-Xylene-alpha alpha'.Diamine Dermal labit (4 hours) Rabbit (1.050 2.000 mg/kg m-Xylene-alpha alpha'.Diamine Inhalation-Dust/Mist (4 hours) LC50 1.2 mg/l m-Xylene-alpha alpha'.Diamine Ingestion Rat (4 hours) LC50 1.2 mg/l m-Xylene-alpha alpha'.Diamine Ingestion Rat (1.050 300 mg/kg Formaldehyde, Polymer with Benzenamine, Hydrogenated Pormal Rat (1.050 300 mg/kg Rat (1.050 300 mg/kg Formaldehyde, Polymer with Benzenamine, Hydrogenated Ingestion Rat (1.050 estimated to be > 5,000 mg/kg LD50 estimated to be 2,000 - 5,000 mg/kg Inorganic Filler Dermal Rabbit (1.050 865 mg/kg LD50 estimated to be 2,000 - 5,000 mg/kg N-Aminoethylpiperazine Ingestion Rat (1.050 1.470 mg/kg LD50 estimated to be > 5,000 mg/kg< | | U | | , 5 5 |
| Dust/Mist (4 hours) | | | | |
| Treated Filler | Treated Filler | | Rat | LC50 3 mg/l |
| Ingestion Rat LD50 6,450 mg/kg | | | | |
| $\begin{array}{c ccccccccccccccccccccccccccccccccccc$ | T . 1 P.11 | | D . | LD50 6450 // |
| Mineral Filler Dermal Dermal Similar compoun ds Mineral Filler Inhalation-Dust/Mist (4 hours) 2,4,6-Tris(dimethylaminomonomethyl)phenol Dermal Rat LD50 1,280 mg/kg LD50 2,000 mg/kg LD50 2,000 mg/kg LD50 1,280 mg/kg LD50 1,2 | | | | , , , |
| Mineral Filler Inhalation-Dust/Mist compoun (4 hours) ds | | | | , 6 6 |
| $ \begin{array}{c ccccccccccccccccccccccccccccccccccc$ | Mineral Filler | Dermal | | LD50 > 5,000 mg/kg |
| Inhalation-Dust/Mist (4 hours) Similar compoun (4 hours) Similar compoun (4 hours) Similar compoun (5 hours) Similar compoun (6 hours) Similar compoun (7 hours) Similar compoun (8 hours) Similar compound (8 h | | | 1 | |
| $\begin{array}{c ccccccccccccccccccccccccccccccccccc$ | Min and Eillen | T11-4: | | LC50 > 2.00 m =/1 |
| (4 hours)ds2,4,6-Tris(dimethylaminomonomethyl)phenolDermalRatLD501,280 mg/kg2,4,6-Tris(dimethylaminomonomethyl)phenolIngestionRatLD501,000 mg/kgm-Xylenealpha.alpha'.DiamineDermalRabbitLD50 > 2,000 mg/kgm-Xylenealpha.alpha'.DiamineInhalation-Dust/Mist (4 hours)RatLC501.2 mg/lm-Xylenealpha.alpha'.DiamineIngestionRatLD50 > 980 mg/kgFormaldehyde, Polymer with Benzenamine, HydrogenatedDermalRatLD50 > 700 mg/kgFormaldehyde, Polymer with Benzenamine, HydrogenatedIngestionRatLD50 estimated to be > 5,000 mg/kgInorganic FillerDermalLD50 estimated to be 2,000 - 5,000 mg/kgN-AminoethylpiperazineDermalRabbitLD50 estimated to be 2,000 - 5,000 mg/kgN-AminoethylpiperazineDermalRatLD50 estimated to be > 5,000 mg/kgQuartz SilicaDermalLD50 estimated to be > 5,000 mg/kg | Mineral Filler | | | LC30 > 2.08 mg/1 |
| 2,4,6-Tris(dimethylaminomonomethyl)phenolDermalRatLD501,280 mg/kg2,4,6-Tris(dimethylaminomonomethyl)phenolIngestionRatLD501,000 mg/kgm-Xylenealpha.alpha'.DiamineDermalRabbitLD50 > 2,000 mg/kgm-Xylenealpha.alpha'.DiamineInhalation-Dust/Mist (4 hours)RatLC501.2 mg/lm-Xylenealpha.alpha'.DiamineIngestionRatLD50 > 980 mg/kgFormaldehyde, Polymer with Benzenamine, HydrogenatedDermalRatLD50 > 700 mg/kgFormaldehyde, Polymer with Benzenamine, HydrogenatedIngestionRatLD50 = 300 mg/kgInorganic FillerDermalLD50 estimated to be > 5,000 mg/kgInorganic FillerIngestionLD50 estimated to be 2,000 - 5,000 mg/kgN-AminoethylpiperazineDermalRatLD50 = 865 mg/kgN-AminoethylpiperazineIngestionRatLD50 = 1,470 mg/kgQuartz SilicaDermalLD50 estimated to be > 5,000 mg/kg | | | 1 | |
| 2,4,6-Tris(dimethylaminomonomethyl)phenolIngestionRatLD50 1,000 mg/kgm-Xylene-alpha alpha'.DiamineDermalRabbitLD50 > 2,000 mg/kgm-Xylene-alpha alpha'.DiamineInhalation-Dust/Mist (4 hours)LC50 1.2 mg/lm-Xylene-alpha.alpha'.DiamineIngestionRatLD50 980 mg/kgFormaldehyde, Polymer with Benzenamine, HydrogenatedDermalRatLD50 > 700 mg/kgFormaldehyde, Polymer with Benzenamine, HydrogenatedIngestionRatLD50 setimated to be > 5,000 mg/kgInorganic FillerDermalLD50 estimated to be 2,000 - 5,000 mg/kgN-AminoethylpiperazineDermalRabbitLD50 865 mg/kgN-AminoethylpiperazineIngestionRatLD50 1,470 mg/kgQuartz SilicaDermalLD50 estimated to be > 5,000 mg/kg | 2.4.6-Tris(dimethylaminomonomethyl)phenol | | | LD50 1 280 mg/kg |
| m-Xylenealpha.alpha'.Diamine Dermal Rabbit LD50 > 2,000 mg/kg Inhalation-Dust/Mist (4 hours) m-Xylenealpha.alpha'.Diamine Ingestion Rat LD50 980 mg/kg Formaldehyde, Polymer with Benzenamine, Hydrogenated Dermal Rat LD50 300 mg/kg Inorganic Filler Ingestion Rat LD50 sestimated to be > 5,000 mg/kg Inorganic Filler Ingestion Dermal Rabbit LD50 estimated to be 2,000 - 5,000 mg/kg N-Aminoethylpiperazine Dermal Rabbit LD50 865 mg/kg LD50 estimated to be > 5,000 mg/kg LD50 estimated to be > 5,000 mg/kg LD50 estimated to be 2,000 - 5,000 mg/kg LD50 estimated to be 2,000 - 5,000 mg/kg N-Aminoethylpiperazine Dermal Rabbit LD50 865 mg/kg N-Aminoethylpiperazine Dermal LD50 estimated to be > 5,000 mg/kg LD50 estimated to be > 5,000 mg/kg | 7 7 3 71 | | | , |
| m-Xylenealpha.alpha'.Diamine Inhalation-Dust/Mist (4 hours) m-Xylenealpha.alpha'.Diamine Ingestion Formaldehyde, Polymer with Benzenamine, Hydrogenated Formaldehyde, Polymer with Benzenamine, Hydrogenated Ingestion Ingestion Rat LD50 980 mg/kg LD50 980 mg/kg LD50 980 mg/kg LD50 stimated to be > 5,000 mg/kg Inorganic Filler Ingestion | | | | |
| Dust/Mist (4 hours) m-Xylenealpha.alpha'.Diamine Ingestion Formaldehyde, Polymer with Benzenamine, Hydrogenated Formaldehyde, Polymer with Benzenamine, Hydrogenated Inorganic Filler Inorganic Filler Inorganic Filler Ingestion Ingestio | | | | , , , |
| m-Xylenealpha.lpha'.Diamine Ingestion Rat LD50 980 mg/kg Formaldehyde, Polymer with Benzenamine, Hydrogenated Dermal Rat LD50 300 mg/kg Formaldehyde, Polymer with Benzenamine, Hydrogenated Ingestion Rat LD50 300 mg/kg Inorganic Filler Dermal LD50 estimated to be > 5,000 mg/kg Inorganic Filler Ingestion LD50 estimated to be 2,000 - 5,000 mg/kg N-Aminoethylpiperazine Dermal Rabbit LD50 865 mg/kg N-Aminoethylpiperazine Ingestion Rat LD50 1,470 mg/kg Quartz Silica Dermal LD50 estimated to be > 5,000 mg/kg | тт-хуюнс-афиальна литис | | Kat | EC30 1.2 mg/1 |
| m-Xylenealpha.lpha'.Diamine Ingestion Rat LD50 980 mg/kg Formaldehyde, Polymer with Benzenamine, Hydrogenated Dermal Rat LD50 > 700 mg/kg Formaldehyde, Polymer with Benzenamine, Hydrogenated Ingestion Rat LD50 300 mg/kg Inorganic Filler Dermal LD50 estimated to be > 5,000 mg/kg Inorganic Filler Ingestion LD50 estimated to be 2,000 - 5,000 mg/kg N-Aminoethylpiperazine Dermal Rabbit LD50 865 mg/kg N-Aminoethylpiperazine Ingestion Rat LD50 1,470 mg/kg Quartz Silica Dermal LD50 estimated to be > 5,000 mg/kg | | | | |
| Formaldehyde, Polymer with Benzenamine, Hydrogenated Formaldehyde, Polymer with Benzenamine, Hydrogenated Ingestion Inorganic Filler Inorganic Filler Ingestion N-Aminoethylpiperazine Dermal Rat LD50 300 mg/kg LD50 estimated to be > 5,000 mg/kg LD50 estimated to be 2,000 - 5,000 mg/kg LD50 estimated to be 2,000 - 5,000 mg/kg LD50 estimated to be 2,000 - 5,000 mg/kg N-Aminoethylpiperazine Dermal Rabbit LD50 865 mg/kg N-Aminoethylpiperazine Ingestion Rat LD50 1,470 mg/kg LD50 estimated to be > 5,000 mg/kg | m-Xylene-,alpha,alpha',Diamine | | Rat | LD50 980 mg/kg |
| | | | | |
| | | | | |
| $ \begin{array}{c ccccccccccccccccccccccccccccccccccc$ | , , , , , , , , , , , , , , , , , , , | | | |
| | Inorganic Filler | Ingestion | | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Quartz Silica Dermal LD50 estimated to be > 5,000 mg/kg | N-Aminoethylpiperazine | Dermal | Rabbit | LD50 865 mg/kg |
| , 5 5 | N-Aminoethylpiperazine | Ingestion | Rat | LD50 1,470 mg/kg |
| Quartz Silica Ingestion LD50 estimated to be > 5,000 mg/kg | Quartz Silica | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| | Quartz Silica | Ingestion | | LD50 estimated to be > 5,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|--|-----------|---------------------------|
| | | |
| Bis(3-Aminopropyl) Ether of Diethylene Glycol | Rabbit | Corrosive |
| Aluminum | Rabbit | No significant irritation |
| Methylenedi(cyclohexylamine) | Rabbit | Corrosive |
| 2-Propenenitrile, Polymer with 1,3-Butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated | Rabbit | Irritant |
| Treated Inorganic Filler | Rabbit | No significant irritation |
| Treated Filler | Rabbit | No significant irritation |
| Mineral Filler | similar | No significant irritation |
| | compoun | |
| | ds | |
| 2,4,6-Tris(dimethylaminomonomethyl)phenol | Rabbit | Corrosive |
| m-Xylenealpha.alpha'.Diamine | Rat | Corrosive |
| Formaldehyde, Polymer with Benzenamine, Hydrogenated | In vitro | Corrosive |
| | data | |
| Inorganic Filler | Professio | No significant irritation |
| | nal | |
| | judgemen | |
| | t | |
| N-Aminoethylpiperazine | Rabbit | Corrosive |
| Quartz Silica | Professio | No significant irritation |
| | nal | |

| judgemen | |
|----------|--|
| t | |

Serious Eye Damage/Irritation

| Name | Species | Value |
|--|-----------|---------------------------|
| Bis(3-Aminopropyl) Ether of Diethylene Glycol | Rabbit | Corrosive |
| | | |
| Aluminum | Rabbit | No significant irritation |
| Methylenedi(cyclohexylamine) | Rabbit | Corrosive |
| 2-Propenenitrile, Polymer with 1,3-Butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1- | Rabbit | Mild irritant |
| piperazinyl)ethyl]amino]butyl-terminated | | |
| Treated Inorganic Filler | Rabbit | No significant irritation |
| Treated Filler | Rabbit | No significant irritation |
| Mineral Filler | similar | Mild irritant |
| | compoun | |
| | ds | |
| 2,4,6-Tris(dimethylaminomonomethyl)phenol | Rabbit | Corrosive |
| m-Xylenealpha.alpha'.Diamine | Rabbit | Corrosive |
| Formaldehyde, Polymer with Benzenamine, Hydrogenated | similar | Corrosive |
| | health | |
| | hazards | |
| Inorganic Filler | Professio | No significant irritation |
| | nal | |
| | judgemen | |
| | t | |
| N-Aminoethylpiperazine | Rabbit | Corrosive |

Sensitization:

Skin Sensitization

| Name | Species | Value |
|--|-----------------------------------|----------------|
| Bis(3-Aminopropyl) Ether of Diethylene Glycol | Professio nal judgemen t | Sensitizing |
| Aluminum | Guinea pig | Not classified |
| Methylenedi(cyclohexylamine) | Guinea pig | Sensitizing |
| 2-Propenenitrile, Polymer with 1,3-Butadiene, 1-cyano-1-methyl-4-oxo-4-[[2-(1-piperazinyl)ethyl]amino]butyl-terminated | Guinea pig | Sensitizing |
| Treated Inorganic Filler | Human and animal | Not classified |
| Mineral Filler | Human | Not classified |
| 2,4,6-Tris(dimethylaminomonomethyl)phenol | Guinea pig | Not classified |
| m-Xylenealpha.alpha'.Diamine | Guinea pig | Sensitizing |
| Formaldehyde, Polymer with Benzenamine, Hydrogenated | Professio nal judgemen t | Sensitizing |
| N-Aminoethylpiperazine | Guinea pig | Sensitizing |

Respiratory Sensitization

| Name | Species | Value |
|----------|---------|----------------|
| | | |
| Aluminum | Human | Not classified |

Germ Cell Mutagenicity

| Name | Route | Value |
|------|-------|-------|
|------|-------|-------|

Page: 10 of 20

| Bis(3-Aminopropyl) Ether of Diethylene Glycol | In Vitro | Not mutagenic |
|--|----------|--|
| Aluminum | In Vitro | Not mutagenic |
| Treated Inorganic Filler | In Vitro | Not mutagenic |
| Mineral Filler | In Vitro | Not mutagenic |
| Mineral Filler | In vivo | Not mutagenic |
| 2,4,6-Tris(dimethylaminomonomethyl)phenol | In Vitro | Not mutagenic |
| m-Xylenealpha.alpha'.Diamine | In Vitro | Not mutagenic |
| m-Xylenealpha.alpha'.Diamine | In vivo | Not mutagenic |
| Formaldehyde, Polymer with Benzenamine, Hydrogenated | In Vitro | Not mutagenic |
| Inorganic Filler | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| N-Aminoethylpiperazine | In vivo | Not mutagenic |
| N-Aminoethylpiperazine | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Quartz Silica | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Quartz Silica | In vivo | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| ear emogenierty | | | |
|--------------------------|------------------|-------------------------------|--|
| Name | Route | Species | Value |
| Treated Inorganic Filler | Not Specified | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Inorganic Filler | Inhalation | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |
| Quartz Silica | Inhalation | Human and animal | Carcinogenic |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|--|-----------|--|-------------------------------|-----------------------------|------------------------------|
| Bis(3-Aminopropyl) Ether of Diethylene Glycol | Ingestion | Not classified for female reproduction | Rat | NOAEL 600 mg/kg/day | premating into lactation |
| Bis(3-Aminopropyl) Ether of Diethylene Glycol | Ingestion | Not classified for male reproduction | Rat | NOAEL 600 mg/kg/day | 59 days |
| Bis(3-Aminopropyl) Ether of Diethylene Glycol | Ingestion | Not classified for development | Rat | NOAEL 600 mg/kg/day | premating into lactation |
| Treated Inorganic Filler | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Treated Inorganic Filler | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Treated Inorganic Filler | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesis |
| Treated Filler | Ingestion | Not classified for development | Rat | NOAEL 625 mg/kg/day | premating & during gestation |
| Mineral Filler | Ingestion | Not classified for development | Multiple animal species | NOAEL 1,600 mg/kg/day | during organogenesis |
| 2,4,6- Tris(dimethylaminomonomethyl)phenol | Ingestion | Not classified for male reproduction | Rat | NOAEL 150 mg/kg/day | 2 generation |
| 2,4,6- Tris(dimethylaminomonomethyl)phenol | Ingestion | Not classified for female reproduction | Rat | NOAEL 50 mg/kg/day | 2 generation |
| 2,4,6- Tris(dimethylaminomonomethyl)phenol | Ingestion | Not classified for development | Rabbit | NOAEL 15 mg/kg/day | during gestation |
| m-Xylenealpha.alpha'.Diamine | Ingestion | Not classified for female reproduction | Rat | NOAEL 450 mg/kg/day | 1 generation |
| m-Xylenealpha.alpha'.Diamine | Ingestion | Not classified for male reproduction | Rat | NOAEL 450 mg/kg | 1 generation |

| m-Xylenealpha.alpha'.Diamine | Ingestion | Not classified for development | Rat | NOAEL 450 | 1 generation |
|---|-----------|--|--------|-----------|----------------|
| | | | | mg/kg/day | |
| Formaldehyde, Polymer with Benzenamine, | Ingestion | Not classified for female reproduction | Rat | NOAEL 140 | premating |
| Hydrogenated | | | | mg/kg/day | into lactation |
| Formaldehyde, Polymer with Benzenamine, | Ingestion | Not classified for male reproduction | Rat | NOAEL 140 | 28 days |
| Hydrogenated | | | | mg/kg/day | |
| Formaldehyde, Polymer with Benzenamine, | Ingestion | Not classified for development | Rat | NOAEL 280 | during |
| Hydrogenated | | _ | | mg/kg/day | gestation |
| N-Aminoethylpiperazine | Ingestion | Not classified for female reproduction | Rat | NOAEL 598 | premating & |
| | | | | mg/kg/day | during |
| | | | | | gestation |
| N-Aminoethylpiperazine | Ingestion | Not classified for male reproduction | Rat | NOAEL 409 | 32 days |
| | | _ | | mg/kg/day | |
| N-Aminoethylpiperazine | Ingestion | Toxic to development | Rabbit | NOAEL 75 | during |
| | _ | - | | mg/kg/day | gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|------------|------------------------|--|------------------------------|------------------------|----------------------|
| Bis(3-Aminopropyl) Ether of Diethylene Glycol | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| Methylenedi(cyclohexylam ine) | Inhalation | respiratory irritation | May cause respiratory irritation | similar health hazards | NOAEL Not available | |
| 2-Propenenitrile, Polymer with 1,3-Butadiene, 1- cyano-1-methyl-4-oxo-4- [[2-(1- piperazinyl)ethyl]amino]bu tyl-terminated | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL not available | |
| Treated Filler | Inhalation | respiratory system | Not classified | Rat | NOAEL 0.812 mg/l | 90 minutes |
| 2,4,6- Tris(dimethylaminomonom ethyl)phenol | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| m- Xylenealpha.alpha'.Diami ne | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Not available | NOAEL Not avaliable | |
| Formaldehyde, Polymer with Benzenamine, Hydrogenated | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| N-Aminoethylpiperazine | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|------------|---|----------------|---------|------------------------|-----------------------|
| Bis(3-Aminopropyl) Ether of Diethylene Glycol | Ingestion | gastrointestinal tract heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system | Not classified | Rat | NOAEL 600 mg/kg/day | 59 days |
| Aluminum | Inhalation | nervous system respiratory system | Not classified | Human | NOAEL Not available | occupational exposure |

| Methylenedi(cyclohexyla mine) | Ingestion | liver muscles | May cause damage to organs though prolonged or repeated exposure | Rat | NOAEL 15 mg/kg/day | 36 days |
|--|------------|---|--|------------------------|-----------------------------|-----------------------|
| Treated Inorganic Filler | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Treated Filler | Inhalation | respiratory system | Not classified | Human | NOAEL Not available | occupational exposure |
| Mineral Filler | Inhalation | respiratory system | Not classified | Human | NOAEL Not available | occupational exposure |
| Mineral Filler | Inhalation | pulmonary fibrosis | Not classified | Human and animal | NOAEL Not available | |
| Mineral Filler | Ingestion | liver kidney and/or bladder hematopoietic system | Not classified | Rat | NOAEL 2,500 mg/kg/day | 2 years |
| 2,4,6- Tris(dimethylaminomono methyl)phenol | Dermal | skin | Not classified | Rat | NOAEL 25 mg/kg/day | 4 weeks |
| 2,4,6- Tris(dimethylaminomono methyl)phenol | Dermal | liver nervous system auditory system hematopoietic system eyes | Not classified | Rat | NOAEL 125 mg/kg/day | 4 weeks |
| 2,4,6- Tris(dimethylaminomono methyl)phenol | Ingestion | heart endocrine system hematopoietic system liver muscles nervous system kidney and/or bladder respiratory system vascular system auditory system skin gastrointestinal tract bone, teeth, nails, and/or hair immune system eyes | Not classified | Rat | NOAEL 150 mg/kg/day | 90 days |
| m- Xylenealpha.alpha'.Diam ine | Ingestion | endocrine system blood bone marrow | Not classified | Rat | NOAEL 600 mg/kg/day | 28 days |
| Formaldehyde, Polymer with Benzenamine, Hydrogenated | Ingestion | kidney and/or bladder | May cause damage to organs though prolonged or repeated exposure | Rat | NOAEL 15 mg/kg/day | 28 days |
| Formaldehyde, Polymer with Benzenamine, Hydrogenated | Ingestion | endocrine system hematopoietic system liver nervous system | Not classified | Rat | NOAEL 300 mg/kg/day | 28 days |
| Inorganic Filler | Inhalation | respiratory system | Not classified | Human | NOAEL not available | occupational exposure |
| N-Aminoethylpiperazine | Dermal | skin | Not classified | Rat | NOAEL 100 mg/kg/day | 29 days |
| N-Aminoethylpiperazine | Dermal | hematopoietic system nervous system kidney and/or bladder | Not classified | Rat | NOAEL 1,000 mg/kg/day | 29 days |
| N-Aminoethylpiperazine | Inhalation | respiratory system | Causes damage to organs through prolonged or repeated exposure | Rat | NOAEL 0.2 mg/m3 | 13 weeks |
| N-Aminoethylpiperazine | Inhalation | hematopoietic system eyes kidney and/or bladder | Not classified | Rat | NOAEL 53.8 mg/m3 | 13 weeks |
| N-Aminoethylpiperazine | Ingestion | heart endocrine system hematopoietic system liver | Not classified | Rat | NOAEL 598 mg/kg/day | 28 days |

| | | nervous system kidney and/or bladder | | | | |
|---------------|------------|--|--|-------|---------------------|-----------------------|
| Quartz Silica | Inhalation | silicosis | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects

No product test data available

| Material | Cas # | Organism | Type | Exposure | Test Endpoint | Test Result |
|---|--------------|-------------|---|----------|---------------|-------------|
| Bis(3- Aminopropyl) Ether of Diethylene Glycol | 4246-51-9 | Bacteria | Experimental | 17 hours | EC50 | 4,000 mg/l |
| Bis(3- Aminopropyl) Ether of Diethylene Glycol | 4246-51-9 | Golden Orfe | Experimental | 96 hours | LC50 | >1,000 mg/l |
| Bis(3- Aminopropyl) Ether of Diethylene Glycol | 4246-51-9 | Green algae | Experimental | 72 hours | EC50 | >500 mg/l |
| Bis(3- Aminopropyl) Ether of Diethylene Glycol | 4246-51-9 | Water flea | Experimental | 48 hours | EC50 | 218.16 mg/l |
| Bis(3- Aminopropyl) Ether of Diethylene Glycol | 4246-51-9 | Green algae | Experimental | 72 hours | EC10 | 5.4 mg/l |
| Epoxy Copolymer | Trade Secret | N/A | Data not available or insufficient for classification | N/A | N/A | N/A |
| Acrylic Copolymer | Trade Secret | N/A | Data not available or insufficient for classification | N/A | N/A | N/A |
| 2-Propenenitrile, Polymer with 1,3- Butadiene, 1- cyano-1-methyl-4- oxo-4-[[2-(1- | 68683-29-4 | N/A | Data not available or insufficient for classification | N/A | N/A | N/A |

| | | | | , | | |
|---|--------------|------------------|------------------------------------|------------|-----------------------------------|---------------------------|
| piperazinyl)ethyl]a | | | | | | |
| mino]butyl- | | | | | | |
| terminated | | | | | | |
| Aluminum | 7429-90-5 | Fish | Experimental | 96 hours | No tox obs at lmt of water sol | >100 mg/l |
| Aluminum | 7429-90-5 | Green algae | Experimental | 72 hours | No tox obs at lmt of water sol | >100 mg/l |
| Aluminum | 7429-90-5 | Water flea | Experimental | 48 hours | No tox obs at lmt of water sol | >100 mg/l |
| Aluminum | 7429-90-5 | Green algae | Experimental | 72 hours | No tox obs at lmt of water sol | 100 mg/l |
| Aluminum | 7429-90-5 | Water flea | Experimental | 21 days | NOEC NOEC | 0.076 mg/l |
| Methylenedi(cyclo | 1761-71-3 | Golden Orfe | Experimental | 96 hours | LC50 | >100 mg/l |
| hexylamine) Methylenedi(cyclo | 1761-71-3 | Green algae | Experimental | 72 hours | EC50 | 140 mg/l |
| hexylamine) Methylenedi(cyclo | 1761-71-3 | Water flea | Experimental | 48 hours | EC50 | 7.07 mg/l |
| hexylamine) Methylenedi(cyclo | 1761-71-3 | Water flea | Analogous | 21 days | NOEC | 4 mg/l |
| hexylamine) | | | Compound | | | |
| Methylenedi(cyclo hexylamine) | 1761-71-3 | Green algae | Experimental | 72 hours | EC10 | 100 mg/l |
| Methylenedi(cyclo hexylamine) | 1761-71-3 | Redworm | Analogous Compound | 56 days | EC10 | 228 mg/kg (Dry Weight) |
| Methylenedi(cyclo hexylamine) | 1761-71-3 | Soil microbes | Analogous Compound | 28 days | EC10 | >1,000 mg/kg (Dry Weight) |
| Methylenedi(cyclo hexylamine) | 1761-71-3 | Bacteria | Experimental | 30 minutes | EC50 | 156 mg/l |
| Treated Inorganic | Trade Secret | N/A | Data not available | N/A | N/A | N/A |
| Filler | Trade Secret | 11/11 | or insufficient for classification | 14/11 | 14/14 | 1071 |
| Inorganic Filler | Trade Secret | Green algae | Experimental | 72 hours | EC50 | >1,000 mg/l |
| Inorganic Filler | Trade Secret | Water flea | Experimental | 72 hours | EC50 | >1,000 mg/l |
| Inorganic Filler | Trade Secret | Zebra Fish | Experimental | 96 hours | LC50 | >1,000 mg/l |
| Inorganic Filler | Trade Secret | Green algae | Experimental | 72 hours | NOEC | >=1,000 mg/l |
| Mineral Filler | Trade Secret | N/A | Data not available | N/A | N/A | N/A |
| Williera Tiller | Trade Secret | 11/11 | or insufficient for classification | 14/11 | 14/14 | 17/11 |
| Treated Filler | Trade Secret | Green algae | Estimated | 72 hours | EC50 | >100 mg/l |
| Treated Filler | Trade Secret | Rainbow Trout | Estimated | 96 hours | LC50 | >100 mg/l |
| Treated Filler | Trade Secret | Water flea | Estimated | 48 hours | EC50 | >100 mg/l |
| Treated Filler | Trade Secret | Green algae | Estimated | 72 hours | EC10 | >100 mg/l |
| 2,4,6- | 90-72-2 | N/A | Experimental | 96 hours | LC50 | 718 mg/l |
| Tris(dimethylamin omonomethyl)phen ol | | IVA | Lapermentar | 70 Hours | EC30 | 710 mg/1 |
| 2,4,6- Tris(dimethylamin | 90-72-2 | Common Carp | Experimental | 96 hours | LC50 | >100 mg/l |
| omonomethyl)phen | | | | | | |
| 2,4,6- | 90-72-2 | Green algae | Experimental | 72 hours | EC50 | 46.7 mg/l |
| Tris(dimethylamin | | oreen ungue | Z.iperimentar | 72 110 015 | 1200 | 10.7 mg/1 |
| omonomethyl)phen | | | | | | |
| 2,4,6- | 90-72-2 | Water flea | Experimental | 48 hours | EC50 | >100 mg/l |
| Tris(dimethylamin |] 70 72 2 | Water fied | Experimental | 10 Hours | Less | 100 mg/1 |
| omonomethyl)phen | | | | | | |
| 2,4,6- | 90-72-2 | Green algae | Experimental | 72 hours | NOEC | 6.44 mg/l |
| Tris(dimethylamin | | | r | | | |
| omonomethyl)phen | | | | | | |
| Formaldehyde, | 135108-88-2 | Activated sludge | Experimental | 3 hours | EC50 | 186.7 mg/l |
| Polymer with Benzenamine, | | | | | | |
| Hydrogenated | | | | | | |
| Formaldehyde, | 135108-88-2 | Green algae | Experimental | 72 hours | EC50 | 43.94 mg/l |
| i ominimonyuc, | 1133100 00-2 | 1 Green argae | Laperinientai | , 2 110013 | IEC20 | 15.77 IIIg/I |

| Polymer with | T | 1 | | | 1 | 1 |
|-------------------|-------------|------------------|--------------|------------|-------|-------------|
| | | | | | | |
| Benzenamine, | | | | | | |
| Hydrogenated | | | | | | |
| Formaldehyde, | 135108-88-2 | Guppy | Experimental | 96 hours | LC50 | 63 mg/l |
| Polymer with | | | | | | |
| Benzenamine, | | | | | | |
| Hydrogenated | | | | | | |
| Formaldehyde, | 135108-88-2 | Water flea | Experimental | 48 hours | EC50 | 15.4 mg/l |
| Polymer with | | | - | | | |
| Benzenamine, | | | | | | |
| Hydrogenated | | | | | | |
| Formaldehyde, | 135108-88-2 | Green algae | Experimental | 72 hours | EC10 | 1.2 mg/l |
| Polymer with | | | F | | | |
| Benzenamine. | | | | | | |
| Hydrogenated | | | | | | |
| m- | 1477-55-0 | Activated sludge | Experimental | 30 minutes | EC50 | >1,000 mg/l |
| Xylenealpha.alph | 14/7-33-0 | Activated studge | Experimental | 30 minutes | EC30 | -1,000 mg/1 |
| a'.Diamine | | | | | | |
| | 1477.55.0 | In t | E : 41 | 161 | EC10 | 24 / |
| m- | 1477-55-0 | Bacteria | Experimental | 16 hours | EC10 | 24 mg/l |
| Xylenealpha.alph | | | | | | |
| a'.Diamine | | | | | | |
| m- | 1477-55-0 | Green algae | Experimental | 72 hours | ErC50 | 28 mg/l |
| Xylenealpha.alph | | | | | | |
| a'.Diamine | | | | | | |
| m- | 1477-55-0 | Medaka | Experimental | 96 hours | LC50 | 87.6 mg/l |
| Xylenealpha.alph | | | 1 | | | |
| a'.Diamine | | | | | | |
| m- | 1477-55-0 | Water flea | Experimental | 48 hours | EC50 | 15.2 mg/l |
| Xylenealpha.alph | | | | | | |
| a'.Diamine | | | | | | |
| m- | 1477-55-0 | Green algae | Experimental | 72 hours | NOEC | 9.8 mg/l |
| Xylenealpha.alph | 1477-33-0 | Green algae | Experimental | /2 Hours | INOLE | 7.8 mg/1 |
| a'.Diamine | | | | | | |
| m- | 1477-55-0 | Water flea | E | 21 4 | NOEC | 4.7/1 |
| | 14//-33-0 | water nea | Experimental | 21 days | NOEC | 4.7 mg/l |
| Xylenealpha.alph | | | | | | |
| a'.Diamine | | ļ | | | | |
| N- | 140-31-8 | Bacteria | Experimental | 17 hours | EC10 | 100 mg/l |
| Aminoethylpiperaz | | | | | | |
| ine | | | | | | |
| N- | 140-31-8 | Golden Orfe | Experimental | 96 hours | LC50 | 368 mg/l |
| Aminoethylpiperaz | | | - | | | |
| ine | | | | | | |
| N- | 140-31-8 | Green algae | Experimental | 72 hours | EC50 | >1,000 mg/l |
| Aminoethylpiperaz | | | F | | | , |
| ine | | | | | | |
| N- | 140-31-8 | Water flea | Experimental | 48 hours | EC50 | 58 mg/l |
| Aminoethylpiperaz | 140 31 0 | Water frea | Experimental | 40 Hours | Leso | 30 mg/1 |
| ine | | | 1 | | | |
| N- | 140-31-8 | Green algae | Experimental | 72 hours | NOEC | 31 mg/l |
| | 140-31-8 | Oreen aigae | Experimental | /2 Hours | INOEC | 31 Hig/1 |
| Aminoethylpiperaz | | | | | | |
| ine | 11000 00 - | ļ | <u> </u> | | 7.7. | 1110 11 |
| Quartz Silica | 14808-60-7 | Green algae | Estimated | 72 hours | EC50 | 440 mg/l |
| Quartz Silica | 14808-60-7 | Water flea | Estimated | 48 hours | EC50 | 7,600 mg/l |
| Quartz Silica | 14808-60-7 | Zebra Fish | Estimated | 96 hours | LC50 | 5,000 mg/l |
| Quartz Silica | 14808-60-7 | Green algae | Estimated | 72 hours | NOEC | 60 mg/l |
| | | | | | | |

12.2. Persistence and degradability

| Material | CAS No. | Test Type | Duration | Study Type | Test Result | Protocol |
|---|-----------|--------------------------------|----------|------------|-------------|----------------------------------|
| Bis(3- Aminopropyl) Ether of Diethylene Glycol | 4246-51-9 | Experimental Biodegradation | | evolution | | OECD 301B - Mod. Sturm or CO2 |

| Bis(3- | 4246-51-9 | Estimated | | Photolytic half-life | 2 06 hours (t 1/2) | 1 |
|---|--------------|--|---------|-----------------------------|---|-----------------------------------|
| Aminopropyl) Ether of Diethylene Glycol | | Photolysis | | (in air) | 2.96 nours (t 1/2) | |
| Epoxy Copolymer | Trade Secret | Data not availbl- insufficient | N/A | N/A | N/A | N/A |
| Acrylic Copolymer | Trade Secret | Data not availbl- insufficient | N/A | N/A | N/A | N/A |
| 2-Propenenitrile, Polymer with 1,3- Butadiene, 1- cyano-1-methyl-4- oxo-4-[[2-(1- piperazinyl)ethyl]a mino]butyl- terminated | 68683-29-4 | Data not availbl- insufficient | N/A | N/A | N/A | N/A |
| Aluminum | 7429-90-5 | Data not availbl- insufficient | N/A | N/A | N/A | N/A |
| Methylenedi(cyclo hexylamine) | 1761-71-3 | Analogous Compound Biodegradation | 28 days | Biological Oxygen Demand | 0 %BOD/ThOD | OECD 301C - MITI (I) |
| Methylenedi(cyclo hexylamine) | 1761-71-3 | Analogous Compound Aquatic Inherent Biodegrad. | 28 days | Percent degraded | <1 %removal of DOC | OECD 302B Zahn- Wellens/EVPA |
| Treated Inorganic Filler | Trade Secret | Data not availbl- insufficient | N/A | N/A | N/A | N/A |
| Inorganic Filler | Trade Secret | Data not availbl- insufficient | N/A | N/A | N/A | N/A |
| Mineral Filler | Trade Secret | Data not availbl- insufficient | N/A | N/A | N/A | N/A |
| Treated Filler | Trade Secret | Data not availbl- insufficient | N/A | N/A | N/A | N/A |
| 2,4,6- Tris(dimethylamin omonomethyl)phen ol | 90-72-2 | Experimental Biodegradation | 28 days | Biological Oxygen Demand | 4 %BOD/ThOD | OECD 301D - Closed Bottle Test |
| Formaldehyde, Polymer with Benzenamine, Hydrogenated | 135108-88-2 | Experimental Biodegradation | 28 days | Biological Oxygen Demand | 0 %BOD/ThOD | |
| m- Xylenealpha.alph a'.Diamine | 1477-55-0 | Experimental Biodegradation | 28 days | Carbon dioxide evolution | 49 %CO2 evolution/THCO2 evolution | OECD 301B - Mod. Sturm or CO2 |
| m- Xylenealpha.alph a'.Diamine | 1477-55-0 | Experimental Aquatic Inherent Biodegrad. | 28 days | Biological Oxygen Demand | 22 %BOD/ThOD | OECD 302C - Modified MITI (II) |
| N- Aminoethylpiperaz ine | 140-31-8 | Experimental Biodegradation | 28 days | Biological Oxygen Demand | 0 %BOD/ThOD | OECD 301C - MITI (I) |
| Quartz Silica | 14808-60-7 | Data not availbl- insufficient | N/A | N/A | N/A | N/A |

12.3. Bioaccumulative potential

| Material | CAS No. | Test Type | Duration | Study Type | Test Result | Protocol |
|---|--------------|---|----------|--------------------------------------|-------------|----------|
| Bis(3- Aminopropyl) Ether of Diethylene Glycol | 4246-51-9 | Experimental Bioconcentration | | Log of Octanol/H2O part. coeff | -1.25 | |
| Epoxy Copolymer | Trade Secret | Estimated Bioconcentration | | Bioaccumulation Factor | 2.9 | |
| Acrylic Copolymer | Trade Secret | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| 2-Propenenitrile, Polymer with 1,3- | 68683-29-4 | Data not available or insufficient for | N/A | N/A | N/A | N/A |

| Butadiene, 1- | 1 | classification | I | | | T |
|---------------------|--------------|--------------------------------|---------|-------------------|-------|------------------------------|
| cyano-1-methyl-4- | | ciassification | | | | |
| oxo-4-[[2-(1- | | | | | | |
| piperazinyl)ethyl]a | | | | | | |
| mino]butyl- | | | | | | |
| terminated | | | | | | |
| Aluminum | 7429-90-5 | Data not available | N/A | N/A | N/A | N/A |
| | | or insufficient for | | | | |
| | | classification | | | | |
| Methylenedi(cyclo | 1761-71-3 | Analogous | | Bioaccumulation | <60 | OECD305-Bioconcentration |
| hexylamine) | | Compound BCF - | | Factor | | |
| | | Fish | | | | |
| Methylenedi(cyclo | 1761-71-3 | Experimental | | Log of | 2.03 | OECD 107 log Kow shke |
| hexylamine) | | Bioconcentration | | Octanol/H2O part. | | flsk mtd |
| | | | | coeff | | |
| Treated Inorganic | Trade Secret | Data not available | N/A | N/A | N/A | N/A |
| Filler | | or insufficient for | | | | |
| | | classification | | | | |
| Inorganic Filler | Trade Secret | Data not available | N/A | N/A | N/A | N/A |
| | | or insufficient for | | | | |
| | m 1 0 | classification | 27/4 | 27/4 | 27/4 | 27/4 |
| Mineral Filler | Trade Secret | Data not available | N/A | N/A | N/A | N/A |
| | | or insufficient for | | | | |
| m . 1 mm | m 1 0 | classification | 27/4 | 27/4 | 27/4 | 27/4 |
| Treated Filler | Trade Secret | Data not available | N/A | N/A | N/A | N/A |
| | | or insufficient for | | | | |
| 2,4,6- | 90-72-2 | classification Experimental | | Log of | -0.66 | 830.7550 Part.Coef Shake |
| Tris(dimethylamin | 90-72-2 | Bioconcentration | | Octanol/H2O part. | -0.00 | Flask |
| omonomethyl)phen | | Bioconcentration | | coeff | | 1 lask |
| ol | | | | COCII | | |
| Formaldehyde, | 135108-88-2 | Experimental BCF | 56 days | Bioaccumulation | ≤ 219 | OECD305-Bioconcentration |
| Polymer with | 133100 00 2 | - Fish | 30 days | Factor | | GEED303 Bioconcentration |
| Benzenamine, | | 1 1011 | | T uctor | | |
| Hydrogenated | | | | | | |
| Formaldehyde, | 135108-88-2 | Experimental | | Log of | 2.68 | EC A.8 Partition Coefficient |
| Polymer with | | Bioconcentration | | Octanol/H2O part. | | |
| Benzenamine, | | | | coeff | | |
| Hydrogenated | | | | | | |
| m- | 1477-55-0 | Experimental BCF | 42 days | Bioaccumulation | <2.7 | OECD305-Bioconcentration |
| Xylenealpha.alph | | - Fish | | Factor | | |
| a'.Diamine | | | | | | |
| m- | 1477-55-0 | Extrapolated | | Log of | 0.18 | OECD 107 log Kow shke |
| Xylenealpha.alph | | Bioconcentration | | Octanol/H2O part. | | flsk mtd |
| a'.Diamine | | | | coeff | | |
| N- | 140-31-8 | Experimental | | Log of | 0.3 | |
| Aminoethylpiperaz | | Bioconcentration | | Octanol/H2O part. | | |
| ine | | | | coeff | | |
| Quartz Silica | 14808-60-7 | Data not available | N/A | N/A | N/A | N/A |
| | | or insufficient for | | | | |
| | | classification | | | | |

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number: UN2735

Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S.

Technical Name: None assigned. Hazard Class/Division: 8
Subsidiary Risk: None assigned.

Packing Group:II

Limited Quantity: None assigned.

Marine Pollutant: Yes

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number: UN2735

Proper Shipping Name: AMINES, LIQUID, CORROSIVE, N.O.S.

Technical Name: None assigned.

Hazard Class/Division:8

Subsidiary Risk: None assigned.

Packing Group:II

Limited Quantity: None assigned.

Marine Pollutant: Yes

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use

(except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my



Safety Data Sheet

Copyright, 2024, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:33-5988-2Version Number:1.00Issue Date:11/11/2024Supercedes Date:Initial Issue

This Safety Data Sheet has been prepared in accordance with the Malaysia Occupational Safety and Health (Chemical Classification, Labelling and Safety Data Sheets) Regulations 2013.

SECTION 1: Identification

1.1. Product identifier

3MTM Impact Resistant Structural Adhesive (Part B) PNs 07333, 57333

Product Identification Numbers

UU-0127-4525-1

1.2. Recommended use and restrictions on use

Recommended use

Automotive, Base side of two-part color changing adhesive with optimized shear, peel and impact performance.

For Industrial or Professional use only

1.3. Supplier's details

ADDRESS: 3M Malaysia Sdn. Bhd., Level 8, Block F, Oasis Square, No.2, Jalan PJU 1A/7A, Ara Damansara 47301

Petaling, Jaya, Selangor

Telephone: 03-7884 2888

E Mail: 3mmyehsr@mmm.com Website: www.3M.com.my

1.4. Emergency telephone number

+60 03-7884 2888

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2.

Skin Sensitizer: Category 1.

Germ Cell Mutagenicity: Category 2. Carcinogenicity: Category 1B.

Chronic Aquatic Toxicity: Category 2.

2.2. Label elements

Signal word

Danger

Symbols

Exclamation mark | Health Hazard | Environment |

Pictograms







Hazard Statements:

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H341 Suspected of causing genetic defects.

H350 May cause cancer.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Prevention:

P201 Obtain special instructions before use.
P273 Avoid release to the environment.

P280E Wear protective gloves.

P281 Use personal protective equipment as required.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with applicable

local/regional/national/international regulations.

2.3. Other hazards

None known

SECTION 3: Composition/information on ingredients

This material is a mixture.

| Ingredient | C.A.S. No. | % by Wt |
|------------------------------|--------------|---------|
| 4,4'-Isopropylidenediphenol- | 25068-38-6 | 70 - 90 |
| Epichlorohydrin Polymer | | |
| Synthetic Rubber | Trade Secret | 4 - 20 |
| Treated Filler | Trade Secret | 1 - 5 |
| Treated Inorganic Filler | Trade Secret | 1 - 5 |

| Inorganic Filler | Trade Secret | 1 - 5 |
|--|--------------|-----------|
| Benzoic Acid, C9-C11-Branched Alkyl | 131298-44-7 | 1 - 5 |
| Esters | | |
| 1,4-Bis[(2,3- | 14228-73-0 | 1 - 5 |
| Epoxypropoxy)Methyl]Cyclohexane | | |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | 2530-83-8 | < 3 |
| Phenolphthalein | 77-09-8 | 0.1 - 0.5 |

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eve Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

| Substance | <u>Condition</u> |
|-------------------|-------------------|
| Aldehydes | During Combustion |
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |
| Hydrogen Chloride | During Combustion |

5.3. Special protective actions for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation

to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|------------------|------------|---------------|--------------------------------|----------------------------|
| Inorganic Filler | Trade | ACGIH | TWA(inhalable | |
| | Secret | | particulates):10 mg/m3 | |
| Inorganic Filler | Trade | ACGIH | TWA(respirable particles):3 | |
| _ | Secret | | mg/m3 | |
| Inorganic Filler | Trade | Malaysia OELs | TWA (proposed)(respirable | |
| _ | Secret | - | particles)(8 hours):3 | |
| | | | mg/m3;TWA | |
| | | | (proposed)(Inhalable | |
| | | | particulate)(8 hours):10 mg/m3 | |
| Treated Filler | Trade | ACGIH | TWA(inhalable | |
| | Secret | | particulates):10 mg/m3 | |
| Treated Filler | Trade | ACGIH | TWA(respirable particles):3 | |
| | Secret | | mg/m3 | |
| Treated Filler | Trade | Malaysia OELs | TWA (proposed)(8 hours):10 | |
| | Secret | | mg/m3 | |

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer's Recommended Guidelines

Malaysia OELs: Malaysia. Occupational Safety and Health (Use and Standards of Exposure of Chemicals Hazardous to Health) Regulations

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Physical state | Liquid |
|---|-----------------------------------|
| Color | Silver-Gray |
| Odor | Very Slight Acrylic |
| Odor threshold | No Data Available |
| pH | No Data Available |
| Melting point/Freezing point | No Data Available |
| Boiling point/Initial boiling point/Boiling range | 35 °C |
| Flash Point | 103.9 °C [Test Method:Closed Cup] |
| Evaporation rate | No Data Available |
| Flammability | Not Applicable |
| | |

| Flammable Limits(LEL) | No Data Available |
|---|---|
| Flammable Limits(UEL) | No Data Available |
| Vapor Pressure | 666.6 Pa |
| Relative Vapor Density | No Data Available |
| Density | 1.132 g/ml |
| Relative Density | 1.132 [<i>Ref Std</i> :WATER=1] |
| Water solubility | No Data Available |
| Solubility- non-water | No Data Available |
| Partition coefficient: n-octanol/ water | No Data Available |
| Autoignition temperature | No Data Available |
| Decomposition temperature | No Data Available |
| Kinematic Viscosity | 441,696 mm2/sec |
| Volatile Organic Compounds | 0.1 % weight [Details: calculated per CARB title 2] |
| Volatile Organic Compounds | 1 g/l [Details:calculated per SCAQMD 443.1] |
| Percent volatile | 0.1 % weight |
| VOC Less H2O & Exempt Solvents | 1 g/l [Details:calculated per SCAQMD 443.1] |
| Molecular weight | No Data Available |

| Particle Characteristics | Not Applicable |
|--------------------------|----------------|
| | |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Strong acids

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|---|---------------------------------------|---------|---|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation- Dust/Mist(4 hr) | | No data available; calculated ATE >5 - =12.5 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| 4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer | Dermal | Rat | LD50 > 1,600 mg/kg |
| 4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer | Ingestion | Rat | LD50 > 1,000 mg/kg |
| Treated Filler | Dermal | Rat | LD50 > 2,000 mg/kg |
| Treated Filler | Inhalation- Dust/Mist (4 hours) | Rat | LC50 3 mg/l |
| Treated Filler | Ingestion | Rat | LD50 6,450 mg/kg |
| Benzoic Acid, C9-C11-Branched Alkyl Esters | Dermal | Rabbit | LD50 > 2,000 mg/kg |
| Benzoic Acid, C9-C11-Branched Alkyl Esters | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 5.5 mg/l |
| Benzoic Acid, C9-C11-Branched Alkyl Esters | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Treated Inorganic Filler | Dermal | Rabbit | LD50 > 5,000 mg/kg |

| Treated Inorganic Filler | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
|--|---------------------------------------|------------------------------|------------------------------------|
| Treated Inorganic Filler | Ingestion | Rat | LD50 > 5,110 mg/kg |
| Inorganic Filler | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Inorganic Filler | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| Inorganic Filler | Ingestion | Rat | LD50 > 5,110 mg/kg |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Dermal | Rabbit | LD50 4,000 mg/kg |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Inhalation- Dust/Mist (4 hours) | Rat | LC50 > 5.3 mg/l |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Ingestion | Rat | LD50 7,010 mg/kg |
| 1,4-Bis[(2,3-Epoxypropoxy)Methyl]Cyclohexane | Ingestion | Rat | LD50 1,000 mg/kg |
| Phenolphthalein | Ingestion | Rat | LD50 > 10,500 mg/kg |
| Phenolphthalein | Dermal | similar health hazards | LD50 estimated to be > 5,000 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value | | |
|---|----------|---------------------------|--|--|
| 4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer | Rabbit | Mild irritant | | |
| Treated Filler | Rabbit | No significant irritation | | |
| Benzoic Acid, C9-C11-Branched Alkyl Esters | Rabbit | Minimal irritation | | |
| Treated Inorganic Filler | Rabbit | No significant irritation | | |
| Inorganic Filler | Rabbit | No significant irritation | | |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Rabbit | Mild irritant | | |
| 1,4-Bis[(2,3-Epoxypropoxy)Methyl]Cyclohexane | In vitro | Irritant | | |
| | data | | | |
| Phenolphthalein | In vitro | Irritant | | |
| | data | | | |

Serious Eye Damage/Irritation

| Name | Species | Value | | |
|---|----------|---------------------------|--|--|
| 4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer | Rabbit | Moderate irritant | | |
| Treated Filler | Rabbit | No significant irritation | | |
| Benzoic Acid, C9-C11-Branched Alkyl Esters | Rabbit | Mild irritant | | |
| Treated Inorganic Filler | Rabbit | No significant irritation | | |
| Inorganic Filler | Rabbit | No significant irritation | | |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Rabbit | Corrosive | | |
| 1,4-Bis[(2,3-Epoxypropoxy)Methyl]Cyclohexane | In vitro | No significant irritation | | |
| | data | | | |
| Phenolphthalein | In vitro | No significant irritation | | |
| | data | | | |

Sensitization:

Skin Sensitization

| Name | Species | Value |
|---|------------------------|----------------|
| 4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer | Human and animal | Sensitizing |
| Benzoic Acid, C9-C11-Branched Alkyl Esters | Guinea pig | Not classified |
| Treated Inorganic Filler | Human and animal | Not classified |
| Inorganic Filler | Human and | Not classified |

| | animal | |
|--|---------|----------------|
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Guinea | Not classified |
| | pig | |
| 1,4-Bis[(2,3-Epoxypropoxy)Methyl]Cyclohexane | similar | Sensitizing |
| | compoun | |
| | ds | |
| Phenolphthalein | Mouse | Not classified |

Respiratory Sensitization

| Name | Species | Value |
|---|---------|----------------|
| 4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer | Human | Not classified |

Germ Cell Mutagenicity

| Name | Route | Value | | |
|---|--|--|--|--|
| 4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer | In vivo | Not mutagenic | | |
| 4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer | In Vitro | Some positive data exist, but the data are not sufficient for classification | | |
| Benzoic Acid, C9-C11-Branched Alkyl Esters | In Vitro | Not mutagenic | | |
| Benzoic Acid, C9-C11-Branched Alkyl Esters | In vivo | Not mutagenic | | |
| Treated Inorganic Filler | In Vitro | Not mutagenic | | |
| Inorganic Filler | In Vitro | Not mutagenic | | |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | In Vitro | Some positive data exist, but the data are not sufficient for classification | | |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | In vivo Some positive data exist, but the data a sufficient for classification | | | |
| 1,4-Bis[(2,3-Epoxypropoxy)Methyl]Cyclohexane | In Vitro | Mutagenic; structurally related to germ cell mutagens | | |
| Phenolphthalein | In Vitro | Some positive data exist, but the data are not sufficient for classification | | |
| Phenolphthalein | In vivo | Mutagenic | | |

Carcinogenicity

| Name | Route | Species | Value |
|---|------------------|----------|--|
| 4,4'-Isopropylidenediphenol-Epichlorohydrin Polymer | Dermal | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Treated Inorganic Filler | Not Specified | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Inorganic Filler | Not Specified | Mouse | Some positive data exist, but the data are not sufficient for classification |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Dermal | Mouse | Not carcinogenic |
| Phenolphthalein | Ingestion | Multiple | Carcinogenic |
| | | animal | |
| | | species | |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|---|-----------|--|---------|------------------------|------------------------------|
| 4,4'-Isopropylidenediphenol- Epichlorohydrin Polymer | Ingestion | Not classified for female reproduction | Rat | NOAEL 750 mg/kg/day | 2 generation |
| 4,4'-Isopropylidenediphenol- Epichlorohydrin Polymer | Ingestion | Not classified for male reproduction | Rat | NOAEL 750 mg/kg/day | 2 generation |
| 4,4'-Isopropylidenediphenol- Epichlorohydrin Polymer | Dermal | Not classified for development | Rabbit | NOAEL 300 mg/kg/day | during organogenesis |
| 4,4'-Isopropylidenediphenol- Epichlorohydrin Polymer | Ingestion | Not classified for development | Rat | NOAEL 750 mg/kg/day | 2 generation |
| Treated Filler | Ingestion | Not classified for development | Rat | NOAEL 625 mg/kg/day | premating & during gestation |
| Benzoic Acid, C9-C11-Branched Alkyl Esters | Ingestion | Not classified for female reproduction | Rat | NOAEL 641 mg/kg/day | 2 generation |

| Benzoic Acid, C9-C11-Branched Alkyl Esters | Ingestion | Not classified for male reproduction | Rat | NOAEL 676 mg/kg/day | 2 generation |
|---|-----------|--|-------|-----------------------------|-------------------------|
| Benzoic Acid, C9-C11-Branched Alkyl Esters | Ingestion | Not classified for development | Rat | NOAEL 191 mg/kg/day | 2 generation |
| Treated Inorganic Filler | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Treated Inorganic Filler | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Treated Inorganic Filler | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesis |
| Inorganic Filler | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Inorganic Filler | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Inorganic Filler | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesis |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Ingestion | Not classified for female reproduction | Rat | NOAEL 1,000 mg/kg/day | 1 generation |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Ingestion | Not classified for male reproduction | Rat | NOAEL 1,000 mg/kg/day | 1 generation |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Ingestion | Not classified for development | Rat | NOAEL 3,000 mg/kg/day | during organogenesis |
| Phenolphthalein | Ingestion | Toxic to female reproduction | Mouse | NOAEL 150 mg/kg/day | 1 generation |
| Phenolphthalein | Ingestion | Toxic to male reproduction | Mouse | NOAEL 150 mg/kg/day | 1 generation |
| Phenolphthalein | Ingestion | Toxic to development | Mouse | NOAEL 150 mg/kg/day | 1 generation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--|------------|------------------------|--|------------------------------|------------------------|----------------------|
| Treated Filler | Inhalation | respiratory system | Not classified | Rat | NOAEL 0.812 mg/l | 90 minutes |
| 1,4-Bis[(2,3- Epoxypropoxy)Methyl]Cyc lohexane | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| Phenolphthalein | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---|------------|--|----------------|---------|-----------------------------|-----------------------|
| 4,4'- Isopropylidenediphenol- Epichlorohydrin Polymer | Dermal | liver | Not classified | Rat | NOAEL 1,000 mg/kg/day | 2 years |
| 4,4'- Isopropylidenediphenol- Epichlorohydrin Polymer | Dermal | nervous system | Not classified | Rat | NOAEL 1,000 mg/kg/day | 13 weeks |
| 4,4'- Isopropylidenediphenol- Epichlorohydrin Polymer | Ingestion | auditory system heart endocrine system hematopoietic system liver eyes kidney and/or bladder | Not classified | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Treated Filler | Inhalation | respiratory system | Not classified | Human | NOAEL Not available | occupational exposure |

| Benzoic Acid, C9-C11- Branched Alkyl Esters | Ingestion | heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system | Not classified | Rat | NOAEL 619 mg/kg/day | 91 days |
|--|------------|--|----------------|-------|-----------------------------|-----------------------|
| Treated Inorganic Filler | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Inorganic Filler | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| 3-(Trimethoxysilyl)Propyl Glycidyl Ether | Ingestion | heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system | Not classified | Rat | NOAEL 1,000 mg/kg/day | 28 days |
| Phenolphthalein | Ingestion | liver heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system nervous system kidney and/or bladder respiratory system | Not classified | Rat | NOAEL 3,500 mg/kg/day | 13 weeks |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labeling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Acute aquatic hazard:

GHS Acute 2: Toxic to aquatic life.

Chronic aquatic hazard:

GHS Chronic 2: Toxic to aquatic life with long lasting effects

No product test data available

| Material | Cas # | Organism | Type | Exposure | Test Endpoint | Test Result |
|-----------------------------------|--------------|------------------|---------------------|-----------|-------------------|-------------------------|
| 4,4'- | 25068-38-6 | Activated sludge | Estimated | 3 hours | IC50 | >100 mg/l |
| Isopropylidenediph | | | | | | |
| enol- Epichlorohydrin | | | | | | |
| Polymer | | | | | | |
| 4,4'- | 25068-38-6 | Green algae | Estimated | 72 hours | EC50 | >11 mg/l |
| Isopropylidenediph | | areen uigue | | , 2 nouis | 1200 | 11 |
| enol- | | | | | | |
| Epichlorohydrin | | | | | | |
| Polymer | 25060.20.6 | D:1 T | F (1 | 061 | 1.050 | |
| 4,4'- Isopropylidenediph | 25068-38-6 | Rainbow Trout | Estimated | 96 hours | LC50 | 2 mg/l |
| enol- | | | | | | |
| Epichlorohydrin | | | | | | |
| Polymer | | | | | | |
| 4,4'- | 25068-38-6 | Water flea | Estimated | 48 hours | EC50 | 1.8 mg/l |
| Isopropylidenediph enol- | | | | | | |
| Epichlorohydrin | | | | | | |
| Polymer | | | | | | |
| 4,4'- | 25068-38-6 | Green algae | Estimated | 72 hours | NOEC | 4.2 mg/l |
| Isopropylidenediph | | | | | | |
| enol- | | | | | | |
| Epichlorohydrin Polymer | | | | | | |
| 4,4'- | 25068-38-6 | Water flea | Estimated | 21 days | NOEC | 0.3 mg/l |
| Isopropylidenediph | 23000 30 0 | , ater nea | Estimated | 21 days | I TOLE | 0.5 mg/1 |
| enol- | | | | | | |
| Epichlorohydrin | | | | | | |
| Polymer | Trade Secret | N/A | Data not available | N/A | N/A | N/A |
| Synthetic Rubber | Trade Secret | IN/A | or insufficient for | N/A | IN/A | IN/A |
| | | | classification | | | |
| 1,4-Bis[(2,3- | 14228-73-0 | Bacteria | Estimated | 18 hours | EC50 | 10,264 mg/l |
| Epoxypropoxy)Met | | | | | | |
| hyl]Cyclohexane | 114220 72 0 | DT/A | F : (1 | 72.1 | EC50 | 120 // |
| 1,4-Bis[(2,3- Epoxypropoxy)Met | 14228-73-0 | N/A | Experimental | 72 hours | EC50 | 38 mg/l |
| hyl]Cyclohexane | | | | | | |
| 1,4-Bis[(2,3- | 14228-73-0 | Water flea | Experimental | 48 hours | EC50 | 71 mg/l |
| Epoxypropoxy)Met | | | 1 | | | |
| hyl]Cyclohexane | | | <u> </u> | | | |
| 1,4-Bis[(2,3- | 14228-73-0 | N/A | Experimental | 72 hours | EC10 | 18 mg/l |
| Epoxypropoxy)Met hyl]Cyclohexane | | | | | | |
| Benzoic Acid, C9- | 131298-44-7 | Green algae | Experimental | 96 hours | No tox obs at lmt | >100 mg/l |
| C11-Branched | | | F | | of water sol | |
| Alkyl Esters | | | | | | |
| Benzoic Acid, C9- | 131298-44-7 | Rainbow Trout | Experimental | 96 hours | No tox obs at lmt | >100 mg/l |
| C11-Branched Alkyl Esters | | | | | of water sol | |
| Benzoic Acid, C9- | 131298-44-7 | Water flea | Experimental | 48 hours | No tox obs at lmt | >100 mg/l |
| C11-Branched | | | | | of water sol | |
| Alkyl Esters | | | | | | |
| Benzoic Acid, C9- | 131298-44-7 | Fathead Minnow | Experimental | 33 days | No tox obs at lmt | >100 mg/l |
| C11-Branched | | | | | of water sol | |
| Alkyl Esters Benzoic Acid, C9- | 131298-44-7 | Green algae | Experimental | 96 hours | No tox obs at lmt | >100 mg/l |
| C11-Branched | 131270-44-7 | Orcen aigae | Lapermientai | 70 Hours | of water sol | 100 mg/1 |
| Alkyl Esters | | | | | | |
| Benzoic Acid, C9- | 131298-44-7 | Midge | Experimental | 28 days | NOEC | 64.7 mg/kg (Dry Weight) |
| C11-Branched | | | | | | |
| Alkyl Esters | 121200 44 5 | XX | l n | 21.1 | | . 100 // |
| Benzoic Acid, C9- | 131298-44-7 | Water flea | Experimental | 21 days | No tox obs at lmt | >100 mg/l |
| C11-Branched Alkyl Esters | | | | | of water sol | |
| | ı | 1 | 1 | 1 | 1 | 1 |

| Benzoic Acid, C9- C11-Branched Alkyl Esters | 131298-44-7 | Activated sludge | Experimental | 3 hours | EC50 | >100 mg/l |
|---|--------------|------------------|---|----------|-------|------------|
| Inorganic Filler | Trade Secret | N/A | Data not available or insufficient for classification | N/A | N/A | N/A |
| Treated Filler | Trade Secret | Green algae | Estimated | 72 hours | EC50 | >100 mg/l |
| Treated Filler | Trade Secret | Rainbow Trout | Estimated | 96 hours | LC50 | >100 mg/l |
| Treated Filler | Trade Secret | Water flea | Estimated | 48 hours | EC50 | >100 mg/l |
| Treated Filler | Trade Secret | Green algae | Estimated | 72 hours | EC10 | >100 mg/l |
| Treated Inorganic Filler | Trade Secret | N/A | Data not available or insufficient for classification | N/A | N/A | N/A |
| 3- (Trimethoxysilyl)P ropyl Glycidyl Ether | 2530-83-8 | Common Carp | Experimental | 96 hours | LC50 | 55 mg/l |
| 3- (Trimethoxysilyl)P ropyl Glycidyl Ether | 2530-83-8 | Green algae | Experimental | 96 hours | ErC50 | 350 mg/l |
| 3- (Trimethoxysilyl)P ropyl Glycidyl Ether | 2530-83-8 | Invertebrate | Experimental | 48 hours | LC50 | 324 mg/l |
| 3- (Trimethoxysilyl)P ropyl Glycidyl Ether | 2530-83-8 | Green algae | Experimental | 96 hours | NOEC | 130 mg/l |
| 3- (Trimethoxysilyl)P ropyl Glycidyl Ether | 2530-83-8 | Water flea | Experimental | 21 days | NOEC | 100 mg/l |
| 3- (Trimethoxysilyl)P ropyl Glycidyl Ether | 2530-83-8 | Activated sludge | Experimental | 3 hours | EC50 | >100 mg/l |
| Phenolphthalein | 77-09-8 | Green algae | Experimental | 72 hours | ErC50 | >3.33 mg/l |
| Phenolphthalein | 77-09-8 | Water flea | Experimental | 48 hours | EC50 | 6.72 mg/l |
| Phenolphthalein | 77-09-8 | Green algae | Experimental | 72 hours | ErC10 | 0.74 mg/l |

12.2. Persistence and degradability

| Material | CAS No. | Test Type | Duration | Study Type | Test Result | Protocol |
|--|--------------|-----------------------------------|----------|-----------------------------|--|-----------------------------------|
| 4,4'- | 25068-38-6 | Estimated | 28 days | Biological Oxygen | 5 %BOD/COD | OECD 301F - Manometric |
| Isopropylidenediph enol- Epichlorohydrin Polymer | | Biodegradation | | Demand | | Respiro |
| 4,4'- Isopropylidenediph enol- Epichlorohydrin Polymer | 25068-38-6 | Estimated Hydrolysis | | Hydrolytic half-life | 117 hours (t 1/2) | |
| Synthetic Rubber | Trade Secret | Data not availbl- insufficient | N/A | N/A | N/A | N/A |
| 1,4-Bis[(2,3- Epoxypropoxy)Met hyl]Cyclohexane | 14228-73-0 | Experimental Biodegradation | 28 days | Carbon dioxide evolution | 1.3 %CO2 evolution/THCO2 evolution | OECD 301B - Mod. Sturm or CO2 |
| Benzoic Acid, C9- C11-Branched Alkyl Esters | 131298-44-7 | Experimental Biodegradation | 28 days | Biological Oxygen Demand | 77.7 %BOD/ThOD | OECD 301F - Manometric Respiro |
| Inorganic Filler | Trade Secret | Data not availbl- | N/A | N/A | N/A | N/A |

| | | insufficient | | | | |
|---|--------------|-----------------------------------|---------|-----------------------------|--------------------|-----------------------------------|
| Treated Filler | Trade Secret | Data not availbl- insufficient | N/A | N/A | N/A | N/A |
| Treated Inorganic Filler | Trade Secret | Data not availbl- insufficient | N/A | N/A | N/A | N/A |
| 3- (Trimethoxysilyl)P ropyl Glycidyl Ether | 2530-83-8 | Experimental Biodegradation | 28 days | | 37 %removal of DOC | EC C.4.A. DOC Die-Away Test |
| 3- (Trimethoxysilyl)P ropyl Glycidyl Ether | 2530-83-8 | Experimental Hydrolysis | | Hydrolytic half-life (pH 7) | \ / | OECD 111 Hydrolysis func of pH |
| Phenolphthalein | 77-09-8 | Experimental Biodegradation | 28 days | Biological Oxygen Demand | 76 %BOD/ThOD | OECD 301F - Manometric Respiro |

12.3. Bioaccumulative potential

| Material | CAS No. | Test Type | Duration | Study Type | Test Result | Protocol |
|--|--------------|---|----------|--------------------------------------|-------------|------------------------------|
| 4,4'- Isopropylidenediph enol- Epichlorohydrin Polymer | 25068-38-6 | Estimated Bioconcentration | | Log of Octanol/H2O part. coeff | 3.242 | |
| Synthetic Rubber | Trade Secret | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| 1,4-Bis[(2,3- Epoxypropoxy)Met hyl]Cyclohexane | 14228-73-0 | Experimental Bioconcentration | | Log of Octanol/H2O part. coeff | 2.05 | |
| Benzoic Acid, C9- C11-Branched Alkyl Esters | 131298-44-7 | Modeled Bioconcentration | | Bioaccumulation Factor | 288 | Catalogic™ |
| Benzoic Acid, C9- C11-Branched Alkyl Esters | 131298-44-7 | Experimental Bioconcentration | | Log of Octanol/H2O part. coeff | 4.61 | EC A.8 Partition Coefficient |
| Inorganic Filler | Trade Secret | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| Treated Filler | Trade Secret | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| Treated Inorganic Filler | Trade Secret | Data not available or insufficient for classification | N/A | N/A | N/A | N/A |
| 3- (Trimethoxysilyl)P ropyl Glycidyl Ether | 2530-83-8 | Experimental Bioconcentration | | Log of Octanol/H2O part. coeff | 0.5 | Episuite TM |
| Phenolphthalein | 77-09-8 | Experimental Bioconcentration | | Log of Octanol/H2O part. coeff | 0.9 | EC A.8 Partition Coefficient |

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available

SECTION 13: Disposal considerations

13.1. Disposal methods

According to the Environmental Quality (Scheduled Wastes) Regulations 2005, scheduled waste has to be sent to a prescribed

premise for recycling, treatment or disposal. Please approach Kualiti Alam for proper schedule waste classification and disposal.

SECTION 14: Transport Information

Marine Transport (IMDG)

UN Number: UN3082

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Technical Name: None assigned.

Hazard Class/Division:9

Subsidiary Risk: None assigned.

Packing Group:III

Limited Quantity: None assigned. Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Air Transport (IATA)

UN Number:UN3082

Proper Shipping Name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Technical Name: None assigned.

Hazard Class/Division:9

Subsidiary Risk: None assigned.

Packing Group:III

Limited Quantity: None assigned. Marine Pollutant: None assigned.

Marine Pollutant Technical Name: None assigned.

Other Dangerous Goods Descriptions:

None assigned.

Transportation classifications are provided as a customer service. As for shipping, YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling or marking requirements. The above information is only for reference. If you are shipping by air or ocean, YOU are advised to check & meet applicable regulatory requirements.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Industrial Safety and Health Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product

complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

DISCLAIMER: The information in this Safety Data Sheet (SDS) is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this SDS or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own evaluation to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into Malaysia, you are responsible for all applicable regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration/notification.

3M Malaysia SDSs are available at www.3M.com.my