

# Safety Data Sheet

Copyright,2024, 3M Company.All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	06-3267-9	Version number:	7.00
Issue Date:	10/12/2024	Supersedes date:	18/08/2021

This Safety Data Sheet has been prepared in accordance with the Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice (Safe Work Australia, December 2011)

# **SECTION 1: Identification**

### 1.1. Product identifier

3M<sup>™</sup> Marine Metal Restorer and Polish, 09019

**Product Identification Numbers** 60-9800-3552-5

### 1.2. Recommended use and restrictions on use

### Recommended use

Marine metal polish, Marine

For Industrial or Professional use only.

### 1.3. Supplier's details

Address:	3M Australia - Building A, 1 Rivett Road, North Ryde NSW 2113
Telephone:	136 136
E Mail:	productinfo.au@mmm.com
Website:	www.3m.com.au

**1.4. Emergency telephone number** EMERGENCY: 1800 097 146 (Australia only)

## **SECTION 2: Hazard identification**

This product is classified as a hazardous chemical according to the Model Work Health and Safety Regulations, 2011, in accordance with applicable State and Territory legislation.

Refer to Section 14 of this Safety Data Sheets for product Dangerous Goods Classification.

### 2.1. Classification of the substance or mixture

Skin Corrosion/Irritation: Category 2. Serious Eye Damage/Irritation: Category 2.

### 2.2. Label elements

The label elements below were prepared in accordance with the Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals (Safe Work Australia, December 2011). This information may be different from the actual product

label.

### Signal word Warning

Symbols Exclamation mark |

### **Pictograms**



Hazard statements H315 H319

Causes skin irritation. Causes serious eye irritation.

<b>Precautionary statements</b> <b>General:</b> P101 P102	If medical advice is needed, have product container or label at hand. Keep out of reach of children.
<b>Prevention:</b> P264	Wash thoroughly after handling.
Response:	
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P337 + P313	IF eye irritation persists: Get medical advice/attention.
P362 + P364	

## 2.3. Other assigned/identified product hazards

Aspiration classification does not apply due to the viscosity of the product.

2.4. Other hazards which do not result in classification Harmful to aquatic life.

# **SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	CAS Nbr	% by Weight
Aluminum Oxide (non-fibrous)	1344-28-1	30 - 60
Water	7732-18-5	30 - 60
Hydrotreated Light Petroleum Distillates	64742-47-8	10 - 30
Oleic Acid	112-80-1	5 - 15
Ammonia, aqueous solution	1336-21-6	< 3
Amides	Trade Secret	< 1

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

### Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

### Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

### If swallowed

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

## 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide. Carbon dioxide. Condition During combustion. During combustion.

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### **6.2.** Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store away from oxidising agents. Store away from areas where product may come into contact with food or pharmaceuticals.

# **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Ammonia released from ammonium hydroxide/aqueous ammonia solutions	1336-21-6	ACGIH	TWA:25 ppm;STEL:35 ppm	
Ammonia released from ammonium hydroxide/aqueous ammonia solutions	1336-21-6	Australia OELs	TWA(8 hours):17 mg/m3(25 ppm);STEL(15 minutes):24 mg/m3(35 ppm)	
Aluminum Oxide (non-fibrous)	1344-28-1	Australia OELs	TWA(Inspirable dust)(8 hours):10 mg/m3	
Aluminum, insoluble compounds	1344-28-1	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcin
Jet Fuels (Non-Aerosol), as Total Hydrocarbon Vapour	64742-47-8	ACGIH	TWA(as total hydrocarbon vapour, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapour, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

Australia OELs : Australia. Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Sen: Sensitiser

Sk: Absorption through the skin may be a significant source of exposure.

### 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

### **8.2.2.** Personal protective equipment (PPE)

### **Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Indirect vented goggles.

Select and use eye protection in accordance with AS/NZS 1336. Eye protection should comply with the performance specifications of AS/NZS 1337.

### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Fluoroelastomer

Select and use gloves according to AS/NZ 2161.

### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer. Select and use respirators according to AS/NZS 1715. Respirators should comply with AS/NZS 1716 performance specifications. For information about respirators, call 3M on 1800 024 464.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

mormation on basic physical and chemical properties		
Physical state	Solid.	
Specific Physical Form:	Paste	
Colour	Pink	
Odour	Slight Ammoniacal	
Odour threshold	No data available.	
рН	Approximately 9.4	
Melting point/Freezing point	No data available.	
Boiling point/Initial boiling point/Boiling range	70 °C	
Flash point	>=93.3 °C [ <i>Test Method</i> :Closed Cup]	
Evaporation rate	>=1 [ <i>Ref Std</i> :WATER=1]	
Flammability	Not applicable.	
Flammable Limits(LEL)	No data available.	
Flammable Limits(UEL)	No data available.	
Vapour pressure	No data available.	
Relative Vapor Density	No data available.	
Density	1.09 g/ml	
Relative density	1.09 [ <i>Ref Std</i> :WATER=1]	
Water solubility	Moderate	
Solubility- non-water	No data available.	
Partition coefficient: n-octanol/water	No data available.	
Autoignition temperature	No data available.	
Decomposition temperature	No data available.	
Kinematic Viscosity	No data available.	
Volatile organic compounds (VOC)	197 g/l [Test Method:calculated SCAQMD rule 443.1]	

Volatile organic compounds (VOC)	18 % weight [Test Method:calculated per CARB title 2]	
Percent volatile	58 % weight	
VOC less H2O & exempt solvents	349 g/l [Test Method:calculated SCAQMD rule 443.1]	
Molecular weight	No data available.	

**Particle Characteristics** 

Not applicable.

# **SECTION 10: Stability and reactivity**

### **10.1 Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

## 10.2 Chemical stability

Stable.

**10.3. Conditions to avoid** None known.

### 10.4. Possibility of hazardous reactions

Hazardous polymerisation will not occur.

### **10.5 Incompatible materials**

Strong oxidising agents.

### 10.6 Hazardous decomposition products

Substance None known. **Condition** 

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

**11.1 Information on Toxicological effects** 

### Signs and Symptoms of Exposure

### Based on test data and/or information on the components, this material may produce the following health effects:

## Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

### Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

### Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

### Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Aluminum Oxide (non-fibrous)	Dermal		LD50 estimated to be $> 5,000 \text{ mg/kg}$
Aluminum Oxide (non-fibrous)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminum Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrotreated Light Petroleum Distillates	Ingestion	Rat	LD50 > 15,000 mg/kg
Hydrotreated Light Petroleum Distillates	Dermal	similar compounds	LD50 > 5,000 mg/kg
Oleic Acid	Dermal	Guinea pig	LD50 > 3,000 mg/kg
Oleic Acid	Ingestion	Rat	LD50 57,000 mg/kg
Ammonia, aqueous solution	Ingestion	Rat	LD50 350 mg/kg

ATE = acute toxicity estimate

### **Skin Corrosion/Irritation**

Name	Species	Value
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Hydrotreated Light Petroleum Distillates	similar compounds	Mild irritant
Oleic Acid	Rabbit	Minimal irritation
Ammonia, aqueous solution	Rabbit	Corrosive

### Serious Eye Damage/Irritation

Name	Species	Value
Aluminum Oxide (non-fibrous)	Rabbit	No significant irritation
Hydrotreated Light Petroleum Distillates	similar compounds	No significant irritation
Oleic Acid	Rabbit	Mild irritant
Ammonia, aqueous solution	Rabbit	Corrosive

## **Skin Sensitisation**

Name	Species	Value
Hydrotreated Light Petroleum Distillates	similar compounds	Not classified

### **Respiratory Sensitisation**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### **Germ Cell Mutagenicity**

Name	Route	Value
Aluminum Oxide (non-fibrous)	In Vitro	Not mutagenic
Hydrotreated Light Petroleum Distillates	In Vitro	Not mutagenic
Oleic Acid	In Vitro	Some positive data exist, but the data are not

	sufficient for classification

## Carcinogenicity

Name	Route	Species	Value
Aluminum Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
Oleic Acid	Dermal	Mouse	Not carcinogenic
Oleic Acid	Ingestion	Rat	Not carcinogenic
Oleic Acid	Not specified.	Multiple animal	Not carcinogenic
		species	

## **Reproductive Toxicity**

## **Reproductive and/or Developmental Effects**

For the component/components, either no data are currently available or the data are not sufficient for classification.

## Target Organ(s)

## Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Hydrotreated Light Petroleum Distillates	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Ammonia, aqueous solution	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL not available	

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Aluminum Oxide (non- fibrous)	Inhalation	pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Aluminum Oxide (non- fibrous)	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Hydrotreated Light Petroleum Distillates	Inhalation	liver	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Hydrotreated Light Petroleum Distillates	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.5 mg/l	13 weeks
Hydrotreated Light Petroleum Distillates	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6 mg/l	13 weeks
Hydrotreated Light Petroleum Distillates	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks
Hydrotreated Light Petroleum	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 100 mg/kg/day	13 weeks

Distillates						
Hydrotreated	Ingestion	hematopoietic	Not classified	Rat	NOAEL 1,000	13 weeks
Light		system   eyes			mg/kg/day	
Petroleum						
Distillates						
Oleic Acid	Ingestion	liver   immune	Not classified	Rat	NOAEL 2,250	108 weeks
	Ū	system			mg/kg/day	
Oleic Acid	Ingestion	hematopoietic	Not classified	Rat	NOAEL 2,550	108 weeks
	_	system			mg/kg/day	

### **Aspiration Hazard**

Name	Value
Hydrotreated Light Petroleum Distillates	Aspiration hazard

### **Exposure Levels**

Refer Section 8.1 Control Parameters of this Safety Data Sheet.

### **Interactive Effects**

Not Determined

# **SECTION 12: Ecological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

### 12.1. Toxicity

### Acute aquatic hazard:

GHS Acute 3: Harmful to aquatic life.

### Chronic aquatic hazard:

Not chronically toxic to aquatic life by GHS criteria.

No product test data available.

Material	CAS Number	Organism	Туре	Exposure	Test endpoint	Test result
Aluminum Oxide (non-fibrous)	1344-28-1	N/A	Experimental	96 hours	LC50	>100 mg/l
Aluminum Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l
Aluminum Oxide (non-fibrous)	1344-28-1	Water flea	Experimental	48 hours	LC50	>100 mg/l
Aluminum Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Green algae	Experimental	72 hours	EL50	>1,000 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Rainbow trout	Experimental	96 hours	LL50	>1,000 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
Hydrotreated Light Petroleum Distillates	64742-47-8	Green algae	Experimental	72 hours	NOEL	1,000 mg/l
Oleic Acid	112-80-1	N/A	Data not available	N/A	N/A	N/A

			or insufficient for classification			
Ammonia, aqueous solution	1336-21-6	Invertebrate	Estimated	48 hours	EC50	21 mg/l
Ammonia, aqueous solution	1336-21-6	Rainbow trout	Estimated	96 hours	LC50	1.8 mg/l
Ammonia, aqueous solution	1336-21-6	Water flea	Estimated	48 hours	LC50	7.36 mg/l
Ammonia, aqueous solution	1336-21-6	Rainbow trout	Estimated	73 days	NOEC	0.0278 mg/l
Ammonia, aqueous solution	1336-21-6	Water flea	Estimated	21 days	NOEC	1.1 mg/l
Amides	Trade Secret	Activated sludge	Experimental	3 hours	NOEC	>100 mg/l
Amides	Trade Secret	Diatom	Experimental	72 hours	EC50	>100 mg/l
Amides	Trade Secret	Rainbow trout	Experimental	96 hours	LC50	2.9 mg/l
Amides	Trade Secret	Water flea	Experimental	48 hours	EC50	3.8 mg/l

## 12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Aluminum Oxide (non-fibrous)	1344-28-1	Data not available- insufficient	N/A	N/A	N/A	N/A
Hydrotreated Light Petroleum Distillates	64742-47-8	Experimental Biodegradation	28 days	BOD	69 %BOD/ThOD (< 10 day window)	OECD 301F - Manometric respirometry
Oleic Acid	112-80-1	Experimental Biodegradation	28 days	BOD	78 %BOD/ThOD	OECD 301C - MITI test (I)
Ammonia, aqueous solution	1336-21-6	Analogous Compound Soil Metabolism Aerobic		Half-life (t 1/2)	6 hours (t 1/2)	
Amides	Trade Secret	Experimental Biodegradation	28 days	CO2 evolution	96 %CO2 evolution/THCO2 evolution	OECD 301B - Modified sturm or CO2

## 12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Aluminum Oxide (non-fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrotreated Light Petroleum Distillates	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Oleic Acid	112-80-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Ammonia, aqueous solution	1336-21-6	Analogous Compound Bioconcentration		Log Kow	-1.14	OECD 107 log Kow shke flsk mtd
Amides	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

## 12.4. Mobility in soil

Please contact manufacturer for more details

### 12.5 Other adverse effects

No information available.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

# **SECTION 14: Transport Information**

Australian Dangerous Goods Code (ADG) - Road/Rail Transport UN No.: Not applicable. Proper shipping name: Not applicable. Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable.

Hazchem Code: Not applicable IERG: Not applicable.

### International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.
Proper shipping name: Not applicable.
Class/Division: Not applicable.
Sub Risk: Not applicable.
Packing Group: Not applicable.

### International Maritime Dangerous Goods Code (IMDG)- Marine Transport

UN No.: Not applicable. Proper shipping name: Not applicable. Class/Division: Not applicable. Sub Risk: Not applicable. Packing Group: Not applicable. Marine Pollutant: Not applicable.

# **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### Australian Inventory Status:

All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC). Conditions may apply prior to introduction for direct importers of this product, Please contact 3M Australia on 136 136 for further details.

**Poison Schedule:** This product is intended for Industrial or Professional Use only and therefore is not packaged and labelled in accordance with the requirements of the Standard for the Uniform Scheduling of Medicines and Poisons.

# **SECTION 16: Other information**

### **Revision information:**

Complete document review.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our

knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Safety Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

Greenguard ® is a United States based program. The 'Low VOC' reference related to United States Federal and State regulations exemptions for some solvents.

### 3M Australia SDSs are available at www.3m.com.au