



Safety Data Sheet

Copyright, 2025, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	26-9520-3	Version Number:	6.10
Issue Date:	12/18/25	Supersedes Date:	11/22/24

SECTION 1: Identification

1.1. Product identifier

3M™ Heavy Duty 20 Spray Adhesive

Product Identification Numbers

62-4915-4920-0, 62-4915-4921-8, 62-4915-4925-9, 62-4915-4930-9
7000028597, 7000121425, 7100179437, 7100179439

1.2. Recommended use and restrictions on use

Recommended use

Adhesive aerosol, Industrial Use

1.3. Supplier's details

MANUFACTURER:	3M
DIVISION:	Industrial Adhesives and Tapes Division
ADDRESS:	3M Center, St. Paul, MN 55144-1000, USA
Telephone:	1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Aerosol Category 1

Serious Eye Damage/Irritation: Category 2B.

Carcinogenicity: Category 2.

Reproductive Toxicity: Category 1B.

Specific Target Organ Toxicity (single exposure): Category 1.

Specific Target Organ Toxicity (repeated exposure): Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

Simple Asphyxiants: Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Flame | Exclamation mark | Health Hazard |

Pictograms**Hazard Statements**

Extremely flammable aerosol.

Pressurized container: may burst if heated.

Causes eye irritation.

Suspected of causing cancer.

May damage fertility or the unborn child.

May cause drowsiness or dizziness.

May cause respiratory irritation.

May displace oxygen and cause rapid suffocation.

Causes damage to organs: cardiovascular system.

Causes damage to organs through prolonged or repeated exposure: nervous system.

Precautionary statements**General:**

Keep out of reach of children.

Prevention:

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Do not breathe vapors.

Wash exposed skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and if needed, respiratory protection (see SDS Section 8).

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Call a POISON CENTER or doctor.

Get medical attention if you feel unwell.

If eye irritation persists: Get medical advice.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C).

Disposal:

Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

Notes to Physician:

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

Supplemental Information:

Intentional concentration and inhalation may be harmful or fatal.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
Methyl Acetate	79-20-9	15 - 40 Trade Secret *
Dimethyl Ether	115-10-6	10 - 30 Trade Secret *
Hexane	110-54-3	10 - 30 Trade Secret *
Non-hazardous Components (NJTS Reg. No. 4499600-6761)	Trade Secret*	15 - 30
Isobutane	75-28-5	5 - 10 Trade Secret *
Propane	74-98-6	3 - 7 Trade Secret *
Toluene	108-88-3	< 1
Talc	14807-96-6	< 0.2

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. Get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details. Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u>	<u>Condition</u>
Aldehydes	During Combustion
Hydrocarbons	During Combustion
Formaldehyde	During Combustion
Methane	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Ketones	During Combustion
Toxic Vapor, Gas, Particulate	During Combustion

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid

etc.) Use personal protective equipment (gloves, respirators, etc.) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcin, Ototoxicant
Toluene	108-88-3	OSHA	TWA:200 ppm;CEIL:300 ppm	
Hexane	110-54-3	ACGIH	TWA:50 ppm	Danger of cutaneous absorption
Hexane	110-54-3	OSHA	TWA:1800 mg/m ³ (500 ppm)	
Dimethyl Ether	115-10-6	AIHA	TWA:1880 mg/m ³ (1000 ppm)	
Silicates (less than 1% crystalline silica) talc (containing asbestos)	14807-96-6	OSHA	TWA - Use asbestos limits:	
Talc	14807-96-6	ACGIH	TWA(respirable fraction):2 mg/m ³	A4: Not class. as human carcin
Talc	14807-96-6	OSHA	TWA concentration(respirable):0.1 mg/m ³ (2.4 millions of particles/cu. ft.);TWA:20 millions of particles/cu. ft.	
Butane, all isomers	74-98-6	ACGIH	STEL:1000 ppm	
Propane	74-98-6	ACGIH	Limit value not established:	simple asphyxiant
Propane	74-98-6	OSHA	TWA:1800 mg/m ³ (1000 ppm)	
Butane, all isomers	75-28-5	ACGIH	STEL:1000 ppm	
Methyl Acetate	79-20-9	ACGIH	TWA:200 ppm;STEL:250 ppm	
Methyl Acetate	79-20-9	OSHA	TWA:610 mg/m ³ (200 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields
Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

For prolonged or repeated contact, gloves made from the following material(s) are recommended (breakthrough times are >4 hours): Polymer laminate

Any glove recommended for prolonged/repeated contact is also suitable for short-term/splash contact.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates
Half facepiece or full facepiece supplied-air respirator
Organic vapor cartridges may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Aerosol
Color	Colorless
Odor	Mild Solvent
Odor threshold	No Data Available
pH	No Data Available
Melting point/Freezing point	No Data Available
Boiling point/Initial boiling point/Boiling range	[Details: Aerosol]Not Applicable
Flash Point	-93.9 °C [Details:Propellant]
Evaporation rate	1.9 [Ref Std:ETHER=1]
Flammability	Flammable Aerosol: Category 1.
Flammable Limits(LEL)	No Data Available
Flammable Limits(UEL)	No Data Available
Vapor Pressure	No Data Available
Relative Vapor Density	2.97 [Ref Std:AIR=1]
Density	0.75 g/ml
Relative Density	0.73 - 0.77 [Ref Std:WATER=1]
Water solubility	Nil
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	No Data Available

Decomposition temperature	<i>Not Applicable</i>
Kinematic Viscosity	Approximately mm ² /sec
Volatile Organic Compounds	<=378 g/l [Test Method:calculated SCAQMD rule 443.1] [Details:Material VOC]
Volatile Organic Compounds	<=51.8 % [Test Method:calculated per CARB title 2]
Percent volatile	<i>No Data Available</i>
VOC Less H₂O & Exempt Solvents	<i>No Data Available</i>
Molecular weight	<i>No Data Available</i>

Particle Characteristics	<i>Not Applicable</i>
---------------------------------	-----------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal.

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Prolonged or repeated exposure may cause target organ effects:

Peripheral Neuropathy: Signs/symptoms may include tingling or numbness of the extremities, incoordination, weakness of the hands and feet, tremors and muscle atrophy.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Talc	14807-96-6	Grp. 2A: Probable human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Methyl Acetate	Dermal	Rat	LD50 > 2,000 mg/kg
Methyl Acetate	Inhalation-Vapor (4 hours)	Rat	LC50 > 49 mg/l
Methyl Acetate	Ingestion	Rat	LD50 > 5,000 mg/kg
Hexane	Dermal	Rabbit	LD50 > 2,000 mg/kg
Hexane	Inhalation-Vapor (4 hours)	Rat	LC50 170 mg/l
Hexane	Ingestion	Rat	LD50 > 28,700 mg/kg
Dimethyl Ether	Inhalation-Gas (4 hours)	Rat	LC50 164,000 ppm

Isobutane	Inhalation-Gas (4 hours)	Rat	LC50 276,000 ppm
Propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
Non-hazardous Components (NJTS Reg. No. 4499600-6761)	Dermal	Not available	LD50 > 2,000 mg/kg
Non-hazardous Components (NJTS Reg. No. 4499600-6761)	Ingestion	Not available	LD50 > 2,000 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Methyl Acetate	Rabbit	No significant irritation
Hexane	Human and animal	Mild irritant
Isobutane	Professional judgement	No significant irritation
Propane	Rabbit	Minimal irritation
Non-hazardous Components (NJTS Reg. No. 4499600-6761)	Professional judgement	No significant irritation
Toluene	Rabbit	Irritant
Talc	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Methyl Acetate	Rabbit	Moderate irritant
Hexane	Rabbit	Mild irritant
Isobutane	Professional judgement	No significant irritation
Propane	Rabbit	Mild irritant
Non-hazardous Components (NJTS Reg. No. 4499600-6761)	Professional judgement	No significant irritation
Toluene	Rabbit	Moderate irritant
Talc	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Methyl Acetate	Human	Not classified
Hexane	Human	Not classified
Non-hazardous Components (NJTS Reg. No. 4499600-6761)		Not classified
Toluene	Guinea pig	Not classified

Respiratory Sensitization

Name	Species	Value
Talc	Human	Not classified

Germ Cell Mutagenicity

Name	Route	Value
Methyl Acetate	In Vitro	Not mutagenic
Methyl Acetate	In vivo	Not mutagenic
Hexane	In Vitro	Not mutagenic
Hexane	In vivo	Not mutagenic
Dimethyl Ether	In Vitro	Not mutagenic
Dimethyl Ether	In vivo	Not mutagenic
Isobutane	In Vitro	Not mutagenic
Propane	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Hexane	Dermal	Mouse	Not carcinogenic
Hexane	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Dimethyl Ether	Inhalation	Rat	Not carcinogenic
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Talc	Dermal	Human	Some positive data exist, but the data are not sufficient for classification
Talc	Inhalation	Rat	Carcinogenic

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
Hexane	Ingestion	Not classified for development	Mouse	NOAEL 2,200 mg/kg/day	during organogenesis
Hexane	Inhalation	Not classified for development	Rat	NOAEL 0.7 mg/l	during gestation
Hexane	Ingestion	Toxic to male reproduction	Rat	NOAEL 1,140 mg/kg/day	90 days
Hexane	Inhalation	Toxic to male reproduction	Rat	LOAEL 3.52 mg/l	28 days
Dimethyl Ether	Inhalation	Not classified for development	Rat	NOAEL 40,000 ppm	during organogenesis
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600	during

				mg/kg	organogenesi s
--	--	--	--	-------	-------------------

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl Acetate	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
Methyl Acetate	Inhalation	blindness	Not classified		NOAEL Not available	
Methyl Acetate	Ingestion	central nervous system depression	May cause drowsiness or dizziness		NOAEL Not available	
Hexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	not available
Hexane	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL Not available	8 hours
Hexane	Inhalation	respiratory system	Not classified	Rat	NOAEL 24.6 mg/l	8 hours
Dimethyl Ether	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 10,000 ppm	30 minutes
Dimethyl Ether	Inhalation	cardiac sensitization	Some positive data exist, but the data are not sufficient for classification	Dog	NOAEL 100,000 ppm	5 minutes
Isobutane	Inhalation	cardiac sensitization	Causes damage to organs	Multiple animal species	NOAEL Not available	
Isobutane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Isobutane	Inhalation	respiratory irritation	Not classified	Mouse	NOAEL Not available	
Propane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Propane	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
Methyl Acetate	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	28 days
Methyl Acetate	Inhalation	endocrine system	Not classified	Rat	NOAEL 6.1 mg/l	28 days
Methyl Acetate	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 6.1 mg/l	28 days
Methyl Acetate	Inhalation	liver	Not classified	Rat	NOAEL 6.1	28 days

					mg/l	
Methyl Acetate	Inhalation	immune system	Not classified	Rat	NOAEL 6.1 mg/l	28 days
Methyl Acetate	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 6.1 mg/l	28 days
Hexane	Inhalation	peripheral nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Hexane	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Mouse	LOAEL 1.76 mg/l	13 weeks
Hexane	Inhalation	liver	Not classified	Rat	NOAEL Not available	6 months
Hexane	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 1.76 mg/l	6 months
Hexane	Inhalation	hematopoietic system	Not classified	Mouse	NOAEL 35.2 mg/l	13 weeks
Hexane	Inhalation	auditory system	Not classified	Human	NOAEL Not available	occupational exposure
Hexane	Inhalation	immune system	Not classified	Human	NOAEL Not available	occupational exposure
Hexane	Inhalation	eyes	Not classified	Human	NOAEL Not available	occupational exposure
Hexane	Inhalation	heart	Not classified	Rat	NOAEL 1.76 mg/l	6 months
Hexane	Inhalation	skin	Not classified	Rat	NOAEL 1.76 mg/l	6 months
Hexane	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.76 mg/l	6 months
Hexane	Ingestion	peripheral nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,140 mg/kg/day	90 days
Hexane	Ingestion	endocrine system	Not classified	Rat	NOAEL Not available	13 weeks
Hexane	Ingestion	hematopoietic system	Not classified	Rat	NOAEL Not available	13 weeks
Hexane	Ingestion	liver	Not classified	Rat	NOAEL Not available	13 weeks
Hexane	Ingestion	immune system	Not classified	Rat	NOAEL Not available	13 weeks
Hexane	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL Not available	13 weeks
Dimethyl Ether	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 25,000 ppm	2 years
Dimethyl Ether	Inhalation	liver	Not classified	Rat	NOAEL 20,000 ppm	30 weeks
Isobutane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 4,500 ppm	13 weeks
Toluene	Inhalation	auditory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	eyes	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	liver	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days

					available	
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
Talc	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL 18 mg/m ³	113 weeks
Talc	Inhalation	respiratory system	Not classified	Rat	NOAEL 18 mg/m ³	113 weeks

Aspiration Hazard

Name	Value
Hexane	Aspiration hazard
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and

handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Flammable (gases, aerosols, liquids, or solids)

Health Hazards

Carcinogenicity

Reproductive toxicity

Serious eye damage or eye irritation

Simple Asphyxiant

Specific target organ toxicity (single or repeated exposure)

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
Hexane	110-54-3	Trade Secret 10 - 30

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 2 **Flammability:** 4 **Instability:** 0 **Special Hazards:** None

Aerosol Storage Code: 3

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document Group: 26-9520-3 **Version Number:** 6.10
Issue Date: 12/18/25 **Supersedes Date:** 11/22/24

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com