



Safety Data Sheet

Copyright, 2026, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	09-5344-8	Version number:	2.00
Revision date:	04/06/2026	Supersedes date:	16/04/2008
Transportation version number:			

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006) as amended by Regulation (EU) 2020/878

IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

3M 08826, 08827 Polyurethane Protective Sealer Grey (kit)

Product Identification Numbers

KS-9990-1050-1 KS-9990-1051-9

7000095229 7000095230

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Address: 3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2
Telephone: +353 1 280 3555
E Mail: ner-productstewardship@mmm.com

Website: www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the MSDSs for components of this product are:

08-8587-1, 09-5258-0

TRANSPORTATION INFORMATION

Refer to section 14 of the kit components for transport information.

KIT LABEL**2.1. Classification of the substance or mixture**
CLP REGULATION (EC) No 1272/2008**CLASSIFICATION:**

Flammable Liquid, Category 3 - Flam. Liq. 3; H226
 Acute Toxicity, Category 4 - Acute Tox. 4; H332
 Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
 Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
 Respiratory Sensitization, Category 1 - Resp. Sens. 1; H334
 Skin Sensitization, Category 1 - Skin Sens. 1; H317
 Carcinogenicity, Category 2 - Carc. 2; H351
 Reproductive Toxicity, Category 2 - Repr. 2; H361d
 Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373
 Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H335
 Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements
CLP REGULATION (EC) No 1272/2008**SIGNAL WORD**

DANGER.

Symbols

GHS02 (Flame) | GHS07 (Exclamation mark) | GHS08 (Health Hazard) |

Pictograms**Contains:**

1-isopropyl-2,2-dimethyltrimethylene diisobutyrate; 2,2'-methylenediphenyl diisocyanate; o-(p-isocyanatobenzyl)phenyl isocyanate; maleic anhydride; 4,4'-methylenediphenyl diisocyanate; Polymethylene polyphenylene isocyanate.

HAZARD STATEMENTS:

H226	Flammable liquid and vapour.
H332	Harmful if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H361d	Suspected of damaging the unborn child.
H335	May cause respiratory irritation.

H373	May cause damage to organs through prolonged or repeated exposure: respiratory system.
------	--

H412	Harmful to aquatic life with long lasting effects.
------	--

PRECAUTIONARY STATEMENTS

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260E	Do not breathe vapour or spray.
P280E	Wear protective gloves.

Response:

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

Refer to Safety Data Sheet for component % unknown values (www.3M.com/msds).

Information required per Regulation (EU) 2020/1149 as regards diisocyanates:

As from 24 August 2023 adequate training is required before industrial or professional use. Further information can be found at feica.eu/Puinfo

EU VOC Directive (2004/42/EC) labelling: 2004/42/EC IIB(e)(840) 135g/l

Revision information:

No revision information



Safety Data Sheet

Copyright, 2026, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	09-5258-0	Version number:	1.01
Revision date:	04/06/2026	Supersedes date:	16/04/2008

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006) as amended by Regulation (EU) 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

3M 08826, 08827, Polyurethane Protective Sealer Gray Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive., Sealant

1.3. Details of the supplier of the safety data sheet

Address:	3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2
Telephone:	+353 1 280 3555
E Mail:	ner-productstewardship@mmm.com
Website:	www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

Aspiration hazard classification does not apply due to the kinematic viscosity of the product.

CLASSIFICATION:

Flammable Liquid, Category 3 - Flam. Liq. 3; H226

Reproductive Toxicity, Category 2 - Repr. 2; H361d

Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements**CLP REGULATION (EC) No 1272/2008****SIGNAL WORD**

WARNING.

Symbols

GHS02 (Flame) | GHS08 (Health Hazard) |

Pictograms**Ingredients:**

Ingredient	Identifier(s)	EC No.	% by Wt
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0	229-934-9	1 - 5

HAZARD STATEMENTS:

H226	Flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H412	Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS**Prevention:**

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280F	Wear respiratory protection.

Response:

P370 + P378	In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.
-------------	---

SUPPLEMENTAL INFORMATION:**Supplemental Hazard Statements:**

EUH208	Contains maleic anhydride. May produce an allergic reaction.
--------	--

44% of the mixture consists of components of unknown acute oral toxicity.

44% of the mixture consists of components of unknown acute dermal toxicity.

25% of the mixture consists of components of unknown acute inhalation toxicity.

Contains 25% of components with unknown hazards to the aquatic environment.

2.3. Other hazards

None known.

This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients**3.1. Substances**

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Limestone	(CAS-No.) 1317-65-3 (EC-No.) 215-279-6	15 - 40	Substance with a national occupational exposure limit
OXIDISED CASTOR OIL	(CAS-No.) 68187-84-8 (EC-No.) 269-128-4	10 - 30	Substance not classified as hazardous
Polyester polyol	None	10 - 20	Substance not classified as hazardous
Talc	(CAS-No.) 14807-96-6 (EC-No.) 238-877-9	7 - 13	Substance with a national occupational exposure limit
Hydrocarbons, C9, aromatics	(EC-No.) 918-668-5 (REACH-No.) 01-2119455851-35	3 - 7	EUH066 Aquatic Chronic 2, H411 Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 STOT SE 3, H335
Kaolin	(CAS-No.) 1332-58-7 (EC-No.) 310-194-1	3 - 7	Substance with a national occupational exposure limit
xylene	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (REACH-No.) 01-2119488216-32	5 - 7	Flam. Liq. 3, H226 Acute Tox. 4, H332 Acute Tox. 4, H312 Skin Irrit. 2, H315 Nota C Asp. Tox. 1, H304 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412
Triiron tetraoxide	(CAS-No.) 1317-61-9 (EC-No.) 215-277-5	< 7	Substance not classified as hazardous
Amine-Modified Hydrogenated Castor Oil	None	< 5	Substance not classified as hazardous
Bentonite	None	< 5	Substance not classified as hazardous
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	(CAS-No.) 6846-50-0 (EC-No.) 229-934-9 (REACH-No.) 01-2119451093-47	1 - 5	Aquatic Chronic 3, H412 Repr. 2, H361d
Iron hydroxide oxide yellow	(CAS-No.) 51274-00-1 (EC-No.) 257-098-5	< 3	Substance not classified as hazardous

Silicic acid, aluminum sodium salt	(EC-No.) 930-915-9	< 2	Substance not classified as hazardous
Castor oil	(CAS-No.) 8001-79-4 (EC-No.) 232-293-8	< 2	Substance not classified as hazardous
Titanium dioxide	(CAS-No.) 13463-67-7 (EC-No.) 236-675-5	< 1	Substance with a national occupational exposure limit
maleic anhydride	(CAS-No.) 108-31-6 (EC-No.) 203-571-6	< 0.1	EUH071 Acute Tox. 4, H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Resp. Sens. 1, H334 Skin Sens. 1A, H317 STOT RE 1, H372

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
maleic anhydride	(CAS-No.) 108-31-6 (EC-No.) 203-571-6	(C >= 0.001%) Skin Sens. 1A, H317

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide

Carbon dioxide.

Irritant vapours or gases.

Condition

During combustion.

During combustion.

During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS. Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (eg. gloves, respirators...) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapour accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidising agents.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	Identifier(s)	Agency	Limit type	Additional comments
maleic anhydride	108-31-6	Ireland OELs	TWA(inhalable fraction and vapour)(8 hours):0.01 ppm	Resp/Dermal sensitizer, Respiratory or dermal sens
Limestone	1317-65-3	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m ³ ;TWA(as respirable dust)(8 hours):4 mg/m ³	
xylene	1330-20-7	Ireland OELs	TWA(8 hours):221 mg/m ³ (50 ppm);STEL(15 minutes):442 mg/m ³ (100 ppm)	SKIN
Kaolin	1332-58-7	Ireland OELs	TWA(as respirable dust)(8 hours):2 mg/m ³	
Titanium dioxide	13463-67-7	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m ³ ;TWA(as respirable dust)(8 hours):4 mg/m ³	
Talc	14807-96-6	Ireland OELs	TWA(Total inhalable dust)(8 hours):10 mg/m ³ ;TWA(as respirable dust)(8 hours):0.8 mg/m ³	

Ireland OELs : Ireland. OELs

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from Indust.

Inspect./Ministry (IE)

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety glasses with side shields.

Applicable Norms/Standards

Use eye protection conforming to EN 16321

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

Applicable Norms/Standards

Use gloves tested to EN 374

Respiratory protection

Wear respiratory protection if ventilation is inadequate to prevent overexposure. An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Paste
Colour	Black, Grey, Ocher
Odor	Solvent
Odour threshold	No data available.

Melting point/freezing point	<i>Not applicable.</i>
Boiling point/boiling range	<i>No data available.</i>
Flammability	Flammable liquid: Category 3.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Flash point	51 °C [<i>Test Method:</i> Closed Cup]
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
pH	<i>substance/mixture is non-soluble (in water)</i>
Kinematic Viscosity	116,788 mm ² /sec
Water solubility	Nil
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Vapour pressure	<i>No data available.</i>
Density	1.35 - 1.39 g/cm ³
Relative density	1.35 - 1.39 [<i>Ref Std:</i> WATER=1]
Relative Vapour Density	<i>No data available.</i>
Particle Characteristics	<i>Not applicable.</i>

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	<i>No data available.</i>
Evaporation rate	<i>No data available.</i>
Percent volatile	10.54 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.
Sparks and/or flames.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness. Contact with the skin during product use is not expected to result in significant irritation.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapour(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Limestone	Dermal	Rat	LD50 > 2,000 mg/kg
Limestone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 3 mg/l
Limestone	Ingestion	Rat	LD50 6,450 mg/kg

3M 08826, 08827, Polyurethane Protective Sealer Gray Part B

Talc	Dermal		LD50 estimated to be > 5,000 mg/kg
Talc	Ingestion		LD50 estimated to be > 5,000 mg/kg
Kaolin	Dermal		LD50 estimated to be > 5,000 mg/kg
Kaolin	Ingestion	Human	LD50 > 15,000 mg/kg
Hydrocarbons, C9, aromatics	Dermal	Rabbit	LD50 > 3,160 mg/kg
xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
Hydrocarbons, C9, aromatics	Inhalation-Vapour (4 hours)	Rat	LC50 > 6.2 mg/l
Hydrocarbons, C9, aromatics	Ingestion	Rat	LD50 3,492 mg/kg
xylene	Inhalation-Vapour (4 hours)	Rat	LC50 29 mg/l
xylene	Ingestion	Rat	LD50 3,523 mg/kg
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	Dermal	Guinea pig	LD50 > 18,800 mg/kg
Triiron tetraoxide	Dermal	Not available	LD50 3,100 mg/kg
Triiron tetraoxide	Ingestion	Not available	LD50 3,700 mg/kg
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 8 mg/l
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	Ingestion	Rat	LD50 > 3,200 mg/kg
Castor oil	Dermal		LD50 estimated to be > 5,000
Castor oil	Ingestion		LD50 estimated to be > 5,000
Silicic acid, aluminum sodium salt	Dermal	Rabbit	LD50 > 2,000 mg/kg
Silicic acid, aluminum sodium salt	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 4.57 mg/l
Silicic acid, aluminum sodium salt	Ingestion	Rat	LD50 > 5,000 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Iron hydroxide oxide yellow	Dermal		LD50 estimated to be > 5,000 mg/kg
Iron hydroxide oxide yellow	Ingestion	Rat	LD50 > 10,000 mg/kg
maleic anhydride	Dermal	Rabbit	LD50 2,620 mg/kg
maleic anhydride	Ingestion	Rat	LD50 1,030 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Limestone	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Hydrocarbons, C9, aromatics	Rabbit	Mild irritant
Kaolin	Professional judgement	No significant irritation
xylene	Rabbit	Mild irritant
Triiron tetraoxide	Rabbit	No significant irritation
Castor oil	Human	Minimal irritation
Silicic acid, aluminum sodium salt	Rabbit	No significant irritation
Titanium dioxide	Rabbit	No significant irritation
Iron hydroxide oxide yellow	Rabbit	No significant irritation
maleic anhydride	Human and animal	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Limestone	Rabbit	No significant irritation
Talc	Rabbit	No significant irritation
Hydrocarbons, C9, aromatics	Rabbit	Mild irritant
Kaolin	Professional judgement	No significant irritation
xylene	Rabbit	Mild irritant
Triiron tetraoxide	Rabbit	No significant irritation
Castor oil	Rabbit	Mild irritant
Silicic acid, aluminum sodium salt	Rabbit	Mild irritant
Titanium dioxide	Rabbit	No significant irritation
Iron hydroxide oxide yellow	Rabbit	No significant irritation
maleic anhydride	Rabbit	Corrosive

Skin Sensitisation

Name	Species	Value
Hydrocarbons, C9, aromatics	Guinea pig	Not classified
Triiron tetraoxide	Human	Not classified
Castor oil	Human	Not classified
Titanium dioxide	Human and animal	Not classified
Iron hydroxide oxide yellow	Human and animal	Not classified
maleic anhydride	Multiple animal species	Sensitising

Respiratory Sensitisation

Name	Species	Value
Talc	Human	Not classified
maleic anhydride	Human	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
Talc	In Vitro	Not mutagenic
Talc	In vivo	Not mutagenic
Hydrocarbons, C9, aromatics	In Vitro	Not mutagenic
xylene	In Vitro	Not mutagenic
xylene	In vivo	Not mutagenic
Triiron tetraoxide	In Vitro	Not mutagenic
Castor oil	In Vitro	Not mutagenic
Castor oil	In vivo	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
maleic anhydride	In vivo	Not mutagenic
maleic anhydride	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Talc	Dermal	Human	Some positive data exist, but the data are not sufficient for classification

Talc	Inhalation	Rat	Carcinogenic.
Kaolin	Inhalation	Multiple animal species	Not carcinogenic
xylene	Dermal	Rat	Not carcinogenic
xylene	Ingestion	Multiple animal species	Not carcinogenic
xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Triiron tetraoxide	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Iron hydroxide oxide yellow	Inhalation	Rat	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Limestone	Ingestion	Not classified for development	Rat	NOAEL 625 mg/kg/day	premating & during gestation
Talc	Ingestion	Not classified for development	Rat	NOAEL 1,600 mg/kg	during organogenesis
Hydrocarbons, C9, aromatics	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C9, aromatics	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	2 generation
Hydrocarbons, C9, aromatics	Not specified.	Not classified for development	Rat	NOAEL Not available	2 generation
xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesis
xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	Ingestion	Toxic to development	Rabbit	NOAEL 300 mg/kg/day	during gestation
maleic anhydride	Ingestion	Not classified for female reproduction	Rat	NOAEL 55 mg/kg/day	2 generation
maleic anhydride	Ingestion	Not classified for male reproduction	Rat	NOAEL 55 mg/kg/day	2 generation
maleic anhydride	Ingestion	Not classified for development	Rat	NOAEL 140 mg/kg/day	during organogenesis

Lactation

Name	Route	Species	Value
xylene	Ingestion	Mouse	Not classified for effects on or via lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Limestone	Inhalation	respiratory system	Not classified	Rat	NOAEL 0.812 mg/l	90 minutes
Hydrocarbons, C9, aromatics	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	

Hydrocarbons, C9, aromatics	Inhalation	respiratory irritation	May cause respiratory irritation		NOAEL Not available	
xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable
maleic anhydride	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Limestone	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pneumoconiosis	Repeated and prolonged exposure to large amounts of talc dust can cause lung injury	Human	NOAEL Not available	occupational exposure
Talc	Inhalation	pulmonary fibrosis respiratory system	Not classified	Rat	NOAEL 18 mg/m ³	113 weeks
Kaolin	Inhalation	pneumoconiosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL NA	occupational exposure
Kaolin	Inhalation	pulmonary fibrosis	Not classified	Rat	NOAEL Not available	
xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
xylene	Inhalation	heart endocrine system gastrointestinal tract hematopoietic system muscles kidney and/or bladder respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
xylene	Ingestion	liver	Not classified	Multiple animal species	NOAEL Not available	
xylene	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system nervous	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks

		system respiratory system				
Triiron tetraoxide	Inhalation	pulmonary fibrosis pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure
Castor oil	Ingestion	heart hematopoietic system liver	Not classified	Rat	NOAEL 4,800 mg/kg/day	13 weeks
Castor oil	Ingestion	kidney and/or bladder	Not classified	Mouse	NOAEL 13,000 mg/kg/day	13 weeks
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Iron hydroxide oxide yellow	Inhalation	respiratory system liver kidney and/or bladder	Not classified	Rat	NOAEL 0.2 mg/l	14 days
maleic anhydride	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.0011 mg/l	6 months
maleic anhydride	Inhalation	endocrine system hematopoietic system nervous system kidney and/or bladder heart liver eyes	Not classified	Rat	NOAEL 0.0098 mg/l	6 months
maleic anhydride	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 55 mg/kg/day	80 days
maleic anhydride	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 250 mg/kg/day	183 days
maleic anhydride	Ingestion	heart nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	183 days
maleic anhydride	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 150 mg/kg/day	80 days
maleic anhydride	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 60 mg/kg/day	90 days
maleic anhydride	Ingestion	skin endocrine system immune system eyes respiratory system	Not classified	Rat	NOAEL 150 mg/kg/day	80 days

Aspiration Hazard

Name	Value
Hydrocarbons, C9, aromatics	Aspiration hazard
xylene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	Identifier(s)	Organism	Type	Exposure	Test endpoint	Test result
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC50	>100 mg/l
Limestone	1317-65-3	Rainbow trout	Estimated	96 hours	LC50	>100 mg/l
Limestone	1317-65-3	Water flea	Estimated	48 hours	EC50	>100 mg/l
Limestone	1317-65-3	Green algae	Estimated	72 hours	EC10	>100 mg/l
OXIDISED CASTOR OIL	68187-84-8	Activated sludge	Analogous Compound	3 hours	NOEC	100 mg/l
OXIDISED CASTOR OIL	68187-84-8	Water flea	Experimental	48 hours	EL50	>100 mg/l
Talc	14807-96-6	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Hydrocarbons, C9, aromatics	918-668-5	Activated sludge	Experimental	10 minutes	EC50	>99 mg/l
Hydrocarbons, C9, aromatics	918-668-5	Green algae	Experimental	72 hours	EC50	0.42 mg/l
Hydrocarbons, C9, aromatics	918-668-5	Rainbow trout	Experimental	96 hours	LL50	9.2 mg/l
Hydrocarbons, C9, aromatics	918-668-5	Water flea	Experimental	48 hours	EL50	3.2 mg/l
Hydrocarbons, C9, aromatics	918-668-5	Green algae	Experimental	72 hours	NOEC	0.07 mg/l
Triiron tetraoxide	1317-61-9	Green algae	Analogous Compound	72 hours	No tox obs at lmt of water sol	>100 mg/l
Triiron tetraoxide	1317-61-9	Water flea	Analogous Compound	48 hours	No tox obs at lmt of water sol	>100 mg/l
Triiron tetraoxide	1317-61-9	Zebra Fish	Analogous Compound	96 hours	No tox obs at lmt of water sol	>100 mg/l
Triiron tetraoxide	1317-61-9	Green algae	Analogous Compound	72 hours	No tox obs at lmt of water sol	>100 mg/l
Triiron tetraoxide	1317-61-9	Water flea	Analogous Compound	21 days	No tox obs at lmt of water sol	>100 mg/l
Triiron tetraoxide	1317-61-9	Activated sludge	Analogous Compound	3 hours	EC50	>=10,000 mg/l
Kaolin	1332-58-7	Water flea	Experimental	48 hours	LC50	>1,100 mg/l
xylene	1330-20-7	Green algae	Analogous Compound	73 hours	ErC50	4.36 mg/l
xylene	1330-20-7	Rainbow trout	Analogous Compound	96 hours	LC50	2.6 mg/l
xylene	1330-20-7	Water flea	Analogous Compound	48 hours	EC50	3.82 mg/l
xylene	1330-20-7	Green algae	Analogous Compound	73 hours	NOEC	0.44 mg/l
xylene	1330-20-7	Water flea	Analogous Compound	7 days	NOEC	0.96 mg/l
xylene	1330-20-7	Rainbow trout	Experimental	56 days	NOEC	1.3 mg/l
xylene	1330-20-7	Activated sludge	Analogous Compound	30 minutes	EC50	>198 mg/l
xylene	1330-20-7	Redworm	Experimental	56 days	NOEC	42.6 mg/kg (Dry Weight)
xylene	1330-20-7	Soil microbes	Experimental	28 days	EC50	>1,000 mg/kg (Dry Weight)
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0	Green algae	Experimental	72 hours	EbC50	8 mg/l
1-isopropyl-2,2-dimethyltrimethylene	6846-50-0	Medaka	Experimental	96 hours	LC50	18 mg/l

3M 08826, 08827, Polyurethane Protective Sealer Gray Part B

diisobutyrate						
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0	Green algae	Experimental	72 hours	NOEC	5.3 mg/l
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0	Water flea	Experimental	21 days	NOEC	0.7 mg/l
Iron hydroxide oxide yellow	51274-00-1	Activated sludge	Estimated	3 hours	EC50	>=10,000 mg/l
Iron hydroxide oxide yellow	51274-00-1	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
Iron hydroxide oxide yellow	51274-00-1	Zebra Fish	Experimental	96 hours	No tox obs at lmt of water sol	>100 mg/l
Castor oil	8001-79-4	Zebra Fish	Analogous Compound	96 hours	LC50	>100 mg/l
Castor oil	8001-79-4	Bacteria	Analogous Compound	16 hours	NOEC	10,000 mg/l
Silicic acid, aluminum sodium salt	930-915-9	Fathead minnow	Experimental	96 hours	LC50	>680 mg/l
Silicic acid, aluminum sodium salt	930-915-9	Green algae	Experimental	72 hours	ErC50	130 mg/l
Silicic acid, aluminum sodium salt	930-915-9	Water flea	Experimental	48 hours	EC50	>1,000 mg/l
Silicic acid, aluminum sodium salt	930-915-9	Fathead minnow	Experimental	30 days	NOEC	>=86.7 mg/l
Silicic acid, aluminum sodium salt	930-915-9	Green algae	Experimental	72 hours	NOEC	18 mg/l
Silicic acid, aluminum sodium salt	930-915-9	Sediment organism	Experimental	96 hours	NOEC	1,563 mg/kg (Dry Weight)
Silicic acid, aluminum sodium salt	930-915-9	Water flea	Experimental	21 days	NOEC	32 mg/l
Silicic acid, aluminum sodium salt	930-915-9	Bacteria	Experimental	16 hours	EC50	950 mg/l
Silicic acid, aluminum sodium salt	930-915-9	Radish	Experimental	28 days	EC50	4,000 mg/kg (Dry Weight)
Silicic acid, aluminum sodium salt	930-915-9	Redworm	Experimental	56 days	NOEC	1,000 mg/kg (Dry Weight)
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
maleic anhydride	108-31-6	Bacteria	Experimental	18 hours	EC10	44.6 mg/l
maleic anhydride	108-31-6	Rainbow trout	Experimental	96 hours	LC50	75 mg/l
maleic anhydride	108-31-6	Green algae	Hydrolysis Product	72 hours	ErC50	74.4 mg/l
maleic anhydride	108-31-6	Water flea	Hydrolysis Product	48 hours	EC50	93.8 mg/l
maleic anhydride	108-31-6	Water flea	Experimental	21 days	NOEC	10 mg/l
maleic anhydride	108-31-6	Green algae	Hydrolysis Product	72 hours	ErC10	11.8 mg/l

12.2. Persistence and degradability

Material	Identifier(s)	Test type	Duration	Study Type	Test result	Protocol
Limestone	1317-65-3	Data not availbl-insufficient	N/A	N/A	N/A	N/A

OXIDISED CASTOR OIL	68187-84-8	Analogous Compound Biodegradation	29 days	CO2 evolution	76-79 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Talc	14807-96-6	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Hydrocarbons, C9, aromatics	918-668-5	Experimental Biodegradation	28 days	BOD	78 %BOD/ThO D	OECD 301F - Manometric respirometry
Triiron tetraoxide	1317-61-9	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Kaolin	1332-58-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A
xylene	1330-20-7	Analogous Compound Biodegradation	28 days	BOD	94 %BOD/ThO D	OECD 301F - Manometric respirometry
xylene	1330-20-7	Experimental Photolysis		Photolytic half-life (in air)	1.4 days (t 1/2)	
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0	Experimental Biodegradation	28 days	CO2 evolution	70.73 %CO2 evolution/THC O2 evolution (does not pass 10-day window)	OECD 301B - Modified sturm or CO2
Iron hydroxide oxide yellow	51274-00-1	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Castor oil	8001-79-4	Analogous Compound Biodegradation	28 days	BOD	64 %BOD/ThO D	OECD 301D - Closed bottle test
Silicic acid, aluminum sodium salt	930-915-9	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Data not availbl-insufficient	N/A	N/A	N/A	N/A
maleic anhydride	108-31-6	Hydrolysis product Biodegradation	25 days	CO2 evolution	>90 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
maleic anhydride	108-31-6	Experimental Hydrolysis		Hydrolytic half-life	0.37 minutes (t 1/2)	

12.3 : Bioaccumulative potential

Material	Identifier(s)	Test type	Duration	Study Type	Test result	Protocol
Limestone	1317-65-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
OXIDISED CASTOR OIL	68187-84-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Talc	14807-96-6	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Hydrocarbons, C9, aromatics	918-668-5	Estimated BCF - Fish	70 days	Bioaccumulation factor	342	
Triiron tetraoxide	1317-61-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Kaolin	1332-58-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
xylene	1330-20-7	Experimental BCF - Fish	56 days	Bioaccumulation factor	<=25.9	
xylene	1330-20-7	Analogous Compound Bioconcentration		Log Kow	3.2	
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0	Experimental BAF - Fish	42 days	Bioaccumulation factor	≤31	OECD305-Bioconcentration
Iron hydroxide oxide yellow	51274-00-1	Data not available or insufficient for	N/A	N/A	N/A	N/A

		classification				
Castor oil	8001-79-4	Modeled Bioconcentration		Bioaccumulation factor	7	Catalogic™
Silicic acid, aluminum sodium salt	930-915-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	
maleic anhydride	108-31-6	Experimental Bioconcentration		Log Kow	-2.61	OECD 107 log Kow shke flsk mtd

12.4. Mobility in soil

Material	Identifier(s)	Test type	Study Type	Test result	Protocol
xylene	1330-20-7	Analogous Compound Mobility in Soil	Koc	537 l/kg	
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	6846-50-0	Modeled Mobility in Soil	Koc	490 l/kg	Episuite™
Castor oil	8001-79-4	Modeled Mobility in Soil	Koc	10,000,000,000 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 - UN Number or ID number	UN1993	UN1993	UN1993
14.2 UN proper shipping name	FLAMMABLE LIQUID, N.O.S.(AROMATIC HYDROCARBON)	FLAMMABLE LIQUID, N.O.S.(AROMATIC HYDROCARBON)	FLAMMABLE LIQUID, N.O.S.(AROMATIC HYDROCARBON)
14.3 Transport hazard class(es)	3	3	3
14.4 Packing group	III	III	III
14.5 Environmental hazards	Not Environmentally Hazardous	Not applicable.	Not a Marine Pollutant
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	F1	Not applicable.	Not applicable.
IMDG Segregation Code	Not applicable.	Not applicable.	NONE

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

Ingredient

Talc

Identifier(s)

14807-96-6

Classification

Grp. 2A: Probable
human carc.

Regulation

International Agency
for Research on Cancer

Titanium dioxide

13463-67-7

Grp. 2B: Possible human
carc.International Agency
for Research on Cancer

xylene

1330-20-7

Gr. 3: Not classifiable

International Agency
for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

xylene

1330-20-7

Global inventory status

Contact 3M for more information.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

List of Relevant Notas

Nota C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
--------	--

Revision information:

No revision information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2026, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	08-8587-1	Version number:	3.00
Revision date:	15/06/2026	Supersedes date:	09/06/2026

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (1907/2006) as amended by Regulation (EU) 2020/878

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Activator for PU Protective Sealers series 08820/08830

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Automotive., Sealant

1.3. Details of the supplier of the safety data sheet

Address:	3M Ireland Limited, 70 SIR JOHN ROGERSON'S QUAY, D02R296 DUBLIN 2
Telephone:	+353 1 280 3555
E Mail:	ner-productstewardship@mmm.com
Website:	www.3M.com

1.4. Emergency telephone number

Emergency medical information: 8am-10pm (seven days) contact National Poisons Information Centre, Beaumont Hospital, Dublin 9 DOV2NO, Ireland. Telephone Number: +353 (0)1 809 2166

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture CLP REGULATION (EC) No 1272/2008

The health and environmental classifications of this material have been derived using the calculation method, except in cases where test data are available or the physical form impacts classification. Classification(s) based on test data or physical form are noted below, if applicable.

CLASSIFICATION:

Acute Toxicity, Category 4 - Acute Tox. 4; H332
Skin Corrosion/Irritation, Category 2 - Skin Irrit. 2; H315
Serious Eye Damage/Eye Irritation, Category 2 - Eye Irrit. 2; H319
Respiratory Sensitization, Category 1 - Resp. Sens. 1; H334
Skin Sensitization, Category 1 - Skin Sens. 1; H317
Carcinogenicity, Category 2 - Carc. 2; H351
Specific Target Organ Toxicity-Repeated Exposure, Category 2 - STOT RE 2; H373

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H335
Hazardous to the Aquatic Environment (Chronic), Category 3 - Aquatic Chronic 3; H412

For full text of H phrases, see Section 16.

2.2. Label elements

CLP REGULATION (EC) No 1272/2008

SIGNAL WORD

DANGER.

Symbols

GHS07 (Exclamation mark) | GHS08 (Health Hazard) |

Pictograms



Ingredients:

Ingredient	Identifier(s)	EC No.	% by Wt
Polymethylene polyphenylene isocyanate	9016-87-9		60 - 90
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	227-534-9	5 - 15
4,4'-methylenediphenyl diisocyanate	101-68-8	202-966-0	5 - 15
2,2'-methylenediphenyl diisocyanate	2536-05-2	219-799-4	< 0.1

HAZARD STATEMENTS:

H332	Harmful if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure: respiratory system.
H412	Harmful to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P261E	Avoid breathing vapour or spray.
P280	Wear protective gloves and eye protection.

Response:

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician.

7% of the mixture consists of components of unknown acute inhalation toxicity.

Information required per Regulation (EU) 2020/1149 as regards diisocyanates:

As from 24 August 2023 adequate training is required before industrial or professional use. Further information can be found at feica.eu/Puinfo

2.3. Other hazards

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.
This material does not contain any substances that are assessed to be a PBT or vPvB

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Ingredient	Identifier(s)	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Polymethylene polyphenylene isocyanate	(CAS-No.) 9016-87-9	60 - 90	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373
o-(p-isocyanatobenzyl)phenyl isocyanate	(CAS-No.) 5873-54-1 (EC-No.) 227-534-9 (REACH-No.) 01-2119480143-45	5 - 15	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 Nota 2,C
4,4'-methylenediphenyl diisocyanate	(CAS-No.) 101-68-8 (EC-No.) 202-966-0 (REACH-No.) 01-2119457014-47	5 - 15	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 Nota 2,C
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	(EC-No.) 923-037-2 (REACH-No.) 01-2119471991-29	3 - 7	Aquatic Chronic 2, H411 Flam. Liq. 3, H226 Asp. Tox. 1, H304 EUH066
2,2'-methylenediphenyl diisocyanate	(CAS-No.) 2536-05-2 (EC-No.) 219-799-4 (REACH-No.) 01-2119927323-43	< 0.1	Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317

			Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373 Nota 2,C
--	--	--	---

Any entry in the Identifier(s) column that begins with the numbers 6, 7, 8, or 9 are a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance.

Please see section 16 for the full text of any H statements referred to in this section

Specific Concentration Limits

Ingredient	Identifier(s)	Specific Concentration Limits
2,2'-methylenediphenyl diisocyanate	(CAS-No.) 2536-05-2 (EC-No.) 219-799-4 (REACH-No.) 01-2119927323-43	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319 (C >= 0.1%) Resp. Sens. 1, H334 (C >= 5%) STOT SE 3, H335
o-(p-isocyanatobenzyl)phenyl isocyanate	(CAS-No.) 5873-54-1 (EC-No.) 227-534-9 (REACH-No.) 01-2119480143-45	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319 (C >= 0.1%) Resp. Sens. 1, H334 (C >= 5%) STOT SE 3, H335
4,4'-methylenediphenyl diisocyanate	(CAS-No.) 101-68-8 (EC-No.) 202-966-0 (REACH-No.) 01-2119457014-47	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319 (C >= 0.1%) Resp. Sens. 1, H334 (C >= 5%) STOT SE 3, H335
Polymethylene polyphenylene isocyanate	(CAS-No.) 9016-87-9	(C >= 5%) Skin Irrit. 2, H315 (C >= 5%) Eye Irrit. 2, H319 (C >= 0.1%) Resp. Sens. 1, H334 (C >= 5%) STOT SE 3, H335

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Remove person to fresh air. Get immediate medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain).

Allergic respiratory reaction (difficulty breathing, wheezing, cough, and tightness of chest). Harmful if inhaled. Irritation to

the skin (localized redness, swelling, itching, and dryness). Allergic skin reaction (redness, swelling, blistering, and itching). Serious irritation to the eyes (significant redness, swelling, pain, tearing, and impaired vision). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide.
Hydrogen cyanide.
Oxides of nitrogen.

Condition

During combustion.
During combustion.
During combustion.
During combustion.

5.3. Advice for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Pour isocyanate decontaminant solution (90% water, 8% concentrated ammonia, 2% detergent) on spill and allow to react for 10 minutes. Or pour water on spill and allow to react for more than 30 minutes. Cover with absorbent material. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorised

person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Dispose of collected material as soon as possible.

6.4. Reference to other sections

Refer to Section 8 and Section 13 for more information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from acids. Store away from oxidising agents. Store away from amines.

7.3. Specific end use(s)

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	Identifier(s)	Agency	Limit type	Additional comments
Isocyanates, All, except Methyl isocyanate (CAS No. 624-83-9) and Toluene (2,4 or 2,6 diisocyanate (CAS No. 584-84-9, 91-08-7)	101-68-8	Ireland OELs	TWA(8 hours):0.02 mg/m ³ ;STEL(15 minutes):0.07 mg/m ³	as NCO, Resp/Dermal sensitizer
4,4'-methylenediphenyl diisocyanate	101-68-8	Ireland OELs	TWA(as NCO)(8 hours):0.005 ppm;TWA(8 hours):0.005 ppm	as NCO, Resp/Dermal sensitizer, Respiratory/Dermal Sensitizer
Isocyanates, All, except Methyl isocyanate (CAS No. 624-83-9) and Toluene (2,4 or 2,6 diisocyanate (CAS No. 584-84-9, 91-08-7)	2536-05-2	Ireland OELs	TWA(8 hours):0.02 mg/m ³ ;STEL(15 minutes):0.07 mg/m ³	as NCO, Resp/Dermal sensitizer
Isocyanates, All, except Methyl isocyanate (CAS No. 624-83-9) and Toluene (2,4 or 2,6 diisocyanate (CAS No. 584-84-9, 91-08-7)	5873-54-1	Ireland OELs	TWA(8 hours):0.02 mg/m ³ ;STEL(15 minutes):0.07 mg/m ³	as NCO, Resp/Dermal sensitizer
Isocyanates, All, except Methyl isocyanate (CAS No. 624-83-9) and Toluene (2,4 or 2,6 diisocyanate (CAS No. 584-84-9,	9016-87-9	Ireland OELs	TWA(8 hours):0.02 mg/m ³ ;STEL(15 minutes):0.07 mg/m ³	as NCO, Resp/Dermal sensitizer

91-08-7)

Ireland OELs : Ireland. OELs

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

Biological limit values

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

Recommended monitoring procedures:Information on recommended monitoring procedures can be obtained from Indust. Inspect./Ministry (IE)

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Applicable Norms/Standards

Use eye/face protection conforming to EN 16321

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Butyl rubber.	0.5	=>8 hours
Neoprene.	0.5	=>8 hours
Nitrile rubber.	0.35	=>8 hours
Natural rubber.	0.5	=>8 hours
Polyvinyl chloride.	0.5	=>8 hours

The glove data presented are based on the substance driving dermal toxicity and the conditions present at the time of testing. Breakthrough time may be altered when the glove is subjected to use conditions that place additional stress on the glove.

Applicable Norms/Standards

Use gloves tested to EN 374

If this product is used in a manner that presents a higher potential for exposure (e.g., spraying, high splash potential, etc.), then use of a protective apron may be necessary. See recommended glove material(s) for determining appropriate apron material(s). If a glove material is not available as an apron, polymer laminate is a suitable option.

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Use a positive pressure supplied-air respirator if there is a potential for over exposure from an uncontrolled release, exposure levels are not known, or under any other circumstances where air-purifying respirators may not provide adequate protection. Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Applicable Norms/Standards

Use a respirator conforming to EN 140 or EN 136: filter types A & P

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Brown
Odor	Characteristic Odour
Odour threshold	No data available.
Melting point/freezing point	Not applicable.
Boiling point/boiling range	No data available.
Flammability	Not applicable.
Flammable Limits(LEL)	No data available.
Flammable Limits(UEL)	No data available.
Flash point	69.5 °C [Test Method: Closed Cup]
Autoignition temperature	No data available.
Decomposition temperature	No data available.
pH	substance/mixture is non-soluble (in water)
Kinematic Viscosity	No data available.
Water solubility	Nil
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Vapour pressure	No data available.
Density	1.19 - 1.23 g/cm ³
Relative density	1.19 - 1.23 [Ref Std: WATER=1]
Relative Vapour Density	No data available.
Particle Characteristics	Not applicable.

9.2. Other information

9.2.2 Other safety characteristics

EU Volatile Organic Compounds	No data available.
Evaporation rate	No data available.
Percent volatile	<=5 % weight

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable. Polymerizes at about 200 C, with evolution of carbon dioxide

10.3 Possibility of hazardous reactions

Hazardous polymerisation may occur. Exothermic reaction with amines and alcohols; reacts with water to form carbon dioxide; in closed contains, risk of bursting due to increase of pressure.

10.4 Conditions to avoid

Heat.

Sparks and/or flames.

10.5 Incompatible materials

Alcohols.

Amines.

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

Strong oxidising agents.

Water

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from internal hazard assessments.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Fatal if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:

Prolonged or repeated exposure may cause target organ effects:

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

Additional information:

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE >0.05 - =0.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Polymethylene polyphenylene isocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
Polymethylene polyphenylene isocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
Polymethylene polyphenylene isocyanate	Ingestion	Rat	LD50 31,600 mg/kg
o-(p-isocyanatobenzyl)phenyl isocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
4,4'-methylenediphenyl diisocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
o-(p-isocyanatobenzyl)phenyl isocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
o-(p-isocyanatobenzyl)phenyl isocyanate	Ingestion	Rat	LD50 31,600 mg/kg
4,4'-methylenediphenyl diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
4,4'-methylenediphenyl diisocyanate	Ingestion	Rat	LD50 31,600 mg/kg
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	Ingestion	Rat	LD50 > 5,000 mg/kg
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	Dermal	similar compounds	LD50 > 5,000 mg/kg
2,2'-methylenediphenyl diisocyanate	Dermal	Rabbit	LD50 > 5,000 mg/kg
2,2'-methylenediphenyl diisocyanate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
2,2'-methylenediphenyl diisocyanate	Ingestion	Rat	LD50 31,600 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Polymethylene polyphenylene isocyanate	official classification	Irritant
o-(p-isocyanatobenzyl)phenyl isocyanate	official classification	Irritant
4,4'-methylenediphenyl diisocyanate	official classification	Irritant
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	Rabbit	Mild irritant
2,2'-methylenediphenyl diisocyanate	official classification	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
------	---------	-------

Polymethylene polyphenylene isocyanate	official classification	Severe irritant
o-(p-isocyanatobenzyl)phenyl isocyanate	official classification	Severe irritant
4,4'-methylenediphenyl diisocyanate	official classification	Severe irritant
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	Rabbit	No significant irritation
2,2'-methylenediphenyl diisocyanate	official classification	Severe irritant

Skin Sensitisation

Name	Species	Value
Polymethylene polyphenylene isocyanate	Mouse	Sensitising
o-(p-isocyanatobenzyl)phenyl isocyanate	Mouse	Sensitising
4,4'-methylenediphenyl diisocyanate	Mouse	Sensitising
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	Guinea pig	Not classified
2,2'-methylenediphenyl diisocyanate	Mouse	Sensitising

Respiratory Sensitisation

Name	Species	Value
Polymethylene polyphenylene isocyanate	Human	Sensitising
o-(p-isocyanatobenzyl)phenyl isocyanate	Human	Sensitising
4,4'-methylenediphenyl diisocyanate	Human	Sensitising
2,2'-methylenediphenyl diisocyanate	Human	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
Polymethylene polyphenylene isocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
o-(p-isocyanatobenzyl)phenyl isocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
4,4'-methylenediphenyl diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	In Vitro	Not mutagenic
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	In vivo	Not mutagenic
2,2'-methylenediphenyl diisocyanate	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Polymethylene polyphenylene isocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
o-(p-isocyanatobenzyl)phenyl isocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
4,4'-methylenediphenyl diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification
2,2'-methylenediphenyl diisocyanate	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
------	-------	-------	---------	-------------	-------------------

Polymethylene polyphenylene isocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
o-(p-isocyanatobenzyl)phenyl isocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
4,4'-methylenediphenyl diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
2,2'-methylenediphenyl diisocyanate	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Polymethylene polyphenylene isocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
o-(p-isocyanatobenzyl)phenyl isocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
2,2'-methylenediphenyl diisocyanate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Polymethylene polyphenylene isocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
o-(p-isocyanatobenzyl)phenyl isocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
4,4'-methylenediphenyl diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	Inhalation	kidney and/or bladder	Not classified	Rat	LOAEL 2.6 mg/l	13 weeks
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	Inhalation	heart liver endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles nervous system eyes respiratory system	Not classified	Rat	NOAEL 10.4 mg/l	13 weeks
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	Ingestion	liver kidney and/or bladder heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles nervous system eyes respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	13 weeks

		system vascular system				
2,2'-methylenediphenyl diisocyanate	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks

Aspiration Hazard

Name	Value
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

11.2. Information on other hazards

This material does not contain any substances that are assessed to be an endocrine disruptor for human health.

SECTION 12: Ecological information

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

12.1. Toxicity

No product test data available.

Material	Identifier(s)	Organism	Type	Exposure	Test endpoint	Test result
Polymethylene polyphenylene isocyanate	9016-87-9	Green algae	Analogous Compound	72 hours	No tox obs at lmt of water sol	>100 mg/l
Polymethylene polyphenylene isocyanate	9016-87-9	Water flea	Analogous Compound	24 hours	No tox obs at lmt of water sol	>100 mg/l
Polymethylene polyphenylene isocyanate	9016-87-9	Green algae	Analogous Compound	72 hours	No tox obs at lmt of water sol	>100 mg/l
Polymethylene polyphenylene isocyanate	9016-87-9	Activated sludge	Analogous Compound	3 hours	EC50	>100 mg/l
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	Activated sludge	Analogous Compound	3 hours	EC50	>100 mg/l
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	Green algae	Analogous Compound	72 hours	No tox obs at lmt of water sol	>100 mg/l
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	Water flea	Analogous Compound	24 hours	No tox obs at lmt of water sol	>100 mg/l
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	Zebra Fish	Analogous Compound	96 hours	No tox obs at lmt of water sol	>100 mg/l
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	Green algae	Analogous Compound	72 hours	NOEL	100 mg/l
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	Water flea	Experimental	21 days	NOEC	100 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Activated sludge	Estimated	3 hours	EC50	>100 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Green algae	Estimated	72 hours	EC50	>1,640 mg/l

4,4'-methylenediphenyl diisocyanate	101-68-8	Water flea	Estimated	24 hours	EC50	>1,000 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Zebra Fish	Estimated	96 hours	LC50	>1,000 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Green algae	Estimated	72 hours	NOEC	1,640 mg/l
4,4'-methylenediphenyl diisocyanate	101-68-8	Water flea	Estimated	21 days	NOEC	10 mg/l
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	923-037-2	Green algae	Experimental	72 hours	EL50	>1,000 mg/l
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	923-037-2	Rainbow trout	Experimental	96 hours	LL50	>1,000 mg/l
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	923-037-2	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	923-037-2	Green algae	Experimental	72 hours	NOEL	1,000 mg/l
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	923-037-2	Water flea	Experimental	21 days	NOEL	1 mg/l
2,2'-methylenediphenyl diisocyanate	2536-05-2	Activated sludge	Estimated	3 hours	EC50	>100 mg/l
2,2'-methylenediphenyl diisocyanate	2536-05-2	Green algae	Estimated	72 hours	EC50	>1,640 mg/l
2,2'-methylenediphenyl diisocyanate	2536-05-2	Water flea	Estimated	24 hours	EC50	>1,000 mg/l
2,2'-methylenediphenyl diisocyanate	2536-05-2	Zebra Fish	Estimated	96 hours	LC50	>1,000 mg/l
2,2'-methylenediphenyl diisocyanate	2536-05-2	Green algae	Estimated	72 hours	NOEC	1,640 mg/l
2,2'-methylenediphenyl diisocyanate	2536-05-2	Water flea	Estimated	21 days	NOEC	10 mg/l

12.2. Persistence and degradability

Material	Identifier(s)	Test type	Duration	Study Type	Test result	Protocol
Polymethylene polyphenylene isocyanate	9016-87-9	Analogous Compound Aquatic Inherent Biodegrad.	28 days	BOD	0 %BOD/ThO D	OECD 302C - Modified MITI (II)
Polymethylene polyphenylene isocyanate	9016-87-9	Analogous Compound Hydrolysis		Hydrolytic half-life	20 hours (t 1/2)	
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	Data not availbl-insufficient	N/A	N/A	N/A	N/A
4,4'-methylenediphenyl diisocyanate	101-68-8	Estimated Hydrolysis		Hydrolytic half-life	20 hours (t 1/2)	
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	923-037-2	Experimental Biodegradation	28 days	BOD	31.3 %BOD/Th OD	OECD 301F - Manometric respirometry
2,2'-methylenediphenyl diisocyanate	2536-05-2	Estimated Hydrolysis		Hydrolytic half-life	20 hours (t 1/2)	

12.3 : Bioaccumulative potential

Material	Identifier(s)	Test type	Duration	Study Type	Test result	Protocol
Polymethylene polyphenylene isocyanate	9016-87-9	Analogous Compound BCF - Fish	28 days	Bioaccumulation factor	200	OECD305-Bioconcentration
Polymethylene polyphenylene isocyanate	9016-87-9	Analogous Compound Bioconcentration		Log Kow	4.51	
o-(p-	5873-54-1	Analogous	28 days	Bioaccumulation	200	

isocyanatobenzyl)phenyl isocyanate		Compound BCF - Fish		factor		
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	Experimental Bioconcentration		Log Kow	4.51	OECD 117 log Kow HPLC method
4,4'-methylenediphenyl diisocyanate	101-68-8	Experimental BCF - Fish	28 days	Bioaccumulation factor	200	OECD305-Bioconcentration
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	923-037-2	Estimated Bioconcentration		Log Kow	> 4	
2,2'-methylenediphenyl diisocyanate	2536-05-2	Estimated BCF - Fish	28 days	Bioaccumulation factor	200	OECD305-Bioconcentration

12.4. Mobility in soil

Material	Identifier(s)	Test type	Study Type	Test result	Protocol
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	Modeled Mobility in Soil	Koc	300,000 l/kg	Episuite™
4,4'-methylenediphenyl diisocyanate	101-68-8	Estimated Mobility in Soil	Koc	34,000 l/kg	Episuite™

12.5. Results of the PBT and vPvB assessment

This material does not contain any substances that are assessed to be a PBT or vPvB

12.6. Endocrine disrupting properties

This material does not contain any substances that are assessed to be an endocrine disruptor for environmental effects

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

EU waste code (product as sold)

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transportation information

Not hazardous for transportation.

	Ground Transport (ADR)	Air Transport (IATA)	Marine Transport (IMDG)
14.1 - UN Number or ID number	No data available.	No data available.	No data available.
14.2 UN proper shipping name	No data available.	No data available.	No data available.
14.3 Transport hazard class(es)	No data available.	No data available.	No data available.
14.4 Packing group	No data available.	No data available.	No data available.
14.5 Environmental hazards	No data available.	No data available.	No data available.
14.6 Special precautions for user	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.	Please refer to the other sections of the SDS for further information.
14.7 Marine Transport in bulk according to IMO instruments	No data available.	No data available.	No data available.
Control Temperature	No data available.	No data available.	No data available.
Emergency Temperature	No data available.	No data available.	No data available.
ADR Classification Code	No data available.	No data available.	No data available.
IMDG Segregation Code	No data available.	No data available.	No data available.

Please contact the address or phone number listed on the first page of the SDS for additional information on the transport/shipment of the material by rail (RID) or inland waterways (ADN).

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Carcinogenicity

<u>Ingredient</u>	<u>Identifier(s)</u>	<u>Classification</u>	<u>Regulation</u>
2,2'-methylenediphenyl diisocyanate	2536-05-2	Carc. 2	Regulation (EC) No. 1272/2008, Table 3.1
o-(p-isocyanatobenzyl)phenyl isocyanate	5873-54-1	Carc. 2	Regulation (EC) No. 1272/2008, Table 3.1
4,4'-methylenediphenyl diisocyanate	101-68-8	Carc. 2	Regulation (EC) No. 1272/2008, Table 3.1
4,4'-methylenediphenyl diisocyanate	101-68-8	Gr. 3: Not classifiable	International Agency for Research on Cancer

Polymethylene polyphenylene isocyanate	9016-87-9	Carc. 2	3M classified according to Regulation (EC) No 1272/2008
Polymethylene polyphenylene isocyanate	9016-87-9	Gr. 3: Not classifiable	International Agency for Research on Cancer

Restrictions on the manufacture, placing on the market and use:

The following substance(s) contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product are required to comply with the restrictions placed upon it by the aforementioned provision.

<u>Ingredient</u>	<u>Identifier(s)</u>
Polymethylene polyphenylene isocyanate	9016-87-9

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) No 1907/2006 for Conditions of Restriction

Global inventory status

Contact 3M for more information.

DIRECTIVE 2012/18/EU

Seveso hazard categories, Annex 1, Part 1

None

Seveso named dangerous substances, Annex 1, Part 2

None

Regulation (EU) No 649/2012

No chemicals listed

15.2. Chemical Safety Assessment

A chemical safety assessment has not been carried out for this substance/mixture in accordance with Regulation (EC) No 1907/2006, as amended.

SECTION 16: Other information

List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure: respiratory system.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

List of Relevant Notas

Nota 2	The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.
Nota C	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Revision information:

No revision information

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications. In addition, this SDS is being provided to convey health and safety information. If you are the importer of record of this product into the European Union, you are responsible for all regulatory requirements, including, but not limited to, product registrations/notifications, substance volume tracking, and potential substance registration.

3M Ireland MSDSs are available at www.3M.com