Safety Data Sheet

Copyright,2026, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	26-7363-0	**Version number:**	5.06
Issue Date:	2026/09/25	**Supersedes Date:**	2026/01/06

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier
3M(TM) Silicone Spray - CA

Product Identification Numbers
62-4699-4920-0 62-4699-4930-9 62-4699-4935-8

1.2. Recommended use and restrictions on use

Intended Use
Industrial use

Specific Use
Lubricant

Restrictions on use
Not applicable

1.3. Supplier's details

Company:	3M Canada Company
Division:	Industrial Adhesives and Tapes Division
Address:	1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone:	(800) 364-3577
Website:	www.3M.ca

1.4. Emergency telephone number
Medical Emergency Telephone:1-800-3M HELPS / 1800 364 3577

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture
Aerosol: Category 1.
Skin Corrosion/Irritation: Category 2.
Serious Eye Damage/Irritation: Category 2A.
Specific Target Organ Toxicity (single exposure): Category 1.
Specific Target Organ Toxicity (single exposure): Category 3.
Aspiration Hazard: Category 1.

Simple Asphyxiants: Category 1

2.2. Label elements
Signal word
Danger

Symbols
Flame |Exclamation mark |Health Hazard |

Pictograms



Hazard Statements
Extremely flammable aerosol. Pressurized container: may burst if heated.
Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. May displace oxygen and cause rapid suffocation.
Causes damage to organs: cardiovascular system.

Precautionary statements
General:
Keep out of reach of children.

Prevention:
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe vapor or spray. Wash exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye protection. In case of inadequate ventilation wear respiratory protection.

Response:
IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Immediately call a POISON CENTRE or doctor. Specific treatment (see Notes to Physician on this label). Do NOT induce vomiting. If eye irritation persists or if skin irritation occurs: Get medical advice. If experiencing respiratory symptoms: Call a POISON CENTER or doctor. Take off contaminated clothing and wash it before reuse.

Storage:
Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C).

Disposal:
Dispose of contents and container in accordance with applicable local, regional, national, and international regulations.

Notes to Physician:
Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

2.3. Other hazards
None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Acetone	67-64-1	15 - 40 Trade Secret *	2-Propanone
Propane	74-98-6	15 - 40 Trade Secret *	Propane
Hydrotreated Light Naphtha (Petroleum)	64742-49-0	10 - 30 Trade Secret *	Naphtha, (petroleum), hydrotreated light
Poly(Dimethylsiloxane)	63148-62-9	1 - 10	Siloxanes and Silicones, di-Me
Methylcyclohexane	108-87-2	1 - 5	Cyclohexane, methyl-
Solvent Naphtha (Petroleum), Light Aliphatic	64742-89-8	1 - 5	Solvent naphtha, petroleum, light aliph.

*The concentration (exact or range) of this component has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Remove person to fresh air. Get medical attention.

Skin Contact:
Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:
Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:
Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Aspiration pneumonitis (coughing, gasping, choking, burning of the mouth, and difficulty breathing). Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required
Exposure may increase myocardial irritability. Do not administer sympathomimetic drugs unless absolutely necessary.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media
Use a fire fighting agent suitable for the surrounding fire.

5.2. Unsuitable extinguishing media
None Determined

5.3. Special hazards arising from the substance or mixture
Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

Substance	Condition
Hydrocarbons	During Combustion
Formaldehyde	During Combustion
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion

5.4. Special protection actions for fire-fighters
Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Use personal protective equipment based on the results of an exposure assessment. Refer to Section 8 for PPE recommendations. If anticipated exposure resulting from an accidental release exceeds the protective capabilities of the PPE listed in Section 8, or are unknown, select PPE that offers an appropriate level of protection. Consider the physical and chemical hazards of the material when doing so. Examples of PPE ensembles for emergency response could include wearing bunker gear for a release of flammable material; wearing chemical protective clothing if the spilled material is a corrosive, a sensitizer, a significant dermal irritant, or can be absorbed through the skin; or donning a positive pressure supplied-air respirator for chemicals with inhalation hazards. For information regarding physical and health hazards, refer to sections 2 and 11 of the SDS.

6.2. Environmental precautions
For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up
If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Cover spill area with a fire extinguishing foam that is resistant to polar solvents. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Do not use in a confined area with minimal air exchange. Keep out of reach of children. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities
Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C). Store away from heat. Store away from acids. Store away from oxidizing agents. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits
If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments

Methylcyclohexane	108-87-2	ACGIH	TWA:100 ppm	
Acetone	67-64-1	ACGIH	TWA:250 ppm;STEL:500 ppm	
Propane	74-98-6	ACGIH	Limit value not established:	simple asphyxiant

ACGIH : American Conference of Governmental Industrial Hygienists
AIHA : American Industrial Hygiene Association
CMRG : Chemical Manufacturer's Recommended Guidelines
TWA: Time-Weighted-Average
STEL: Short Term Exposure Limit
CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls
Do not remain in area where available oxygen may be reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Indirect Vented Goggles

Skin/hand protection
Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
Half facepiece or full facepiece air-purifying respirator suitable for organic vapors
Half facepiece or full facepiece supplied-air respirator
Organic vapor cartridges may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Specific Physical Form:	Aerosol
Colour	Gray
Odour	Mild Solvent
Odour threshold	*No Data Available*
pH	*Not Applicable*
Melting point/Freezing point	*Not Applicable*

Boiling point	54.4 ºC [*Test Method:*Estimated]
Flash Point	-28.9 ºC [*Test Method:*Closed Cup] [*Details:*Propellant]
Evaporation rate	*No Data Available*
Flammability	Flammable Aerosol: Category 1.
Flammable Limits(LEL)	*No Data Available*
Flammable Limits(UEL)	*No Data Available*
Vapour Pressure	*No Data Available*
Relative Vapour Density	>=1 [*Ref Std:*AIR=1]
Density	0.65 g/ml
Relative density	0.65 [@ 21.1 ºC] [*Ref Std:*WATER=1]
Water solubility	Moderate
Solubility- non-water	*No Data Available*
Partition coefficient: n-octanol/ water	*No Data Available*
Autoignition temperature	*No Data Available*
Decomposition temperature	*No Data Available*
Kinematic Viscosity	*No Data Available*
Volatile Organic Compounds	<=390 g/l [*Test Method:*calculated SCAQMD rule 443.1] [*Details:*low solids less exempts]
Volatile Organic Compounds	<=60 % weight [*Test Method:*calculated per CARB title 2]
Percent volatile	95 %
VOC Less H2O & Exempt Solvents	<=548 g/l [*Test Method:*calculated SCAQMD rule 443.1]
Average particle size	*No Data Available*
Bulk density	*No Data Available*
Molecular weight	*No Data Available*
Softening point	*No Data Available*
Solids Content	0 % weight

* The values noted with an asterisk (*) in the above table are representative values based on testing of raw materials and selected products. Additionally, a material's characteristics may change depending upon the process and conditions of use at a facility, including further changes in particle size, or mixture with other materials. In order to obtain specific data for the material, we recommend the user conduct characterization testing based on the use factors at the specific facility.

Particle Characteristics	*Not Applicable*

SECTION 10: Stability and reactivity

10.1. Reactivity
This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability
Stable.

10.3. Possibility of hazardous reactions
Hazardous polymerization will not occur.

10.4. Conditions to avoid
Heat

10.5. Incompatible materials
Strong oxidizing agents

10.6. Hazardous decomposition products

Substance	Condition
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:
Simple Asphyxiation: Signs/symptoms may include increased heart rate, rapid respirations, drowsiness, headache, incoordination, altered judgement, nausea, vomiting, lethargy, seizures, coma, and may be fatal. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:
Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Eye Contact:
Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:
Chemical (Aspiration) Pneumonitis: Signs/symptoms may include coughing, gasping, choking, burning of the mouth, difficulty breathing, bluish coloured skin (cyanosis), and may be fatal. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:
Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness. Single exposure, above recommended guidelines, may cause: Cardiac Sensitization: Signs/symptoms may include irregular heartbeat (arrhythmia), faintness, chest pain, and may be fatal.

Toxicological Data
If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg

Propane	Inhalation-Gas (4 hours)	Rat	LC50 > 200,000 ppm
Acetone	Dermal	Rabbit	LD50 > 15,688 mg/kg
Acetone	Inhalation-Vapor (4 hours)	Rat	LC50 76 mg/l
Acetone	Ingestion	Rat	LD50 5,800 mg/kg
Hydrotreated Light Naphtha (Petroleum)	Dermal	Rabbit	LD50 > 3,160 mg/kg
Hydrotreated Light Naphtha (Petroleum)	Inhalation-Vapor (4 hours)	Rat	LC50 > 14.7 mg/l
Hydrotreated Light Naphtha (Petroleum)	Ingestion	Rat	LD50 > 5,000 mg/kg
Poly(Dimethylsiloxane)	Dermal	Multiple animal species	LD50 > 2,000 mg/kg
Poly(Dimethylsiloxane)	Ingestion	Rat	LD50 > 5,000 mg/kg
Methylcyclohexane	Inhalation-Vapor	Professional judgement	LC50 estimated to be 20 - 50 mg/l
Methylcyclohexane	Ingestion	Professional judgement	LD50 estimated to be 2,000 - 5,000 mg/kg
Methylcyclohexane	Dermal	similar compounds	LD50 > 2,000 mg/kg
Solvent Naphtha (Petroleum), Light Aliphatic	Dermal	Rabbit	LD50 3,000 mg/kg
Solvent Naphtha (Petroleum), Light Aliphatic	Inhalation-Vapor (4 hours)	Rat	LC50 > 5.2 mg/l
Solvent Naphtha (Petroleum), Light Aliphatic	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Propane	Rabbit	Minimal irritation
Acetone	Mouse	Minimal irritation
Hydrotreated Light Naphtha (Petroleum)	Rabbit	Irritant
Poly(Dimethylsiloxane)	Human and animal	No significant irritation
Methylcyclohexane	Rabbit	No significant irritation
Solvent Naphtha (Petroleum), Light Aliphatic	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Propane	Rabbit	Mild irritant
Acetone	Rabbit	Severe irritant
Hydrotreated Light Naphtha (Petroleum)	Rabbit	Mild irritant
Poly(Dimethylsiloxane)	Rabbit	No significant irritation
Methylcyclohexane	Rabbit	No significant irritation
Solvent Naphtha (Petroleum), Light Aliphatic	Rabbit	No significant irritation

Skin Sensitization

Name	Species	Value
Hydrotreated Light Naphtha (Petroleum)	Guinea pig	Not classified
Poly(Dimethylsiloxane)	Human and animal	Not classified

Methylcyclohexane	similar compoun ds	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Propane	In Vitro	Not mutagenic
Acetone	In vivo	Not mutagenic
Acetone	In Vitro	Some positive data exist, but the data are not sufficient for classification
Hydrotreated Light Naphtha (Petroleum)	In Vitro	Not mutagenic
Poly(Dimethylsiloxane)	In Vitro	Not mutagenic
Poly(Dimethylsiloxane)	In vivo	Not mutagenic
Methylcyclohexane	In Vitro	Not mutagenic
Solvent Naphtha (Petroleum), Light Aliphatic	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Acetone	Not Specified	Multiple animal species	Not carcinogenic
Hydrotreated Light Naphtha (Petroleum)	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Poly(Dimethylsiloxane)	Dermal	Mouse	Not carcinogenic
Poly(Dimethylsiloxane)	Ingestion	Mouse	Not carcinogenic
Methylcyclohexane	Inhalation	Multiple animal species	Not carcinogenic
Solvent Naphtha (Petroleum), Light Aliphatic	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Acetone	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,700 mg/kg/day	13 weeks
Acetone	Inhalation	Not classified for development	Rat	NOAEL 5.2 mg/l	during organogenesis
Poly(Dimethylsiloxane)	Ingestion	Not classified for development	Rat	NOAEL 3,800 mg/kg/day	during organogenesis
Poly(Dimethylsiloxane)	Dermal	Not classified for development	Rabbit	NOAEL 1,000 mg/kg/day	during organogenesis
Methylcyclohexane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Methylcyclohexane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
Methylcyclohexane	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration

Propane	Inhalation	cardiac sensitization	Causes damage to organs	Human	NOAEL Not available	
Propane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Propane	Inhalation	respiratory irritation	Not classified	Human	NOAEL Not available	
Acetone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Acetone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 hours
Acetone	Inhalation	liver	Not classified	Guinea pig	NOAEL Not available	
Acetone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Hydrotreated Light Naphtha (Petroleum)	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Hydrotreated Light Naphtha (Petroleum)	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Hydrotreated Light Naphtha (Petroleum)	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Methylcyclohexane	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
Methylcyclohexane	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Solvent Naphtha (Petroleum), Light Aliphatic	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Solvent Naphtha (Petroleum), Light Aliphatic	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Solvent Naphtha (Petroleum), Light Aliphatic	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Acetone	Dermal	eyes	Not classified	Guinea pig	NOAEL Not available	3 weeks
Acetone	Inhalation	hematopoietic system	Not classified	Human	NOAEL 3 mg/l	6 weeks
Acetone	Inhalation	immune system	Not classified	Human	NOAEL 1.19 mg/l	6 days
Acetone	Inhalation	kidney and/or bladder	Not classified	Guinea pig	NOAEL 119 mg/l	not available
Acetone	Inhalation	heart	Not classified	Rat	NOAEL 45 mg/l	8 weeks
Acetone	Inhalation	liver	Not classified	Rat	NOAEL 45 mg/l	8 weeks
Acetone	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 900 mg/kg/day	13 weeks
Acetone	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 200 mg/kg/day	13 weeks

Acetone	Ingestion	liver	Not classified	Mouse	NOAEL 3,896 mg/kg/day	14 days
Acetone	Ingestion	eyes	Not classified	Rat	NOAEL 3,400 mg/kg/day	13 weeks
Acetone	Ingestion	respiratory system	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Acetone	Ingestion	muscles	Not classified	Rat	NOAEL 2,500 mg/kg	13 weeks
Acetone	Ingestion	skin	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Acetone	Ingestion	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
Poly(Dimethylsiloxane)	Ingestion	eyes	Not classified	Rat	NOAEL 10%	90 days
Poly(Dimethylsiloxane)	Ingestion	respiratory system	Not classified	Rat	NOAEL 1%	90 days
Poly(Dimethylsiloxane)	Ingestion	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 10%	90 days
Poly(Dimethylsiloxane)	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 10%	90 days
Poly(Dimethylsiloxane)	Ingestion	heart	Not classified	Rat	NOAEL 1%	90 days
Poly(Dimethylsiloxane)	Ingestion	liver	Not classified	Rat	NOAEL 1%	90 days
Poly(Dimethylsiloxane)	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1%	90 days
Poly(Dimethylsiloxane)	Ingestion	vascular system	Not classified	Rat	NOAEL 1%	90 days
Methylcyclohexane	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 8 mg/l	1 years
Methylcyclohexane	Inhalation	heart	Not classified	Rat	NOAEL 8 mg/l	1 years
Methylcyclohexane	Inhalation	skin	Not classified	Rat	NOAEL 8 mg/l	1 years
Methylcyclohexane	Inhalation	endocrine system	Not classified	Rat	NOAEL 8 mg/l	1 years
Methylcyclohexane	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 8 mg/l	1 years
Methylcyclohexane	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 8 mg/l	1 years
Methylcyclohexane	Inhalation	liver	Not classified	Rat	NOAEL 8 mg/l	1 years
Methylcyclohexane	Inhalation	immune system	Not classified	Rat	NOAEL 8 mg/l	1 years
Methylcyclohexane	Inhalation	nervous system	Not classified	Rat	NOAEL 8 mg/l	1 years
Methylcyclohexane	Inhalation	respiratory system	Not classified	Rat	NOAEL 8 mg/l	1 years
Methylcyclohexane	Ingestion	endocrine system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Methylcyclohexane	Ingestion	hematopoietic system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Methylcyclohexane	Ingestion	liver	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Methylcyclohexane	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Methylcyclohexane	Ingestion	heart	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Methylcyclohexane	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Methylcyclohexane	Ingestion	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Methylcyclohexane	Ingestion	immune system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Methylcyclohexane	Ingestion	muscles	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Methylcyclohexane	Ingestion	nervous system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Methylcyclohexane	Ingestion	eyes	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Methylcyclohexane	Ingestion	respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days

Aspiration Hazard

Name	Value
Hydrotreated Light Naphtha (Petroleum)	Aspiration hazard
Methylcyclohexane	Aspiration hazard
Solvent Naphtha (Petroleum), Light Aliphatic	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Facility must be capable of handling aerosol cans. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The

components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 **Flammability:** 4 **Instability:** 0 **Special Hazards:** None
Aerosol Storage Code: 3

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	26-7363-0	**Version number:**	5.06
Issue Date:	2026/09/25	**Supersedes Date:**	2026/01/06

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca